





## FHEM12









## Thermoplastic Adjustable LED Emergency Lights


- Push to test switch
- LED charge indicator
- Long life LED lamps
- Fully adjustable glare free lighting heads
- Wet location option available


- Universal mounting pattern knockouts in backplate for J-Box mounting
- Snap fit construction speeds installation
- Dual voltage 120V/277V
- UL listed in accordance with UL924
- Maintenance Free 3.6v NiCd Battery

<b>General Specifications</b>
Innut Voltage

Input Voltage	120/277VAC
Input Current (120V)	186mA
Input Current (277V)	12mA
Input Power (120V)	3.32W
Input Power (277V)	3.3W
Operating Frequency	60Hz
Operating Ambient Temperature Range (Ta)	Ambient temperature rating: 10°C to 40°C.
Overall Size	12.30" L x 4.90" H (Common)
	13.33" L x 5.76" H (Water Proof)
Emergency Operation	90 minutes
Compliance	UL 924 Listed
	Damp Location (Common)
	Wet Location (Water Proof)
Warranty	5 years from the date of manufacture

## **Mechanical Data**





**FRONT VIEW** 

SIDE VIEW

## **Part Number Matrix**

FHEM12



**Housing Color** W = White

**Options** Blank = Common W = Water Proof