




GE
Lighting

63050 - GEMH175MVA-F

GE HID Magnetic HID Metal Halide Enclosed and Potted F-Can Ballast

- For applications requiring quieter or cooler operation than provided by standard coil & coil ballasts.
- Excellent sound-deadening and heat transfer qualities.
- Reliable low-temperature starting-as low as -20F.



CAUTIONS & WARNINGS

Warning

- Risk of Electric Shock
 - Properly ground ballast and fixture.
 - Turn power off before servicing--see instructions.

GENERAL CHARACTERISTICS

Lamp Type	HID -
Bulb	Magnetic
Ballast Type	HID Metal Halide Enclosed and Potted F-Can
Starting Method	Probe Start
Line Voltage Regulation (+/-) (NOM)	5.0 %
Ambient Temperature (MIN)	-30.0 °F
Ambient Temperature (MAX)	105.0 °C
Case Temperature (MAX)	90.0 °C
Ballast Factor	Normal
Circuit Type	HX-HPF
Insulation Class	A
Enclosure Type	Metal Can
Distance to Lamp (MAX)	10.0 ft
Additional Info	Thermally protected
Primary Application	Indoor/Outdoor;Grocery Display;Hospitality;Office;Restaurant;Refrigerator;Warehouse

ELECTRICAL CHARACTERISTICS

Lamp Operating Frequency (NOM)	60.0 Hz
Supply Current Frequency (NOM)	60.0 Hz

DIMENSIONS

Weight (NOM)	12.97 lb
Exit Type	
Remote Mounting Distance (NOM)	10.0 ft

PRODUCT INFORMATION

Product Code	63050
Description	GEMH175MVA-F
Standard Package	Case
Standard Package GTIN	10043168630501
Standard Package Quantity	2
Sales Unit	Individual Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	2
UPC	043168630504