

34279 - Integrated 4ft LED Glass Tubes

LED10ET8/G/4/835

- ☞ Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall.
- ☞ Each LED tube is outfitted with an internal GE driver.
- ☞ The GE integrated LED tubes run on electronic T8 instant-start or programmed start ballasts.
- ☞ 2.3x longer life than LFL (70 000 vs. 30 000 hours)
- ☞ No UV
- ☞ Easy disposal non-hazardous waste
- ☞ UL Listed
- ☞ DLC rated
- ☞ Check ballast compatibility at www.gelighting.com/LEDTUBES-ballast-compatibility

PRODUCT PHOTO



GENERAL CHARACTERISTICS

Base Description	LED_Bs_G13
Base Type	G13
Dimmable	Yes (with compatible dimming ballasts)
Product Technology	LED
Rated Life (Hours)	70000 h
Dimmable / Non-Dimmable	No
Lamp Count	1
Life in Years	63.9 yr
Requested Structure	Carton
Estimated Energy Cost per Year	1.2
Bulb Shape	T8

PHOTOMETRIC CHARACTERISTICS

Nominal Initial Lumen per Watt	160
Initial Lumens-nominal	1600 lm
Color Rendering Index-CRI	80
Color Temperature	3500 K

PRODUCT INFORMATION

Product Code	34279
Description	LED10ET8/G/4/835
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168342797
Standard Package GTIN	00043168342797
No Of Items Per Sales Unit	
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	
Alternative Unit Of Measure	CASE
Standard Package Quantity	20
Ean UPC	043168342797
Standard Package GTIN	10043168342794
No Of Items Per Sales Unit	
No Of Items Per Standard Package	20
Sales Unit	Case
UCC	

DIMENSIONS

Bulb Max Overall Length-MOL	48.0 in
-----------------------------	---------

ELECTRICAL CHARACTERISTICS

Rated power (Watts)	10 W
---------------------	------