

# 34401 - Integrated 3ft LED Glass Tubes T5 HE

#### LED10ET5G3/840HE

- Required T5 HE Ballast
- Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall.
- Each LED tube is outfitted with an internal GE driver.
- The GE integrated LED tubes run on electronic T5 instant-start or programmed start ballasts.
- Longer life than LFL (50 000 vs. 30 000 hours)
- Easy disposal non-hazardous waste
- UL Listed

# **PRODUCT PHOTO**



# **GENERAL CHARACTERISTICS**

Base Description LED\_Bs\_G5

Base Type G5

Dimmable Yes (with compatible dimming

ballasts)

Product Technology
Rated Life (Hours)
50000 h
Dimmable / Non-Dimmable
Lamp Count
Life in Years
Requested Structure
Estimated Energy Cost per Year
Bulb Shape
LED
45.7 yr
45.7 yr
75.7 yr
75.7

### PHOTOMETRIC CHARACTERISTICS

Nominal Initial Lumen per Watt 160
Initial Lumens-nominal 1600 lm
Color Rendering Index-CRI 80
Color Temperature 4000 K

# PRODUCT INFORMATION

Product Code 34401

Description LED10ET5G3/840HE

Alternative Unit Of Measure CASE Standard Package Quantity 20

Ean UPC 043168344012 Standard Package GTIN 10043168344019

No Of Items Per Sales Unit

No Of Items Per Standard Package 20 Sales Unit Case

UCC

Alternative Unit Of Measure EACH Standard Package Quantity 1

Ean UPC 043168344012 Standard Package GTIN 00043168344012

No Of Items Per Sales Unit

No Of Items Per Standard Package 1
Sales Unit Each

UCC

### **DIMENSIONS**

Bulb Max Overall Length-MOL 34.0 in

# **ELECTRICAL CHARACTERISTICS**

Rated power (Watts) 10 W

 $Mar\ 19, 2020\ 2:28:04\ PM\ |\ For\ additional\ information,\ visit\ products. current by ge.com$