

34412 - Integrated 2ft LED Glass Tubes T5 HE

LED7ET5/G2/850HE

- ➡ Required T5 HE Ballast
- ➡ Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall.
- ➡ Each LED tube is outfitted with an internal GE driver.
- ➡ The GE integrated LED tubes run on electronic T5 instant-start or programmed start ballasts.
- ➡ Longer life than LFL (50 000 vs. 30 000 hours)
- ➡ Easy disposal non-hazardous waste
- ➡ UL Listed

PRODUCT PHOTO



GENERAL CHARACTERISTICS

Base Description	LED_Bs_G5
Base Type	G5
Dimmable	Yes (with compatible dimming ballasts)
Product Technology	LED
Rated Life (Hours)	50000 h
Dimmable / Non-Dimmable	No
Lamp Count	1
Life in Years	45.7 yr
Requested Structure	Carton
Estimated Energy Cost per Year	0.84
Bulb Shape	T5

PHOTOMETRIC CHARACTERISTICS

Nominal Initial Lumen per Watt	164
Initial Lumens-nominal	1150 lm
Color Rendering Index-CRI	80
Color Temperature	5000 K

PRODUCT INFORMATION

Product Code	34412
Description	LED7ET5/G2/850HE
Alternative Unit Of Measure	CASE
Standard Package Quantity	20
Ean UPC	043168344128
Standard Package GTIN	10043168344125
No Of Items Per Sales Unit	
No Of Items Per Standard Package	20
Sales Unit	Case
UCC	
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168344128
Standard Package GTIN	00043168344128
No Of Items Per Sales Unit	
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	

DIMENSIONS

Bulb Max Overall Length-MOL	22.0 in
-----------------------------	---------

ELECTRICAL CHARACTERISTICS

Rated power (Watts)	7 W
---------------------	-----