



GE  
Lighting

## 63052 - GEMH400MVA-F

GE HID Magnetic HID Metal Halide Enclosed and Potted F-Can Ballast

- For applications requiring quieter or cooler operation than provided by standard coil & coil ballasts.
- Excellent sound-deadening and heat transfer qualities.
- Reliable low-temperature starting-as low as -20F.

## GENERAL CHARACTERISTICS

Application	1-400W M59 120/277 Enclosed and Potted F-Can for HID Metal Halide Lamps
Category	High Intensity Discharge
Ballast Type	Magnetic - HID Metal Halide Enclosed and Potted F-Can
Starting Method	Probe Start
Line Voltage Regulation (+/-) (NOM)	5.0 %
Ambient Temperature (MIN)	-30.0 °F
Ambient Temperature (MAX)	105.0 °C ( 41 °C)
Case Temperature (MAX)	90.0 °C
Ballast Factor	Normal
Circuit Type	HX-HPF
Insulation Class	A
Enclosure Type	Metal Can
Distance to Lamp (MAX)	10.0 ft
Additional Info	Thermally protected
Primary Application	Indoor/Outdoor

## PRODUCT INFORMATION

Product Code	63052
Description	GEMH400MVA-F
Standard Package	Case
Standard Package GTIN	10043168630525
Standard Package Quantity	2
Sales Unit	Individual Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	2
UPC	043168630528

## DIMENSIONS

Case dimensions			
Length (L)		21.6 in( 548.64 mm)	
Width (W)		3.2 in( 82.04 mm)	
Height (H)		2.8 in( 69.85 mm)	
Mounting dimensions			
Bracket Length (BL)		NaN in( NaN mm)	
Mount Length (M)		21.0 in( 533.40 mm)	
Mount Width (X or F)		NaN in( NaN mm)	
Mount Slots (MS)		NaN in( NaN mm)	
Weight (NOM)		23.69 lb	
Exit Type		Side	
Remote Mounting Distance (NOM)		10.0 ft	
Lead lengths	Qty	Exit	Length (± 1 in.)
Black	1	Left	12 ( 305 mm)
Black/Yellow	1	Left	12 ( 305 mm)
Red	1	Right	12 ( 305 mm)
White	1	Left	12 ( 305 mm)

## ELECTRICAL CHARACTERISTICS

Lamp Operating Frequency (NOM)	60.0 Hz
Supply Current Frequency (NOM)	60.0 Hz

## SAFETY & PERFORMANCE

- UL Listed
- UL type 1
- Indoor/Outdoor

## SPECIFICATIONS BY LAMP & LINE VOLTAGE

Lamp	# of Lamps by Line Voltage	Specifications	System Wattage	Nominal Current	Ballast Factor	Ballast Efficiency	Max.Input Current	Starting Current	Open Circuit Voltage	Drop Out Voltage	Power factor	Min.starting temperature	Fuse rating	UL bench top rise
M59	1	120	445.0	3.93 A A		0.899	NaN A	NaN A	NaN V	NaN V		-30.0 °C °F		
M59	1	277	446.0	1.7 A A		0.897	NaN A	NaN A	NaN V	NaN V		-30.0 °C °F		

## CAUTIONS & WARNINGS

### Warning

- Risk of Electric Shock
  - Properly ground ballast and fixture.
  - Turn power off before servicing--see instructions.

**WARRANTY INFORMATION**

GE Lighting warrants to the purchaser that each ballast will be free from defects in material or workmanship for period as defined in the attached documents from the date of manufacture when properly installed and under normal conditions of use.