



GE
Lighting

73232 - GE LFL UltraMax™ Load Shed 0-10V Dimming Electronic Dimming Ballast

GE332MAX90-V60

- ☞ Load Shed Variable Dimming 0-10V 100% to 60%
- ☞ Anti-Striation Control for better light quality, with no striations.
- ☞ UL 55C Ambient Rating - High Temperature Protection Circuit
- ☞ Multi-Voltage Technology handles voltage from 120 to 277V
- ☞ UL Type CC Rating provides protection against arcing in electrical devices.
- ☞ Cold temperature -22F Minimum Starting Temperature

Product Photo



GENERAL CHARACTERISTICS

Ballast Factor	High (1.18)
Ballast Type	Dimming
Case Temperature (Max)	70 °C
Dimming Type	Continuous
Enclosure Type	Metal
Line Voltage Regulation (+/-)	10%
Classification (Regulations)	cUL Listed
	UL Type 1 Outdoor
	UL Type CC
	UL Type HL
	Meets ANSI Standard C82.11-Cons 2002
	Meets ANSI Standard C62.41-1991
	FCC Part 18 (Class A) for EMI and RFI Non-Consumer Limits
	High Temperature Rated: Suitable for high temperature applications
	70C max case temp 5 yr warranty or 90C max case temp 3 yr warranty
	Complies with ANSI C82.11 Annex A Specification for Low Voltage Control Interface for Controllable Ballasts
	Class 1 or 2 Circuit 10V
	0.5mA
	Product is compliant with material restriction requirements of RoHS
	A (20-24 decibels)
Sound Rating	Instant start
Starting Method	Linear Fluorescent
Product Technology	Parallel
Lamp Wiring	Active
Power Factor Correction	

PRODUCT INFORMATION

Product Code	73232
Description	GE332MAX90-V60
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168732321
Standard Package GTIN	10043168732328
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168732321
Alternative Unit Of Measure	EACH
Standard Package Quantity	10
Ean UPC	043168732321
Standard Package GTIN	00043168732321
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
Sales Unit	Each
UCC	043168732321

DIMENSIONS

Weight	1.4 lb
Exit Type	
Remote Mount Distance	6.0 ft

Case Dimensions

Length	9.5in
Width	1.7in
Height	1.18in

Mounting Dimensions

Mount Length	8.89in
Mount Width	1.13in
Mount Slot	0.312in

Lead Color	Qty	Exit	Length (1 in.)
Blue	3	Right	34in
Violet	1	Left	25in
Red	1	Right	34in
Gray	1	Left	25in
Yellow	1		41in
Black	1	Left	25in
White	1	Left	25in

ELECTRICAL CHARACTERISTICS

Supply Current Frequency<Min>	60
-------------------------------	----

SAFETY & PERFORMANCE

-  cUL_Listed
-  UL_Type1_Out
-  UL_Type_CC
-  UL_Type_HL
-  Meets_2002
-  Meets_1991
-  FCC_Part_18_Limits
-  High_Temp_App
-  C_max_wty_temp

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)	Crest Factor (<=)	THD% (<=)	Min. Starting Temp (F/ C)
F17T8	2	120	47	0.41	1.27	3	0.99	1.4	10	
F17T8	2	277	47	0.2	1.27	3	0.91	1.4	21	
F17T8	3	120	61	0.54	1.15	2	0.99	1.4	10	
F17T8	3	277	60	0.24	1.15	2	0.95	1.4	17	
F17T8	2	120	104	0.87	1.22	1	0.99	1.4	10	-22
F17T8	2	277	102	0.38	1.22	1	0.97	1.4	10	-22
F17T8	2	120	85	0.72	1.29	2	0.99	1.4	10	-22
F17T8	2	277	84	0.32	1.29	2	0.97	1.4	13	-22
F17T8	3	120	113	0.94	1.18	1	0.99	1.4	10	-22
F17T8	3	120	66	0.55	0.71	1	0.99	1.4	10	-22
F17T8	3	277	110	0.41	1.18	1	0.97	1.4	10	-22
F17T8	3	277	65	0.25	0.71	1	0.94	1.4	17	-22
F17T8	2	120	73	0.61	1.26	2	0.99	1.4	10	-22
F17T8	3	277	94	0.35	1.18	1	0.96	1.4	13	60
F17T8	2	277	72	0.27	1.26	2	0.95	1.4	16	-22
F17T8	3	120	95	0.81	1.18	1	0.99	1.4	10	60
F17T8	2	120	79	0.67	1.26	2	0.99	1.4	10	60
F17T8	2	277	78	0.3	1.26	2	0.96	1.4	16	60
F17T8	3	277	102	0.38	1.18	1	0.97	1.4	10	60
F17T8	3	120	104	0.91	1.18	1	0.99	1.4	10	60
F17T8	2	120	69	0.57	1.26	2	0.99	1.4	10	60
F17T8	2	277	68	0.26	1.26	2	0.95	1.4	17	60
F17T8	3	277	89	0.33	1.18	1	0.96	1.4	16	60
F17T8	3	120	91	0.77	1.18	1	0.99	1.4	10	60
F32T8/WM	3	120	72	0.61	0.78	1	0.99	1.4	10	60
F32T8/WM	3	277	71	0.28	0.78	1	0.94	1.4	17	60
F28T8	3	120	71	0.64	0.87	1	0.99	1.4	10	60
F28T8	3	277	70	0.28	0.87	1	0.93	1.4	17	60
F32T8/25W	3	120	71	0.63	0.89	1	0.99	1.4	10	60
F32T8/25W	3	277	70	0.28	0.89	1	0.93	1.4	17	60
F17T8	3	120	58	0.51	1.14	2	0.99	1.4	10	
F17T8	3	277	58	0.23	1.14	2	0.94	1.4	17	
F40T8	2	120	66	0.61	0.68	1	0.99	1.4	10	-22

F32T8	2	120	72	0.62	1.05	1	0.99	1.4	10	-22
F40T8	2	277	65	0.27	0.68	1	0.96	1.4	14	-22
F32T8	2	277	72	0.28	1.05	1	0.93	1.4	18	-22
F32T8/WM	2	120	65	0.61	1.07	2	0.99	1.4	10	60
F32T8/WM	2	277	65	0.27	1.07	2	0.93	1.4	18	60
F28T8	2	120	68	0.57	1.1	2	0.99	1.4	10	-22
F28T8	2	277	67	0.25	1.1	2	0.93	1.4	18	-22
F32T8/25W	2	277	63	0.24	1.15	2	0.93	1.4	17	60
F32T8/25W	2	120	64	0.54	1.15	2	0.99	1.4	10	60
F17T8	2	120	45	0.4	1.25	3	0.99	1.4	10	
F17T8	2	277	45	0.19	1.25	3	0.91	1.4	20	

