



GE
Lighting

78528 - GE HID Distributor Replacement Kit Magnetic Core & Coil Ballast

GEP320TRIAC4-5

- Magnetic ballast construction ideal for a wide variety of lighting applications.
- Precision-wound coils, ensuring even heat dissipation and the highest electrical integrity.
- Distributor replacement kit contains the appropriate core & coil with color coded leads, a properly rated capacitor and ignitor (if required) and all other components required for ballast replacement
- Tri-Tap ballast (120, 277, 347)

Product Photo



GENERAL CHARACTERISTICS

Ambient Temp [Max]	200 °C
Ballast Factor	Normal
Ballast Type	Core and Coil
Capacitor Temp Rating	105 °C
Case Temperature (Max)	105 °C
Circuit Type	CWA
Insulation Class	200C
Line Voltage Regulation (+/-)	10%
Classification (Regulations)	cUL Listed UL Listed
Starting Method	Pulse start
Type	Replacement kit
Type of Capacitor	Oil filled
Product Technology	High Intensity Discharge

PRODUCT INFORMATION

Product Code	78528
Description	GEP320TRIAC4-5
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168785280
Standard Package GTIN	10043168785287
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168785280
Alternative Unit Of Measure	PACK
Standard Package Quantity	
Ean UPC	043168785280
Standard Package GTIN	30043168785281
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Inner Pack
UCC	043168785280

DIMENSIONS

Diameter	2.0
Weight	11.02 lb
Exit Type	

ELECTRICAL CHARACTERISTICS


Capacitance	21
Supply Current Frequency<Min>	60
Voltage<Min>	450 V



SAFETY & PERFORMANCE

- cUL_Listed
- UL_Listed

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)	Crest Factor (<=)	THD% (<=)	Min. Starting Temp (F/ C)
M132	1	120	375	3.2	1.0		90.0			-40
M132	1	277	375	1.4	1.0		90.0			-40
M154	1	120	375	3.2	1.0		90.0			-40
M154	1	277	375	1.4	1.0		90.0			-40
M132	1	347	375	1.1	1.0		90.0			-40
M154	1	347	375	1.1	1.0		90.0			-40





Feb 13, 2018 1:48:18 PM For additional information, visit www.gelighting.com