

78535 - GE HID Distributor Replacement Kit Magnetic Core & Coil Ballast

GES100TRILC3-5

- Magnetic ballast construction ideal for a wide variety of lighting applications.
- Precision-wound coils, ensuring even heat dissipation and the highest electrical integrity.
- Distributor replacement kit contains the appropriate core & coil with color coded leads, a properly rated capacitor and ignitor (if required) and all other components required for ballast replacement
- Tri-Tap ballast (120, 277, 347)

Product Photo



GENERAL CHARACTERISTICS

200 °C Ambient Temp [Max] **Ballast Factor** Normal Core and Coil **Ballast Type** Capacitor Temp Rating 105 °C Case Temperature (Max) 105 °C Circuit Type HX-HPF Insulation Class 200C Line Voltage Regulation (+/-) Classification (Regulations) cUL Listed

Type UL Listed Replacement kit

Type of Capacitor Oil filled

Product Technology High Intensity Discharge

PRODUCT INFORMATION

Product Code 78535

Description GES100TRILC3-5

Alternative Unit Of Measure CASE

Standard Package Quantity

Ean UPC 043168785358 Standard Package GTIN 0043168785355

No Of Items Per Sales Unit

No Of Items Per Standard Package

Sales Unit Case

UCC 043168785358
Alternative Unit Of Measure PACK

Standard Package Quantity

Ean UPC 043168785358 Standard Package GTIN 30043168785359

No Of Items Per Sales Unit

No Of Items Per Standard Package

Sales Unit Inner Pack
UCC 043168785358

DIMENSIONS

Diameter 1.8 Weight 6.38 lb

Exit Type

ELECTRICAL CHARACTERISTICS

Capacitance 10
Supply Current Frequency<Min> 60
Voltage<Min> 300 V


SAFETY & PERFORMANCE


CUL_Listed
UL_Listed

| SPECIFICATIONS BY LAMP & WATTAGE | | | | | | | | | | |
|----------------------------------|------------|------------|-----------------|----------------------|-----------------------------|-------------------------------|-----------------------|----------------------|-----------|-----------------------------|
| Lamp | # of Lamps | Line Volts | System Watts | Nom. Line Current | System Ballast Factor | Ballast Efficacy Factor | Power Factor% (>=) | Crest Factor (<=) | THD% (<=) | Min. Starting Temp (F/C) |
| S54 High Pressure Sodium | 1 | 120 | 129 | 1.16 | 1.0 | | 90.0 | | | -40 |
| S54 High Pressure Sodium | 1 | 347 | 129 | 0.4 | 1.0 | | 90.0 | | | -40 |
| S54 High Pressure Sodium | 1 | 277 | 129 | 0.5 | 1.0 | | 90.0 | | | -40 |









Feb 13, 2018 2:19:24 PM For additional information, visit www.gelighting.com