



GE
Lighting

93907 - GE F32T825SXLSPX50E

F32T825W/SXL/SPX50/ECO

- ☞ Saves energy compared to standard wattage lamps
- ☞ Passes TCLP, which can lower disposal costs.

Product Photo



GENERAL CHARACTERISTICS

| | |
|-------------------------------|---------------------------------|
| Base Description | Medium Bi-Pin |
| Base Type | Pin/Plug-In |
| Mercury Content | 3.95 mg |
| Rated Life Instant Start-Hrs | 50000 h @ 3 h 70000 h @ 12 h |
| Rated Life Rapid Start - Hrs | 80000 h @ 3 h 84000 h @ 12 h |
| Starting Temp (MIN) C-degrees | 15 °C |
| Bulb Material | Soda lime |
| Rated Life Hours-nominal | 80000 h |
| Primary Application | Energy Saving |
| Product Technology | Linear Fluorescent |
| Base | G13 |
| Bulb Shape | T8 |

PHOTOMETRIC CHARACTERISTICS

| | |
|--------------------------------|---------|
| Mean Lumens nominal | 2250 lm |
| Nominal Initial Lumen per Watt | 96 |
| Initial Lumens-nominal | 2400 lm |
| Color Rendering Index-CRI | 82 |
| Color Temperature | 5000 K |

PRODUCT INFORMATION

| | |
|----------------------------------|------------------------|
| Product Code | 93907 |
| Description | F32T825W/SXL/SPX50/ECO |
| Alternative Unit Of Measure | CASE |
| Standard Package Quantity | |
| Ean UPC | 043168939072 |
| Standard Package GTIN | 10043168939079 |
| No Of Items Per Sales Unit | |
| No Of Items Per Standard Package | |
| Sales Unit | Case |
| UCC | 043168939072 |

DIMENSIONS

| | |
|---------------------------------------|----------|
| Bulb Diameter (DIA) <Min> | 0.94 in |
| Diameter | 1.0 in |
| End of Base Pin to Pin | 47.67 in |
| Face to End of Opposing Pin (B) <Max> | 47.5 in |
| Face to End of Opposing Pin (B) <Min> | 47.4 in |
| Nominal Length | 48.0 in |

ELECTRICAL CHARACTERISTICS

| | |
|---|------------------|
| Current Crest Factor (MAX) | 1.7 |
| Open Circuit Voltage (instant start) Min @ Temperature | 550.00 V @ 15 °C |
| Cathode Resistance Ratio - Rh/Rc (MIN) | 4.250 |
| Cathode Resistance Ratio - Rh/Rc (MAX) | 6.500 |
| Rated power (Watts) | 25 W |