



GE
Lighting

94843 - null

F32T8SPX65ECO/CVG

- ☞ A shatter resistant lamp encased in a 0.015" Lexan® polycarbonate sleeve.
- ☞ Meets FDA food code 6-202 and 21CFR 110.20 regulations.
- ☞ Compliant with NSF/ANSI2 Standards for Food Equipment and UL2007A Shatter Containment of Lamps for Use in Regulated Food Establishments.
- ☞ Blocks UV lamp emissions up to 380nm.

Product Photo



GENERAL CHARACTERISTICS

Base Description	Medium Bi-pin
Base Type	Pin/Plug-in
Mercury Content	2.95 mg
Mercury-Picogram per mean lm hr	36.8
Rated Life Instant Start-Hrs	30000
Rated Life Rapid Start - Hrs	30000
Starting Temp (MIN) C-degrees	10 °C
Bulb Material	Soda lime
Product Technology	Linear Fluorescent
Base	G13
Bulb Shape	T8

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	2670 lm
Nominal Initial Lumen per Watt	87.5
Initial Lumens-nominal	2800 lm
Color Rendering Index-CRI	78
Color Temperature	6500 K

PRODUCT INFORMATION

Product Code	94843
Description	F32T8SPX65ECO/CVG
Alternative Unit Of Measure	EACH
Standard Package Quantity	36
Ean UPC	043168948432
Standard Package GTIN	00043168948432
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	36
Sales Unit	Each
UCC	043168948432
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168948432
Standard Package GTIN	10043168948439
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168948432

DIMENSIONS

Diameter	1.0 in
Bulb Max Overall Length-MOL	48.0 mm