

awaken



LED replacement lamps



ecomagination

current
powered by GE



Exceeding Expectations

Why Use GE LED Lamps?


COMPLETE



From LFL to HID and everything in between, GE has a full family of LED lamp replacements for almost every lighting need. All designed by GE engineers.

How We Do It

Outcomes We Drive



Breadth & Depth



One-Stop Shop

INNOVATIVE



With Plug & Play simplicity and color enhancing technologies, GE engineers design cutting-edge lamps that allow LEDs to go places they have never gone before.



System Expertise



Patented Color Enhancement



Drive Top Line & Bottom Line

TRUSTED



When it comes to LED lamps that last up to 50,000 hours, quality and reliability really matter. GE has been designing lamps for over 100 years and backs all LEDs with a limited warranty that you can trust.



In-House Testing



Measuring What Matters



Savings With Confidence



LED replacement lamps

Decorative Lamps

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (in)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information	
Candles																		
	MED	4	75554	LED4DCAMCF/824	120	6	4.2	250		2400	80	25W	15,000	Yes		Damp	Clear, Bent tip	
			21250	LED4DCAM-C3/827	120	6	4.2	300		2700	80	40W	15,000	Yes	★	Damp	Clear, Bent tip	
			69111	LED4DCAM-C3/850	120	6	4.2	300		5000	80	40W	15,000	Yes	★	Damp	Clear, Bent tip	
		4.2	92389	LED4DCAM-W3/827	120	6	4.2	300		2700	80	40W	15,000	Yes	★	Damp	White, Bent tip	
7		21251	LED7DCAM-C3/827	120	6	4.8	500		2700	80	60W	15,000	Yes	★	Damp	Clear, Bent tip		
CAND		4	75553	LED4DCACCF/824	120	6	4.3	250		2400	80	25W	15,000	Yes		Damp	Clear, Bent tip	
			21231	LED4DCAC-C3/827	120	6	4.3	300		2700	80	40W	15,000	Yes	★	Damp	Clear, Bent tip	
		69109	LED4DCAC-C3/850	120	6	4.3	300		5000	80	40W	15,000	Yes	★	Damp	Clear, Bent tip		
	4.2	97230	LED4DCAC-W3/OTB	120	4	4.3	300		2700	80	40W	15,000	Yes	★	Damp	White, Bent tip		
	7	21233	LED7DCAC-C3/827	120	6	4.8	500		2700	80	60W	15,000	Yes	★	Damp	Clear, Bent tip		
Globes																		
	G25	MED	4.5	39935	LED4DG25-C3-OT	120	3	4.3	290		2700	82	25W	15,000	Yes	★	Damp	Clear
				21253	LED5DG25-W3/827	120	6	4.3	350		2700	80	40W	15,000	Yes	★	Damp	White
			7	21255	LED7DG25-W3/827	120	6	4.3	500		2700	80	60W	15,000	Yes	★	Damp	White
	G16	CAND	3.5	28297	LED3DG16-AGC-2	120	6	3.0	250		2700	80	25W	15,000	Yes		Damp	Clear
				28280	LED3DFG16-GW-2T	120	6	3.0	250		2700	80	25W	15,000	Yes		Damp	Frosted

Filament Lamps

Filament Lamps

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (in)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
Candles																	
	MED	3	76018	LED3DST19-V	120	6	5	200		2500		25W	15,000	Yes		Damp	Vintage Filament
		5	33024	LED5DST19-V-OT	120	8	5	440		2500		40W	15,000	YES		Damp	Vintage Filament
	MED	3	75914	LED3DCAM-V	120	6	4.4	300		2500	80	40W	15,000	Yes		Damp	Bent Tip, Vintage Filament
	CAND		33027	LED3DCAC-V-OT	120	4	4.4	300		2500	80	40W	15,000	Yes		Damp	Bent Tip, Vintage Filament

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "7TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at
<http://products.currentbyge.com>.

LED replacement lamps

A-Line Lamps

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
A-15																	
	MED	4	34038	LED4DA15-W3/827	120	6	3.5	300		2700	80	40W	15,000	Yes		Damp	White
			34051	LED4DA15-C3/827	120	6	3.5	300		2700	80	40W	15,000	Yes		Damp	Clear
A-19																	
	MED	6	69115	LED6DA19/827	120	6	4.4	480		2700	80	40W	15,000	Yes	★	Damp	White, Omnidirectional
			69118	LED6DA19/830	120	6	4.4	480		3000	80	40W	15,000	Yes	★	Damp	White, Omnidirectional
			69132	LED6DA19/840	120	6	4.4	480		4000	80	40W	15,000	Yes	★	Damp	White, Omnidirectional
			69144	LED6DA19/850	120	6	4.4	480		5000	80	40W	15,000	Yes	★	Damp	White, Omnidirectional
	10		69117	LED10DA19/827	120	6	4.4	800		2700	80	60W	15,000	Yes	★	Damp	White, Omnidirectional
			69119	LED10DA19/830	120	6	4.4	800		3000	80	60W	15,000	Yes	★	Damp	White, Omnidirectional
			69133	LED10DA19/840	120	6	4.4	800		4000	80	60W	15,000	Yes	★	Damp	White, Omnidirectional
			69146	LED10DA19/850	120	6	4.4	800		5000	80	60W	15,000	Yes	★	Damp	White, Omnidirectional
			GU24	38220	LED10DA19GU24827	120	6	4.4	800	2700	80	60W	15,000	Yes		Damp	White, Omnidirectional
A-21																	
	MED	12	76037	LED12DA21/827	120	6	5.16	1100		2700	80	75W	15,000	Yes	★	Damp	White, Omni, ES 2.0
			76041	LED12DA21/830	120	6	5.16	1100		3000	80	75W	15,000	Yes	★	Damp	White, Omni, ES 2.0
			76045	LED12DA21/840	120	6	5.16	1100		4000	80	75W	15,000	Yes	★	Damp	White, Omni, ES 2.0
			76102	LED12DA21/850	120	6	5.16	1100		5000	80	75W	15,000	Yes	★	Damp	White, Omni, ES 2.0
			73404	LED12DA21/850FE	120	6	5.31	1100		5000	80	75W	25,000	Yes		Enclosed	White, Enclosed, Omni
			73384	LED12DA21/830FE	120	6	5.31	1100		3000	80	75W	25,000	Yes		Enclosed	White, Enclosed, Omni
		15	76038	LED15DA21/827	120	6	5.16	1600		2700	80	100W	15,000	Yes	★	Damp	White, Omni, ES 2.0
			76043	LED15DA21/830	120	6	5.16	1600		3000	80	100W	15,000	Yes	★	Damp	White, Omni, ES 2.0
			76060	LED15DA21/840	120	6	5.16	1600		4000	80	100W	15,000	Yes	★	Damp	White, Omni, ES 2.0
			76117	LED15DA21/850	120	6	5.16	1600		5000	80	100W	15,000	Yes	★	Damp	White, Omni, ES 2.0
		GU24	16	92498	LED16DA21827GU24	120	6	5.43	1600	2700	80	100W	25,000	Yes		Damp	White, Omnidirectional
		MED	16	73376	LED16A30/100/827	120	6	5.31	360/1400/900	2700	80	30/70/100	25,000	-	★	Damp	White, 3-Way
		92118	LED16A30/100/5KB	120	3	5.31	360/1400/900	5000	80	30/70/100	25,000	-	★	Damp	White, 3-Way		
		19	38563	LED19A50/150/827	120	6	5.31	650/2155/1300	2700	80	50/100/150	15,000	-	-	Damp	White, 3-Way	
22	92120	LED22A50/150/5KB	120	3	5.31	700/2155/1600	5000	80	50/100/150	25,000	-	-	Damp	White, 3-Way			

LED Bright Stik™

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (in)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
LED Bright Stik™																	
	Med	5.5	66256	LED5.5LS3/827	120	48	4.45	450		2700	80	40W	15,000	-	★	Damp	Case = 16 3-pack
			75177	LED5.5LS3/850	120	48	4.45	450		5000	80	40W	15,000	-	★	Damp	Case = 16 3-pack
		9	75184	LED9LS3/827	120	48	4.45	800		2700	80	60W	15,000	-	★	Damp	Case = 16 3-pack
			75588	LED9LS3/850	120	48	4.45	800		5000	80	60W	15,000	-	★	Damp	Case = 16 3-pack
		12	75590	LED12LS2/827	120	32	5.24	1100		2700	80	75W	15,000	-	★	Damp	Case = 16 2-pack
			75591	LED12LS2/850	120	32	5.24	1100		5000	80	75W	15,000	-	★	Damp	Case = 16 2-pack
		15	75593	LED15LS2/827	120	32	5.24	1600		2700	80	100W	15,000	-	★	Damp	Case = 16 2-pack
			75644	LED15LS2/850	120	32	5.24	1600		5000	80	100W	15,000	-	★	Damp	Case = 16 2-pack

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

<http://products.currentbyge.com>

LED replacement lamps

Reflector Lamps

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
R20																	
	MED	7	38268	LED7DR20/827	120	6	3.64	470		2700	80	45W	25,000	Yes		Damp	White
			43233	LED7DR20/830	120	6	3.64	470		3000	80	45W	25,000	Yes		Damp	White
			38273	LED7DR20/850	120	6	3.64	500		5000	80	45W	25,000	Yes		Damp	White
BR30																	
	MED	10	68160	LED10DR303/827W	120	6	5.4	700		2700	80	65W	25,000	Yes	★	Damp	Frosted, White body
			68161	LED10DR303/830W	120	6	5.4	700		3000	80	65W	25,000	Yes	★	Damp	Frosted, White body
			69107	LED10DR303/850W	120	6	5.4	700		5000	80	65W	25,000	Yes	★	Damp	Frosted, White body
			43234	LED10DR30V/827W	120	3	5.37	650		2700	80	65W	15,000	Yes		Damp	Frosted, White body
			43237	LED10DR30V/830W	120	3	5.37	650		3000	80	65W	15,000	Yes		Damp	Frosted, White body
			43241	LED10DR30V/850W	120	3	5.37	650		5000	80	65W	15,000	Yes		Damp	Frosted, White body
BR40																	
	MED	13	64176	LED13DBR40/827	120	6	6.3	1070		2700	80	85W	25,000	Yes	★	Damp	Frosted, White body
			14708	LED13DBR40/830	120	6	6.3	1070		3000	80	85W	25,000	Yes	★	Damp	Frosted, White body
			69108	LED13BR40/850	120	3	6.34	1070		5000	80	85W	25,000	Yes	★	Damp	Frosted, White body

Directional Lamps (MR16 - GU10)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information	
12 Volt AC/DC MR16																		
	GU5.3	6.5	75155	LED6.5XDMR16W82715	12	6	1.87	500	4900	2700	80	50W	25,000	Yes	★	Damp	Spot 15° beam, White	
			75153	LED6.5DMR16W83015	12	6	1.87	520	4900	3000	80	50W	25,000	Yes	★	Damp	Spot 15° beam, White	
			75158	LED6.5DMR16W84015	12	6	1.87	550	5000	4000	80	50W	25,000	Yes	★	Damp	Spot 15° beam, White	
			93226	LED6.5DMR16W82725	12	6	1.79	500	2350	2700	80	50W	25,000	Yes	★	Damp	Narrow 25° beam, White	
			93222	LED6.5DMR16W83025	12	6	1.79	520	2350	3000	80	50W	25,000	Yes	★	Damp	Narrow 25° beam, White	
			93228	LED6.5DMR16W84025	12	6	1.79	550	2400	4000	82	50W	25,000	Yes	★	Damp	Narrow 25° beam, White	
			93227	LED6.5DMR16W82735	12	6	1.79	500	1350	2700	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, White	
			93223	LED6.5DMR16W83035	12	6	1.79	520	1350	3000	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, White	
			93229	LED6.5DMR16W84035	12	6	1.79	550	1400	4000	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, White	
			7	21359	LED7MRX16R930/10	12	6	2.01	350	8000	3000	95	50W	25,000	-		Damp	Spot, 10° beam, Reveal
			93412	LED7DMR16S830/15	12	6	2.3	460	3800	3000	80	35W	25,000	Yes		Damp	Spot 15° beam, Silver	
			Value 12 Volt AC/DC MR16															
	GU5.3	5.5	35542	LED5.5DMR1684035	12	6	1.86	460	1100	4000	80	35W	25,000	Yes	★	Damp	Flood, 35° beam, White	
			35535	LED5.5DMR1683035	12	6	1.86	420	1000	3000	80	35W	25,000	Yes	★	Damp	Flood, 35° beam, White	
			35540	LED5.5DMR1682735	12	6	1.86	400	1000	2700	80	35W	25,000	Yes	★	Damp	Flood, 35° beam, White	
		6	20165	LED6DMR16-32725	12	6	1.86	500	2350	2700	80	50W	25,000	Yes	★	Damp	Narrow 25° beam, White	
			20168	LED6DMR16-32735	12	6	1.86	500	1350	2700	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, White	
			20156	LED6DMR16-38325	12	6	1.86	500	2350	3000	81	50W	25,000	Yes	★	Damp	Narrow 25° beam, White	
			20157	LED6DMR16-38335	12	6	1.86	500	1350	3000	81	50W	25,000	Yes	★	Damp	Flood, 35° beam, White	
120 Volt GU10																		
	MR16	GU10	3.5	37114	LED4D/GU1083035	120	6	2.1	300	550	3000	80	35W	25,000	Yes	★	Dry	Flood, 35° beam, White
			4	89020	LED4D/GU10/NFLTP	120	3	2.1	250	720	3000	80	35W	25,000	Yes	★	Damp	Flood, 35° beam, White
			6	26346	LED6D/GU10/NFL/TP	120	3	2.1	430	1100	3000	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, White
				37117	LED6D/GU1083035	120	6	2.1	430	1100	3000	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, White

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity=6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at
<http://products.currentbyge.com>.

LED replacement lamps

Directional Lamps (PAR16 - PAR20)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
Compact PAR16																	
	MED	4	26383	LED4D/P16/NFLTP	120	3	2.8	260	720	3000	80	40W	25,000	Yes	★	Dry	Flood, 35° beam, White
		6	26384	LED6D/P16/NFLTP	120	3	2.8	380	1100	3000	80	60W	25,000	Yes	★	Dry	Flood, 35° beam, White
Compact PAR20																	
	MED	7	93327	LED7DP203B830/20	120	6	3.5	520	3600	3000	80	50W	25,000	Yes	★	Damp	Narrow Flood, 20° beam , Black Casing
			93347	LED7DP203W830/20	120	6	3.5	520	3600	3000	80	50W	25,000	Yes	★	Damp	Narrow Flood, 20° beam
			93348	LED7DP203W830/35	120	6	3.5	520	1200	3000	80	50W	25,000	Yes	★	Damp	Flood, 35° beam
			93349	LED7DP203B827/20	120	6	3.5	500	3600	2700	80	50W	25,000	Yes	★	Damp	Narrow Flood, 20° beam, Black Casing
			93354	LED7DP203B827/35	120	6	3.5	500	1150	2700	80	50W	25,000	Yes	★	Damp	Flood, 35° beam, Black Casing
			93360	LED7DP203W827/20	120	6	3.5	500	3600	2700	80	50W	25,000	Yes	★	Damp	Narrow Flood, 20° beam
			93362	LED7DP203W827/35	120	6	3.5	500	1150	2700	80	50W	25,000	Yes	★	Damp	Flood, 35° beam

Directional Lamps (PAR30 - Low Glare - Visual Comfort Lens™)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
Compact PAR30 - Low Glare - Visual Comfort Lens™																	
	MED	12	84374	LED12DP30RW93015	120	6	3.74	860	9400	3000	90	75W	25,000	Yes	★	Damp	Spot, 15° beam, White
			84379	LED12DP30RW93025	120	6	3.74	900	3900	3000	90	75W	25,000	Yes	★	Damp	Narrow Flood, 25° beam, White
			84380	LED12DP30RW93040	120	6	3.74	900	1800	3000	90	75W	25,000	Yes	★	Damp	Flood, 40° beam, White
			84392	LED12DP30RW92725	120	6	3.74	850	3500	2700	90	75W	25,000	Yes	★	Damp	Narrow Flood, 25° beam, White
			84395	LED12DP30RW92740	120	6	3.74	850	1700	2700	90	75W	25,000	Yes	★	Damp	Flood, 40° beam, White
			84384	LED12DP30RW83025	120	6	3.74	1050	4800	3000	80	75W	25,000	Yes	★	Damp	Narrow Flood, 25° beam, White
			42131	LED12DP30RW83040	120	6	3.74	1050	2400	3000	80	75W	25,000	Yes	★	Damp	Flood, 40° beam, White
			42133	LED12DP30RW82725	120	6	3.74	1000	4700	2700	80	75W	25,000	Yes	★	Damp	Narrow Flood, 25° beam, White
			42134	LED12DP30RW82740	120	6	3.74	1000	2200	2700	80	75W	25,000	Yes	★	Damp	Flood, 40° beam, White
			73583	LED12DP30RB82740	120	6	3.74	1000	2200	2700	80	75W	25,000	Yes	★	Damp	Flood, 40° beam, White
Compact PAR30 - Long Neck - Low Glare - Visual Comfort Lens™																	
	MED	12	84399	LED12DP3LRW93025	120	6	4.72	900	3900	3000	90	75W	25,000	Yes	★	Damp	Narrow Flood, 25° beam, White
			84400	LED12DP3LRW93040	120	6	4.72	900	1800	3000	90	75W	25,000	Yes	★	Damp	Flood, 40° beam, White
			84407	LED12DP3LRW92740	120	6	4.72	850	1700	2700	90	75W	25,000	Yes	★	Damp	Flood, 40° beam, White
			42136	LED12DP3LRW83025	120	6	4.72	1050	4800	3000	80	75W	25,000	Yes	★	Damp	Narrow Flood, 25° beam, White
			42137	LED12DP3LRW83040	120	6	4.72	1050	2400	3000	80	75W	25,000	Yes	★	Damp	Flood, 40° beam, White
			42141	LED12DP3LRW82725	120	6	4.72	1000	4700	2700	80	75W	25,000	Yes	★	Damp	Narrow Flood, 25° beam, White
			42144	LED12DP3LRW82740	120	6	4.72	1000	2200	2700	80	75W	25,000	Yes	★	Damp	Flood, 40° beam, White

Directional Lamps (PAR30 - STIR)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
Compact PAR30																	
	MED	12	98755	LED12DP303W83035	120	6	3.66	950	2600	3000	80	75W	25,000	Yes	★	Damp	Flood, 35° beam, White, STIR
Compact PAR30 Long Neck																	
	MED	12	98811	LED12DP3L3W83035	120	6	4.61	950	2600	3000	80	75W	25,000	Yes	★	Damp	Accent, 35° beam, White, STIR

Directional Lamps (PAR30 - High Output)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
Universal 120-277V																	
	MED	18	75089	LED18P30LW83015	120-277	6	4.6	1800	15500	3000	80	75W	25,000	-	★	Damp	Spot, 15°, White
			75091	LED18P30LW83025	120-277	6	4.6	1800	7000	3000	80	75W	25,000	-	★	Damp	Narrow Flood, 25°, White
			75065	LED18P30LW93015	120-277	6	4.6	1400	12500	3000	90	75W	25,000	-	★	Damp	Spot, 15° beam, MTO, 1000 Min. Qty, 12 Week Lead Time, White
			75078	LED18P30LW93025	120-277	6	4.6	1400	5000	3000	90	75W	25,000	-	★	Damp	Narrow Flood, 25°, White

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in “/TP” indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at
<http://products.currentbyge.com>.

LED replacement lamps

Directional Lamps (PAR38)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (in)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
PAR38 - Low Glare - Visual Comfort Lens™																	
	MED	12	92971	LED12D38W3827/40	120	6	5.31	1050	2300	2700	81	100W	25,000	Yes	★	Damp	Flood, 40° beam, White
			92972	LED12D38W3830/25	120	6	5.31	1050	5500	3000	81	100W	25,000	Yes	★	Damp	Narrow Flood, 25° beam, White
			92973	LED12D38W3830/40	120	6	5.31	1050	2300	3000	80	100W	25,000	Yes	★	Wet	Flood, 40° beam, White
	18		24520	LED12D38W3930/12	120	6	5.31	950	15000	3000	90	90W	25,000	-	-	Damp	Spot, 12° beam, White
			92950	LED18D38OW3827/25	120	6	5.12	1550	5800	2700	81	120W	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White
			92923	LED18D38W3927/25	120	6	5.31	1250	4900	2700	92	100W	25,000	Yes	★	Damp	Narrow Flood, 25° beam, White
			92958	LED18D38OW3827/40	120	6	5.12	1550	3800	2700	81	120W	25,000	Yes	★	Wet	Flood, 40° beam, White
			92926	LED18D38W3927/40	120	6	5.12	1250	2900	2700	92	120W	25,000	Yes	★	Damp	Flood, 40° beam, White
			92927	LED18D38W3930/15	120	6	5.32	1350	15000	3000	92	75W	25,000	Yes	★	Wet	Spot, 15° beam, White
			92961	LED18D38W3830/15	120	6	5.12	1750	20000	3000	81	150W	25,000	Yes	★	Wet	Spot, 15° beam, White
			92963	LED18D38OW3830/25	120	6	5.12	1550	6000	3000	81	120W	25,000	Yes	★	Wet	Flood, 40° beam, White
			92933	LED18D38W3930/25	120	6	5.31	1350	5200	3000	92	100W	25,000	Yes	★	Damp	Narrow Flood, 25° beam, White
			92967	LED18D38OW3830/40	120	6	5.12	1550	4000	3000	81	150W	25,000	Yes	★	Wet	Flood, 40° beam, White
			92934	LED18D38W3930/40	120	6	5.12	1350	3200	3000	92	120W	25,000	Yes	★	Damp	Flood, 40° beam, White
			85085	LED18D38OW3835/25	120	6	5.31	1700	6500	3500	81	120W	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White
			87917	LED18D38OW3835/40	120	6	5.31	1700	4400	3500	81	150W	25,000	Yes	★	Wet	Flood, 40° beam, White
			93171	LED18D38OW3840/25	120	6	5.31	1700	6500	4000	81	120W	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White
			93172	LED18D38OW3840/40	120	6	5.31	1700	4400	4000	81	150W	25,000	Yes	★	Wet	Flood, 40° beam, White
			65730	LED18D38OW3850/25	120	6	5.31	1700	6500	5000	81	120W	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White
			65731	LED18D38OW3850/40	120	6	5.31	1700	4400	5000	81	150W	25,000	Yes	★	Wet	Flood, 40° beam, White

Directional Lamps (PAR38 – High Output)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (in)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
Single Optics																	
	MED	32	75447	LED32DP38W830/15	120	6	5.12	3000	26,000	3000	82	250W	25,000	Yes	★	Wet	Spot, 15° beam, White
			88801	LED32DP38W830/25	120	6	5.12	3000	13,000	3000	80	250W	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White
			88810	LED32DP38W830/40	120	6	5.12	3000	6,000	3000	80	250W	25,000	Yes	★	Wet	Flood, 40° beam, White
			30233	LED32DP38W835/15	120	6	5.12	3100	25000	3500	80	250W	25,000	Yes	★	Wet	Spot, 15° beam, White
			30237	LED32DP38W835/25	120	6	5.12	3100	13000	3500	80	250W	25,000	Yes	★	Wet	Narrow Flood, 25° beam, White
			30239	LED32DP38W835/40	120	6	5.12	3100	6000	3500	80	250W	25,000	Yes	★	Wet	Flood, 40° beam, White
			20109	LED32P38W830/15	120-277	6	5.12	3000	25000	3000	80	250W	25,000	-	★	Wet	Spot, 15° beam, White
			20130	LED32P38W830/25	120-277	6	5.12	3000	13000	3000	80	250W	25,000	-	★	Wet	Narrow Flood, 25° beam, White
			20137	LED32P38W830/40	120-277	6	5.12	3000	6000	3000	80	250W	25,000	-	★	Wet	Flood, 40° beam, White

Directional Lamps (PAR38- Value)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (in)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
Single Optics																	
	PAR38 MED	11	91360	LED11P38W830/25	120	6	5.04	950	4000	3000	80	90W	10,000	-		Wet	Flood, 25° beam, White, STIR
		15	32213	LED15DP38W830/40	120	6	5.04	1300	2300	3000	81	90W	25,000	Yes	★	Wet	Flood, 40° beam, White, STIR

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)
** Minimum order quantity = 6
★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.
UL 1993 Environmental Requirements for LED LAMPS
Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.
Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.
Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.
Notes: 1) Product descriptions ending in "7TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at
<http://products.currentbyge.com>.

LED replacement lamps

LED HID Type A

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	#Location Rating	Additional Information
400 Watt Metal Halide Replacement Lamp																
	EX39	60	43263	LED60/2M175/740		3	8.4	8,800		4000	70	175W	50,000	-	Damp	Open or Closed Rated, CWA ANSI -M57, M137, M152
			88107	LED60/2M175/750		3	8.4	8,800		5000	70	175W	50,000	-	Damp	Open or Closed Rated, CWA ANSI -M57, M137, M152
	80	43258	LED80/2M250/740			3	8.4	11,800		4000	70	250W	50,000	-	Damp	Open or Closed Rated, CWA ANSI -M58, M138, M153
			88099	LED80/2M250/750		3	8.4	11,800		5000	70	250W	50,000	-	Damp	Open or Closed Rated, CWA ANSI -M58, M138, M153
	130	43252	LED130/2M400/740			3	8.4	18,500		4000	70	400W	50,000	-	Damp	Open or Closed Rated, CWA, ANSI - M59, M135, M155
			88109	LED130/2M400/750		3	8.4	18,500		5000	70	400W	50,000	-	Damp	Open or Closed Rated, CWA, ANSI - M59, M135, M155
	165	21259	LED165/M400/740			3	11.42	20,000		4000	73	400W	50,000	-	Dry	Open Rated Only, CWA, ANSI - M59, M135, M155

LED HID Type B

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	DLC*	#Location Rating	Additional Information
LED Replacement Lamps for HID																	
	MED	21	27729	LED21ED17/740	120-277	3	5.4	3,000		4000K	>70	50W	50,000	-	-	Damp	Ballast bypass required.
			27732	LED21ED17/750	120-277	3	5.4	3,000		5000K	>70	50W	50,000	-	-	Damp	Ballast bypass required.
	35	27602	LED35ED17/740		120-277	3	5.4	5,000		4000K	>70	70W	50,000	-	-	Damp	Ballast bypass required.
			27724	LED35ED17/750	120-277	3	5.4	5,000		5000K	>70	70W	50,000	-	-	Damp	Ballast bypass required.
	50	22779	LED50ED23.5M/740		120-277	3	7.7	7,500		4000K	>70	100W	50,000	-	-	Damp	Ballast bypass required.
	80	22768	LED80ED23.5M/740		120-277	3	7.7	12,000		4000K	>70	175W	50,000	-	-	Damp	Ballast bypass required.
	EX39	50	27572	LED50ED23.5/725	120-277	3	7.7	7,150		2450K	>70	100W	50,000	-	-	Damp	Ballast bypass required.
			22679	LED50ED23.5/740	120-277	3	7.7	7,500		4000K	>70	100W	50,000	-	Yes	Damp	Ballast bypass required.
			22739	LED50ED23.5/750	120-277	3	7.7	7,500		5000K	>70	100W	50,000	-	Yes	Damp	Ballast bypass required.
	80	27539	LED80ED23.5/725		120-277	3	7.7	11,500		2450K	>70	175W	50,000	-	-	Damp	Ballast bypass required.
			22635	LED80ED23.5/740	120-277	3	7.7	12,000		4000K	>70	175W	50,000	-	Yes	Damp	Ballast bypass required.
			22676	LED80ED23.5/750	120-277	3	7.7	12,000		5000K	>70	175W	50,000	-	Yes	Damp	Ballast bypass required.
	115	22622	LED115ED28/740		120-277	3	8.3	18,000		4000K	>70	250W	50,000	-	Yes	Damp	Ballast bypass required.
			22623	LED115ED28/750	120-277	3	8.3	18,000		5000K	>70	250W	50,000	-	Yes	Damp	Ballast bypass required.
	150	22611	LED150ED28/740		120-277	3	8.3	23,500		4000K	>70	400W	50,000	-	Yes	Damp	Ballast bypass required.
			22613	LED150ED28/750	120-277	3	8.3	23,500		5000K	>70	400W	50,000	-	Yes	Damp	Ballast bypass required.
	270	93095547	LED270BT56/740		277-480	3	12.2	40,000		4000K	>70	1000W	50,000	-	-	Damp	Coming Soon.
			93095553	LED270BT56/750	277-480	3	12.2	40,000		5000K	>70	1000W	50,000	-	-	Damp	Coming Soon.
	450	93096445	LED450BT56/740		277-480	3	12.2	65,000		4000K	>70	1000W	50,000	-	-	Damp	Coming Soon.
			93096547	LED450BT56/750	277-480	3	12.2	65,000		5000K	>70	1000W	50,000	-	-	Damp	Coming Soon.

- Check compatibility at [GELighting.com/LED4pin-compatibility](http://www.gelighting.com/LED4pin-compatibility)

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

^ Not suitable for air-tight explosive or hazardous fixtures.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

<http://products.currentbyge.com>.

LED replacement lamps

4 Pin Plug-In

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (in)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	DLC®	#Location Rating	Additional Information
Vertical																	
	Plug-In	G24q/GX24q	9	33956	LED9G24Q-V/827	#	6	5.31	1100	2700	80		50,000	-	Yes	Damp	Requires Electronic Ballast, Fully Enclosed
				33969	LED9G24Q-V/830	#	6	5.31	1200	3000	80		50,000	-	Yes	Damp	Requires Electronic Ballast, Fully Enclosed
				33974	LED9G24Q-V/835	#	6	5.31	1200	3500	80		50,000	-	Yes	Damp	Requires Electronic Ballast, Fully Enclosed
				33975	LED9G24Q-V/840	#	6	5.31	1200	4000	80		50,000	-	Yes	Damp	Requires Electronic Ballast, Fully Enclosed
	GX24q	18.5	39288	LED19GX24q-V/827	#	6	6.42	1800	2700	80		50,000	-	-	Damp	Requires Electronic Ballast, White	
			39277	LED19GX24q-V/830	#	6	6.42	1850	3000	80		50,000	-	-	Damp	Requires Electronic Ballast, White	
			39275	LED19GX24q-V/835	#	6	6.42	1950	3500	80		50,000	-	-	Damp	Requires Electronic Ballast, White	
			39279	LED19GX24q-V/840	#	6	6.42	1950	4000	80		50,000	-	-	Damp	Requires Electronic Ballast, White	
Horizontal																	
	Plug-In	G24q/GX24q	9	33994	LED9G24Q-H/827	#	6	5.31	1100	2700	80		50,000	-	Yes	Damp	Requires Electronic Ballast, Fully Enclosed
				33997	LED9G24Q-H/830	#	6	5.31	1200	3000	80		50,000	-	Yes	Damp	Requires Electronic Ballast, Fully Enclosed
				33998	LED9G24Q-H/835	#	6	5.31	1200	3500	80		50,000	-	Yes	Damp	Requires Electronic Ballast, Fully Enclosed
				33999	LED9G24Q-H/840	#	6	5.31	1200	4000	80		50,000	-	Yes	Damp	Requires Electronic Ballast, Fully Enclosed
	GX24q	18.5	39289	LED19GX24q-H/827	#	6	6.7	1800	2700	80		50,000	-	-	Damp	Requires Electronic Ballast, White	
			39282	LED19GX24q-H/830	#	6	6.7	1850	3000	80		50,000	-	-	Damp	Requires Electronic Ballast, White	
			39276	LED19GX24q-H/835	#	6	6.7	1950	3500	80		50,000	-	-	Damp	Requires Electronic Ballast, White	
			39283	LED19GX24q-H/840	#	6	6.7	1950	4000	80		50,000	-	-	Damp	Requires Electronic Ballast, White	

2 Pin Plug-In

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	#Location Rating	Additional Information
2-Pin																
	Plug-In	GX23	5	91404	LED5GX23/827	#	6	6.7	500	2700	80	13	50,000	-	Damp	Magnetic Ballast, Fully Enclosed
				91405	LED5GX23/830	#	6	6.7	530	3000	80	13	50,000	-	Damp	Magnetic Ballast, Fully Enclosed
				91407	LED5GX23/835	#	6	6.7	545	3500	80	13	50,000	-	Damp	Magnetic Ballast, Fully Enclosed
				91408	LED5GX23/840	#	6	6.7	560	4000	80	13	50,000	-	Damp	Magnetic Ballast, Fully Enclosed
				91410	LED5GX23/850	#	6	6.7	565	5000	80	13	50,000	-	Damp	Magnetic Ballast, Fully Enclosed
Horizontal 2-Pin																
	G24d	10.5	92994	LED11G24d-H/827	#	6	6.5	1000	2700	80	18 or 26	50,000	-	Damp	Magnetic Ballast, Fully Enclosed	
				92993	LED11G24d-H/830	#	6	6.5	1050	3000	80	18 or 26	50,000	-	Damp	Magnetic Ballast, Fully Enclosed
				92990	LED11G24d-H/835	#	6	6.5	1050	3500	80	18 or 26	50,000	-	Damp	Magnetic Ballast, Fully Enclosed
				92992	LED11G24d-H/840	#	6	6.5	1050	4000	80	18 or 26	50,000	-	Damp	Magnetic Ballast, Fully Enclosed
Vertical 2-Pin																
	G24d	10.5	93002	LED11G24d-V/827	#	6	6.1	1000	2700	80	18 or 26	50,000	-	Damp	Magnetic Ballast, Fully Enclosed	
				93001	LED11G24d-V/830	#	6	6.1	1050	3000	80	18 or 26	50,000	-	Damp	Magnetic Ballast, Fully Enclosed
				92988	LED11G24d-V/835	#	6	6.1	1050	3500	80	18 or 26	50,000	-	Damp	Magnetic Ballast, Fully Enclosed
				92996	LED11G24d-V/840	#	6	6.1	1050	4000	80	18 or 26	50,000	-	Damp	Magnetic Ballast, Fully Enclosed

- Check compatibility at GELighting.com/LED2pin-compatibility

High Lumen Biax

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	#Location Rating	Additional Information
High Lumen Biax (HLBX)																
HLBX	2G11	17	39073	LED172G11/830/10	#	10	22.3	2150		3000	80		50,000	-	Damp	Indoor, White, Instant/PS Ballast
			39074	LED172G11/835/10	#	10	22.3	2150		3500	80		50,000	-	Damp	Indoor, White, Instant/PS Ballast
			39075	LED172G11/840/10	#	10	22.3	2200		4000	80		50,000	-	Damp	Indoor, White, Instant/PS Ballast
			39076	LED172G11/850/10	#	10	22.3	2200		5000	80		50,000	-	Damp	MTO, 1000 Min. Qty., 12 Week Lead Time

- Check compatibility at GELighting.com/LED2G11-compatibility

RS Cans

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (in)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
RS Cans																	
	E26	10	95853	LED10RS4/827E26P	120	12	4.32	700		2700	80	65W	50,000	Yes	★	Damp	4" Can, Pigtail Attachment
			95854	LED10RS4/830E26P	120	12	4.32	700		3000	80	65W	50,000	Yes	★	Damp	4" Can, Pigtail Attachment
			35365	LED10RS4/840E26P	120	12	4.32	700		4000	80	65W	50,000	Yes	★	Damp	4" Can, Pigtail Attachment
			19888	LED8DRS6/827	120	4	4.96	700		2700	80	65W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment
	8		19908	LED8DRS6/830	120	4	4.96	700		3000	80	65W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment
			20026	LED8DRS6/840	120	4	4.96	700		4000	80	65W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment
			13	20037	LED13DRS6/827	120	4	4.96	1000	2700	80	90W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment
				20048	LED13DRS6/830	120	4	4.96	1000	3000	80	90W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)
** Minimum order quantity = 6

UL 1993 Environmental Requirements for LED LAMPS
Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.
Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.
Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.
Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at
<http://products.currentbyge.com>

Title 20 LED Lamps



Set up your transition plan today. For more information contact your GE sales representative. Full California Title 20

Requirements can be found at <http://www.energy.ca.gov/title20/>

Bulb Shape	Base Type	Watts	Order Code	Description	UOS	Case Qty**	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status
G16.5	E12	4.5	45695	LED5DGC-GCSW9C2	2	6	350	2700	90	40	15,000	Yes	
G16.5	E12	4.5	45710	LED5DGC-GCDL9C2	2	6	350	5000	90	40	15,000	Yes	
G16.5	E12	4.5	45711	LED5DGC-GWSW9C2	2	6	350	2700	90	40	15,000	Yes	
G16.5	E12	4.5	45715	LED5DGC-GWDL9C2	2	6	350	5000	90	40	15,000	Yes	
G25	E26	4.5	43259	LED5DG25-GCSW9C3	3	6	350	2700	90	40	15,000	Yes	
G25	E26	4.5	43266	LED5DG25-GCDL9C3	3	6	350	5000	90	40	15,000	Yes	
G25	E26	4.5	43269	LED5DG25-GWSW9C3	3	6	350	2700	90	40	15,000	Yes	
G25	E26	4.5	43281	LED5DG25-GWDL9C3	3	6	350	5000	90	40	15,000	Yes	
G25	E26	5.5	43306	LED6DG25-GCSW9C3	3	6	500	2700	90	60	15,000	Yes	
G25	E26	5.5	43310	LED6DG25-GCDL9C3	3	6	500	5000	90	60	15,000	Yes	
G25	E26	5.5	43316	LED6DG25-GWSW9C3	3	6	500	2700	90	60	15,000	Yes	
G25	E26	5.5	43317	LED6DG25-GWDL9C3	3	6	500	5000	90	60	15,000	Yes	
G25	E26	4.5	36850	LED5DG25-GCSW9C	1	6	350	2700	90	40	15,000	Yes	
G25	E26	4.5	36948	LED5DG25-GCDL9C	1	6	350	5000	90	40	15,000	Yes	
G25	E26	4.5	36852	LED5DG25-GWSW9C	1	6	350	2700	90	40	15,000	Yes	
G25	E26	4.5	36955	LED5DG25-GWDL9C	1	6	350	5000	90	40	15,000	Yes	
G25	E26	5.5	36855	LED6DG25-GCSW9C	1	6	500	2700	90	60	15,000	Yes	
G25	E26	5.5	36857	LED6DG25-GCDL9C	1	6	500	5000	90	60	15,000	Yes	
G25	E26	5.5	36862	LED6DG25-GWSW9C	1	6	500	2700	90	60	15,000	Yes	
G25	E26	5.5	36891	LED6DG25-GWDL9C	1	6	500	5000	90	60	15,000	Yes	
CAM	E26	2.5	48209	LED3DCAM-GWSW9C2	2	6	200	2700	90	25	15000	Yes	
CAM	E26	4.0	48232	LED4DCAM-GWSW9C2	2	6	300	2700	90	40	15000	Yes	
CAM	E26	4.0	48233	LED4DCAM-GWDL9C2	2	6	300	5000	90	40	15000	Yes	
CAM	E26	4.0	36903	LED4DCAM-GCSW9C2	2	6	300	2700	90	40	15,000	Yes	
CAM	E26	4.0	36978	LED4DCAM-GCDL9C2	2	6	300	5000	90	40	15,000	Yes	
CAM	E26	4.0	48262	LED4DCAM-GWDL9C4	4	6	300	5000	90	40	15000	Yes	
CAM	E26	4.0	48263	LED4DCAM-GWSW9C4	4	6	300	2700	90	40	15000	Yes	
CAM	E26	5.5	48264	LED6DCAM-GWDL9C4	4	6	500	5000	90	60	15000	Yes	
CAM	E26	5.5	48265	LED6DCAM-GWSW9C4	4	6	500	2700	90	60	15000	Yes	
CAM	E26	2.5	36969	LED3DCAM-GCSW9C2	2	6	200	2700	90	25	15,000	Yes	
CAM	E26	2.5	36973	LED3DCAM-GCDL9C2	2	6	200	5000	90	25	15,000	Yes	
CAM	E26	2.5	45576	LED3DCAM-GCSW9C4	4	6	200	2700	90	25	15,000	Yes	
CAM	E26	2.5	45577	LED3DCAM-GCDL9C4	4	6	200	5000	90	25	15,000	Yes	
CAM	E26	4.0	45660	LED4DCAM-GCSW9C4	4	6	300	2700	90	40	15,000	Yes	
CAM	E26	4.0	45661	LED4DCAM-GCDL9C4	4	6	300	5000	90	40	15,000	Yes	
CAM	E26	5.5	36942	LED6DCAM-GCSW9C2	2	6	500	2700	90	60	15,000	Yes	
CAM	E26	5.5	36848	LED6DCAM-GCDL9C2	2	6	500	5000	90	60	15,000	Yes	
CAM	E26	5.5	43255	LED6DCAM-GCSW9C4	4	6	500	2700	90	60	15,000	Yes	
CAM	E26	5.5	43256	LED6DCAM-GCDL9C4	4	6	500	5000	90	60	15,000	Yes	
CAC	E12	2.5	48234	LED3DCAC-GWSW9C4	4	6	200	2700	90	25	15000	Yes	
CAC	E12	4.0	48243	LED4DCAC-GWDL9C4	4	6	300	5000	90	40	15000	Yes	

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

^ Not suitable for air-tight explosive or hazardous fixtures.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

<http://products.currentbyge.com.>

Title 20 LED Lamps

Bulb Shape	Base Type	Watts	Order Code	Description	UOS	Case Qty**	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status
CAC	E12	2.5	36968	LED3DCAC-GCDL9C2	2	6	200	5000	90	25	15,000	Yes	
CAC	E26	4.0	36893	LED4DCAC-GCSW9C2	2	6	300	2700	90	40	15,000	Yes	
CAC	E26	4.0	36896	LED4DCAC-GCDL9C2	2	6	300	5000	90	40	15,000	Yes	
CAC	E12	5.5	36846	LED6DCAC-GCSW9C2	2	6	500	2700	90	60	15,000	Yes	
CAC	E12	5.5	36847	LED6DCAC-GCDL9C2	2	6	500	5000	90	60	15,000	Yes	
CAC	E12	5.5	48249	LED6DCAC-GWDL9C4	4	6	500	5000	90	60	15000	Yes	
CAC	E12	4.0	36985	LED4DCAC-GWSW9C4	4	6	300	2700	90	40	15,000	Yes	
CAC	E12	5.5	36986	LED6DCAC-GWSW9C4	4	6	500	2700	90	60	15,000	Yes	
CAC	E12	4.0	36987	LED4DCAC-GWSW9C2	2	6	300	2700	90	40	15,000	Yes	
CAC	E12	5.5	36988	LED6DCAC-GWSW9C2	2	6	500	2700	90	60	15,000	Yes	
CAC	E12	2.5	45555	LED3DCAC-GCSW9C4	4	6	200	2700	90	25	15,000	Yes	
CAC	E12	2.5	45567	LED3DCAC-GCDL9C4	4	6	200	5000	90	25	15,000	Yes	
CAC	E12	4.0	45640	LED4DCAC-GCSW9C4	4	6	300	2700	90	40	15,000	Yes	
CAC	E12	5.5	43227	LED6DCAC-GCSW9C4	4	6	500	2700	90	60	15,000	Yes	
CAC	E12	4.0	45653	LED4DCAC-GCDL9C4	4	6	300	5000	90	40	15,000	Yes	
CAC	E12	5.5	43245	LED6DCAC-GCDL9C4	4	6	500	5000	90	60	15,000	Yes	
CAC	E12	2.5	36967	LED3DCAC-GCSW9C2	2	6	200	2700	90	25	15,000	Yes	
A15	E26	5.5	36980	LED6DA15-GCSW9C2	2	6	500	2700	90	60	15,000	Yes	
A15	E26	5.5	36981	LED6DA15-GCDL9C2	2	6	500	5000	90	60	15,000	Yes	
A15	E26	5.5	36982	LED6DA15-GWSW9C2	2	6	500	2700	90	60	15,000	Yes	
A15	E26	5.5	36984	LED6DA15-GWDL9C2	2	6	500	5000	90	60	15,000	Yes	
A15	E26	4.0	45672	LED4DA15-GCSW9C2	2	6	300	2700	90	40	15,000	Yes	
A15	E26	4.0	45676	LED4DA15-GCDL9C2	2	6	300	5000	90	40	15,000	Yes	
A15	E26	4.0	37751	LED4DA15-GWSW9C2	2	6	300	2700	90	40	15,000	Yes	
A15	E26	4.0	37760	LED4DA15-GWDL9C2	2	6	300	5000	90	40	15,000	Yes	
A19	E26	6	42975	LED6DASW9C-4PK	4	6	450	2700	90	40	15,000	Yes	★
A19	E26	6	42976	LED6DADL9C-4PK	4	6	450	5000	90	40	15,000	Yes	★
A19	E26	10.5	42977	LED10DASW9C-4PK	4	6	800	2700	90	60	15,000	Yes	★
A19	E26	10.5	42978	LED10DADL9C-4PK	4	6	800	5000	90	60	15,000	Yes	★
A19	E26	5.5	36990	LED6ASW9CP-4P	4	6	380	2700	90	40	10,000	No	
A19	E26	5.5	36992	LED6ADL9CP-4P	4	6	400	5000	90	40	10,000	No	
A19	E26	10	36993	LED10ASW9CP-4P	4	6	750	2700	90	60	10,000	No	
A19	E26	10	37004	LED10ADL9CP-4P	4	6	750	5000	90	60	10,000	No	
A19	E26	5.5	37033	LED6ASW9CP-8P	8	6	380	2700	90	40	10,000	No	
A19	E26	5.5	37035	LED6ADL9CP-8P	8	6	380	5000	90	40	10,000	No	
A19	E26	10	37043	LED10ASW9CP-8P	8	6	750	2700	90	60	10,000	No	
A19	E26	10	37048	LED10ADL9CP-8P	8	6	750	5000	90	60	10,000	No	
A19	E26	10.5	46183	LED10DASW9CG24-1	1	4	800	2700	90	60	15,000	Yes	★
A19	E26	10.5	46184	LED10DADL9CG24-1	1	4	800	5000	90	60	15,000	Yes	★
A19	E26	6.0	36833	LED6DASW9C-2PK	2	6	450	2700	90	40	15,000	Yes	
A19	E26	6.0	36834	LED6DADL9C-2PK	2	6	450	5000	90	40	15,000	Yes	
A19	E26	10.5	36835	LED10DASW9C-2PK	2	6	800	2700	90	60	15,000	Yes	
A19	E26	10.5	36845	LED10DADL9C-2PK	2	6	800	5000	90	60	15,000	Yes	
A21	E26	16	46226	LED30/100SW9C	1	3	1,500	2700	90	30/100	15,000	No	★
A21	E26	16	46228	LED30/100DL9C	1	3	1,500	5000	90	30/100	15,000	No	★
A21	E26	13	42979	LED13DASW9C-2PK	2	6	1,100	2700	90	75	15,000	Yes	★
A21	E26	13	42980	LED13DADL9C-2PK	2	6	1,100	5000	90	75	15,000	Yes	★
A21	E26	17	44148	LED17DASW9C-2PK	2	6	1,600	2700	90	100	15,000	Yes	★

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "7TP" indicate a corded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

<http://products.currentbyge.com>

Title 20 LED Lamps

Bulb Shape	Base Type	Watts	Order Code	Description	UOS	Case Qty**	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status
A21	E26	17	44149	LED17DADL9C-2PK	2	6	1,600	5000	90	100	15,000	Yes	★
A21	E26	13	37015	LED13ASW9CP-2P	2	6	1,050	2700	90	75	10,000	No	
A21	E26	13	37019	LED13ADL9CP-2P	2	6	1,050	5000	90	75	10,000	No	
A21	E26	16	37025	LED16ASW9CP-2P	2	6	1,490	2700	90	100	10,000	No	
A21	E26	16	37027	LED16ADL9CP-2P	2	6	1,490	5000	90	100	10,000	No	
MR16	GU5.3	6.5	75155	LED6.5DMR16W82715	1	6	500	2700	80	50W	25,000	Yes	★
MR16	GU5.3	6.5	75153	LED6.5DMR16W83015	1	6	520	3000	80	50W	25,000	Yes	★
MR16	GU5.3	6.5	75158	LED6.5DMR16W84015	1	6	550	4000	80	50W	25,000	Yes	★
MR16	GU5.3	6.5	93226	LED6.5DMR16W82725	1	6	500	2700	80	50W	25,000	Yes	★
MR16	GU5.3	6.5	93222	LED6.5DMR16W83025	1	6	520	3000	80	50W	25,000	Yes	★
MR16	GU5.3	6.5	93228	LED6.5DMR16W84025	1	6	550	4000	82	50W	25,000	Yes	★
MR16	GU5.3	6.5	93227	LED6.5DMR16W82735	1	6	500	2700	80	50W	25,000	Yes	★
MR16	GU5.3	6.5	93223	LED6.5DMR16W83035	1	6	520	3000	80	50W	25,000	Yes	★
MR16	GU5.3	6.5	93229	LED6.5DMR16W84035	1	6	550	4000	80	50W	25,000	Yes	★
MR16	GU5.3	6	20165	LED6DMR16-32725	1	6	500	2700	80	50W	25,000	Yes	★
MR16	GU5.3	6	20168	LED6DMR16-32735	1	6	500	2700	80	50W	25,000	Yes	★
MR16	GU5.3	6	20156	LED6DMR16-38325	1	6	500	3000	81	50W	25,000	Yes	★
MR16	GU5.3	6	20157	LED6DMR16-38335	1	6	500	3000	81	50W	25,000	Yes	★
MR16	GU5.3	6.5	37059	LED6.5DMR16W-C-1	1	6	520	3000	82	50	25,000	Yes	
R14	E26	4.0	47856	LED4DR14E9SW-1P	1	6	250	2700	90	25	15000	Yes	
R14	E26	4.0	48120	LED4DR14E9DL-1P	1	6	250	5000	90	25	15000	Yes	
R16	E26	6.0	48138	LED6DR16E9SW-1P	1	6	400	2700	90	40	15000	Yes	
R16	E26	6.0	48179	LED6DR16E9DL-1P	1	6	400	5000	90	40	15000	Yes	
R20	E26	5.0	45545	LED5DR209CSW	1	6	450	2700	92	45	15,000	Yes	
R20	E26	5.0	45546	LED5DR209CDL	1	6	450	5000	92	45	15,000	Yes	
R30	E26	8.0	48193	LED8DBR309CSB-2P	2	6	700	2700	90	65	10000	Yes	
R30	E26	8.0	48197	LED8DBR309CDB-2P	2	6	700	5000	90	65	10000	Yes	
R30	E26	8.0	48198	LED8DBR309CSB-1P	1	6	700	2700	90	65	10000	Yes	
R30	E26	8.0	48206	LED8DBR309CDB-1P	1	6	700	5000	90	65	10000	Yes	
BR30	E26	8.0	43073	LED8DBR309CSW4P	4	6	700	2700	92	65	15,000	Yes	
BR30	E26	8.0	43074	LED8DBR309CDL4P	4	6	700	5000	92	65	15,000	Yes	
BR30	E26	8.0	45177	LED8DBR309CSW2P	2	6	700	2700	92	65	15,000	Yes	
BR30	E26	8.0	45195	LED8DBR309CDL2P	2	6	700	5000	92	65	15,000	Yes	
BR30	E26	8.0	36904	LED8DBR309CSW-1	1	6	700	2700	92	65	15,000	Yes	
BR30	E26	8.0	36908	LED8DBR309CDL-1	1	6	700	5000	92	65	15,000	Yes	
BR40	E26	11.0	43058	LED11DBR409CSW	1	6	950	2700	90	65	15,000	Yes	
BR40	E26	11.0	46329	LED11DBR409CDL	1	6	950	5000	90	65	15,000	Yes	
PAR20	E26	7.0	45441	LED7DP209CSW-1P	1	6	500	2700	92	50	15,000	Yes	
PAR20	E26	7.0	45499	LED7DP209CDL-1P	1	6	500	5000	92	50	15,000	Yes	
PAR30	E26	12	84392	LED12DP30RW92725	1	6	850	2700	90	75W	25,000	Yes	★
PAR30	E26	12	84395	LED12DP30RW92740	1	6	850	2700	90	75W	25,000	Yes	★
PAR30	E26	12	84374	LED12DP30RW93015	1	6	860	3000	90	75W	25,000	Yes	★
PAR30	E26	12	84379	LED12DP30RW93025	1	6	900	3000	90	75W	25,000	Yes	★

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

^ Not suitable for air-tight explosive or hazardous fixtures.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

<http://products.currentbyge.com>.

Title 20 LED Lamps

Bulb Shape	Base Type	Watts	Order Code	Description	UOS	Case Qty**	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status
PAR30	E26	12	84380	LED12DP30RW93040	1	6	900	3000	90	75W	25,000	Yes	★
PAR30	E26	12.0	43095	LED12DP309CDL2P	2	6	900	5000	92	75	15,000	Yes	
PAR30	E26	12.0	36920	LED12DP309CSW-1	1	6	900	2700	92	75	15,000	Yes	
PAR30	E26	12.0	36921	LED12DP309CDL-1	1	6	900	5000	92	75	15,000	Yes	
PAR30L	E26	12	84407	LED12DP3LRW92740	1	6	850	2700	90	75W	25,000	Yes	★
PAR30L	E26	12	84399	LED12DP3LRW93025	1	6	900	3000	90	75W	25,000	Yes	★
PAR30L	E26	12	84400	LED12DP3LRW93040	1	6	900	3000	90	75W	25,000	Yes	★
PAR30L	E26	18	75065	LED18P30LW93015	1	6	1400	3000	90	75W	25,000	-	★
PAR30L	E26	18	75078	LED18P30LW93025	1	6	1400	3000	90	75W	25,000	-	★
PAR30L	E26	12.0	43096	LED12DP3L9CSW2P	2	6	900	2700	92	75	15,000	Yes	
PAR30L	E26	12.0	36925	LED12DP3L9CSW-1	1	6	1,050	2700	92	75	15,000	Yes	
PAR30L	E26	12.0	43098	LED12DP3L9CDL2P	2	6	900	5000	92	75	15,000	Yes	
PAR30L	E26	12.0	36926	LED12DP3L9CDL-1	1	6	1,050	5000	92	75	15,000	Yes	
PAR38	E26	16.0	43076	LED16DP389CWW-2P	2	6	1,300	2700	92	120	15,000	Yes	
PAR38	E26	16.0	43093	LED16DP389CDL-2P	2	6	1,300	5000	92	120	15,000	Yes	
PAR38	E26	18	92923	LED18D38W3927/25	1	6	1250	2700	92	100W	25,000	Yes	★
PAR38	E26	18	92926	LED18D38W3927/40	1	6	1250	2700	92	120W	25,000	Yes	★
PAR38	E26	18	92927	LED18D38W3930/15	1	6	1350	3000	92	75W	25,000	Yes	★
PAR38	E26	18	92933	LED18D38W3930/25	1	6	1350	3000	92	100W	25,000	Yes	★
PAR38	E26	18	92934	LED18D38W3930/40	1	6	1350	3000	92	120W	25,000	Yes	★
PAR38	E26	15.0	45249	LED15DP389CWW2P	2	6	1,200	3000	92	90	15,000	Yes	
PAR38	E26	15.0	45272	LED15DP389CDL2P	2	6	1,200	5000	92	90	15,000	Yes	
PAR38	E26	16.0	36909	LED16DP389CWW-1	1	6	1,300	2700	92	120	15,000	Yes	
PAR38	E26	16.0	36913	LED16DP389CDL-1	1	6	1,300	5000	92	120	15,000	Yes	
PAR38	E26	15.0	36930	LED15DP389CWW-1	1	6	1,200	3000	92	90	15,000	Yes	
PAR38	E26	15.0	36933	LED15DP389CDL-1	1	6	1,200	5000	92	90	15,000	Yes	
PAR38	E26	15.0	48266	LED15DP389CWWB-1	1	6	1,200	3000	90	90	10000	Yes	
PAR38	E26	15.0	48267	LED15DP389CWWB-2	2	6	1,200	3000	90	90	10000	Yes	
RS Can	E26	9.0	47852	LED9DRS69CSW-2P	2	4	750	2700	90	65	15000	Yes	
RS Can	E26	9.0	47853	LED9DRS69CDL-2P	2	4	750	5000	90	65	15000	Yes	

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

<http://products.currentbyge.com>.

LED replacement Tubes

Integrated Plastic Tubes - Type A

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC®	UL	#Location Rating	Additional Information
Integrated 4ft LED Plastic Tubes (operates on Instant Start or Program Start Ballast)																
T8	G13	18	31550	LED18ET8/4/830	25	48	2450	3000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	18	93133	LED18ET8/4/835	25	48	2550	3500K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	18	93135	LED18ET8/4/840	25	48	2550	4000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	18	93140	LED18ET8/4/850	25	48	2650	5000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	15	62399	LED15ET8/4/830	25	48	2150	3000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	15	62401	LED15ET8/4/835	25	48	2250	3500K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	15	62402	LED15ET8/4/840	25	48	2250	4000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	15	62409	LED15ET8/4/850	25	48	2350	5000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	15	62410	LED15ET8/4/865	25	48	2350	6500K	80+			70,000	-	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	12	61218	LED12ET8/4/830	25	48	1750	3000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	12	61223	LED12ET8/4/835	25	48	1800	3500K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	12	61271	LED12ET8/4/840	25	48	1800	4000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	12	61327	LED12ET8/4/850	25	48	1900	5000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	12	61329	LED12ET8/4/865	25	48	1900	6500K	80+			70,000	-	Yes	Damp	Instant or PRS Ballast, NSF Rated
Integrated 3ft LED Plastic Tubes (operates on Instant Start or Program Start Ballast)																
	G13	12	31554	LED12ET8/3/830	25	36	1500	3000K	80+			70,000	-	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	12	26544	LED12ET8/3/835	25	36	1550	3500K	80+			70,000	-	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	12	26625	LED12ET8/3/840	25	36	1550	4000K	80+			70,000	-	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	12	26627	LED12ET8/3/850	25	36	1650	5000K	80+			70,000	-	Yes	Damp	Instant or PRS Ballast, NSF Rated
Integrated 2ft LED Plastic Tubes (operates on Instant Start or Program Start Ballast)																
	G13	9	31557	LED9ET8/2/830	25	24	1350	3000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	9	26635	LED9ET8/2/835	25	24	1350	3500K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	9	26648	LED9ET8/2/840	25	24	1400	4000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated
	G13	9	26676	LED9ET8/2/850	25	24	1400	5000K	80+			70,000	Yes	Yes	Damp	Instant or PRS Ballast, NSF Rated
Integrated U6 Plastic Tubes																
	G13	13	43120	LED13ET8/U6/830	12	22.5	1800	3000K	80+			50,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	13	43125	LED13ET8/U6/835	12	22.5	1850	3500K	80+			50,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	13	43129	LED13ET8/U6/840	12	22.5	1900	4000K	80+			50,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	13	43130	LED13ET8/U6/850	12	22.5	1900	5000K	80+			50,000	Yes	Yes	Damp	Instant or PRS Ballast

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

<http://products.currentbyge.com>.

LED replacement tubes

Integrated Glass Tubes - Type A

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC*	UL	#Location Rating	Additional Information
Integrated 4 ft LED Glass Tubes (operates on Instant Start or Program Start Ballast)																
T8	G13	18	35767	LED18ET8/G/4/830		20	48	2400	3000K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	18	35768	LED18ET8/G/4/835		20	48	2500	3500K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	18	35769	LED18ET8/G/4/840		20	48	2500	4000K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	18	35772	LED18ET8/G/4/850		20	48	2600	5000K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	18	35773	LED18ET8/G/4/865		20	48	2600	6500K	80+		70,000	-	Yes	Damp	Instant or PRS Ballast
	G13	15	35790	LED15ET8/G/4/830		20	48	2100	3000K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	15	35791	LED15ET8/G/4/835		20	48	2200	3500K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	15	35793	LED15ET8/G/4/840		20	48	2200	4000K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	15	35797	LED15ET8/G/4/850		20	48	2300	5000K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	15	35798	LED15ET8/G/4/865		20	48	2300	6500K	80+		70,000	-	Yes	Damp	Instant or PRS Ballast
	G13	13.5	21309	LED13ET8G4/830US		20	48	1900	3000K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast- Assembled in USA
	G13	13.5	21344	LED13ET8G4/835US		20	48	2000	3500K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast- Assembled in USA
	G13	13.5	21373	LED13ET8G4/840US		20	48	2000	4000K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast- Assembled in USA
	G13	13.5	21377	LED13ET8G4/850US		20	48	2000	5000K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast- Assembled in USA
	G13	12	43284	LED12ET8/G/4/830		20	48	1700	3000K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	12	43288	LED12ET8/G/4/835		20	48	1750	3500K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	12	43291	LED12ET8/G/4/840		20	48	1750	4000K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	12	43293	LED12ET8/G/4/850		20	48	1850	5000K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	10	34277	LED10ET8/G/4/830		20	48	1550	3000K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	10	34279	LED10ET8/G/4/835		20	48	1600	3500K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	10	34280	LED10ET8/G/4/840		20	48	1600	4000K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	10	34282	LED10ET8/G/4/850		20	48	1650	5000K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
Integrated 4 ft 50K Value LED Glass Tubes (operates on Instant Start or Program Start Ballast)																
	G13	14	34283	LED14ET8/G/4/830		20	48	1950	3000K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	14	34289	LED14ET8/G/4/835		20	48	2000	3500K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	14	34291	LED14ET8/G/4/840		20	48	2000	4000K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	14	34300	LED14ET8/G/4/850		20	48	2050	5000K	80+		50,000	Yes	Yes	Damp	Instant or PRS Ballast
Integrated 3 ft LED Glass Tubes (operates on Instant Start or Program Start Ballast)																
	G13	11	35783	LED11ET8/G/3/830		20	36	1450	3000K	80+		70,000	-	Yes	Damp	Instant or PRS Ballast
	G13	11	35784	LED11ET8/G/3/835		20	36	1500	3500K	80+		70,000	-	Yes	Damp	Instant or PRS Ballast
	G13	11	35788	LED11ET8/G/3/840		20	36	1500	4000K	80+		70,000	-	Yes	Damp	Instant or PRS Ballast
	G13	11	35789	LED11ET8/G/3/850		20	36	1600	5000K	80+		70,000	-	Yes	Damp	Instant or PRS Ballast
Integrated 2 ft LED Glass Tubes (operates on Instant Start or Program Start Ballast)																
	G13	8	35775	LED8ET8/G/2/830		20	24	1300	3000K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	8	35776	LED8ET8/G/2/835		20	24	1350	3500K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	8	35778	LED8ET8/G/2/840		20	24	1350	4000K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	8	35779	LED8ET8/G/2/850		20	24	1400	5000K	80+		70,000	Yes	Yes	Damp	Instant or PRS Ballast

Integrated Glass Tubes with reveal® TriGain™ Technology - Type A

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC*	UL	#Location Rating	Additional Information
Integrated 4 ft High CRI with reveal® TriGain™ Technology LED Glass Tubes (operates on Instant Start or Program Start Ballast)																
	G13	15	34307	LED15ET8/G/4/935		20	48	2150	3500K	90		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	15	34313	LED15ET8/G/4/940		20	48	2200	4000K	90		70,000	Yes	Yes	Damp	Instant or PRS Ballast
	G13	15	34316	LED15ET8/G/4/950		20	48	2250	5000K	90		70,000	Yes	Yes	Damp	Instant or PRS Ballast
Integrated 3 ft High CRI with reveal® TriGain™ Technology LED Glass Tubes (operates on Instant Start or Program Start Ballast)																
	G13	11	34323	LED11ET8/G/3/935		20	36	1500	3500K	90		70,000	-	Yes	Damp	Instant or PRS Ballast
	G13	11	34326	LED11ET8/G/3/940		20	36	1500	4000K	90		70,000	-	Yes	Damp	Instant or PRS Ballast
	G13	11	34332	LED11ET8/G/3/950		20	36	1600	5000K	90		70,000	-	Yes	Damp	Instant or PRS Ballast
Integrated 2 ft High CRI with reveal® TriGain™ Technology LED Glass Tubes (operates on Instant Start or Program Start Ballast)																
	G13	9	34337	LED9ET8/G/2/935		20	24	1300	3500K	90		70,000	-	Yes	Damp	Instant or PRS Ballast
	G13	9	34341	LED9ET8/G/2/940		20	24	1300	4000K	90		70,000	-	Yes	Damp	Instant or PRS Ballast
	G13	9	34342	LED9ET8/G/2/950		20	24	1400	5000K	90		70,000	-	Yes	Damp	Instant or PRS Ballast

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)
 ** Minimum order quantity = 6

UL 1993 Environmental Requirements for LED LAMPS
 Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.
 Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.
 Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at
<http://products.currentbyge.com>

LED replacement tubes

Integrated Glass Tubes - Type A

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (in)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC*	UL	#Location Rating	Additional Information
Integrated 4 ft LED Glass T5 HO Tubes (operates on Instant Start or Program Start Ballast)																
T5	G5	25.5	19203	LED26ET5/G/4/830		20	46	3650	3000K	80+		50,000	Yes	Yes	Damp	Requires T5 HO Ballast
	G5	25.5	19221	LED26ET5/G/4/835		20	46	3750	3500K	80+		50,000	Yes	Yes	Damp	Requires T5 HO Ballast
	G5	25.5	19227	LED26ET5/G/4/840		20	46	3800	4000K	80+		50,000	Yes	Yes	Damp	Requires T5 HO Ballast
	G5	25.5	19348	LED26ET5/G/4/850		20	46	3900	5000K	80+		50,000	Yes	Yes	Damp	Requires T5 HO Ballast
	G5	25.5	19488	LED26ET5/G/4/865		20	46	3800	6500K	80+		50,000	-	Yes	Damp	Requires T5 HO Ballast
Integrated 2 ft LED Glass T5 HO Tubes (operates on Instant Start or Program Start Ballast)																
	G5	11	34413	LED11ET5/G/2/830		20	22	1500	3000K	80+		50,000	-	Yes	Damp	Requires T5 HO Ballast
	G5	11	34417	LED11ET5/G/2/835		20	22	1550	3500K	80+		50,000	-	Yes	Damp	Requires T5 HO Ballast
	G5	11	34418	LED11ET5/G/2/840		20	22	1600	4000K	80+		50,000	-	Yes	Damp	Requires T5 HO Ballast
	G5	11	34424	LED11ET5/G/2/850		20	22	1600	5000K	80+		50,000	-	Yes	Damp	Requires T5 HO Ballast
Integrated 4 ft LED Glass T5 HE Tubes (operates on Instant Start or Program Start Ballast)																
	G5	13	34351	LED13ET5G4/830HE		20	46	1900	3000K	80+		50,000	-	Yes	Damp	Requires T5 HE Ballast
	G5	13	34354	LED13ET5G4/835HE		20	46	1950	3500K	80+		50,000	-	Yes	Damp	Requires T5 HE Ballast
	G5	13	34355	LED13ET5G4/840HE		20	46	2000	4000K	80+		50,000	-	Yes	Damp	Requires T5 HE Ballast
	G5	13	34367	LED13ET5G4/850HE		20	46	2000	5000K	80+		50,000	-	Yes	Damp	Requires T5 HE Ballast
Integrated 3 ft LED Glass T5 HE Tubes (operates on Instant Start or Program Start Ballast)																
	G5	10	34371	LED10ET5G3/830HE		20	34	1500	3000K	80+		50,000	-	Yes	Damp	Requires T5 HE Ballast
	G5	10	34376	LED10ET5G3/835HE		20	34	1550	3500K	80+		50,000	-	Yes	Damp	Requires T5 HE Ballast
	G5	10	34401	LED10ET5G3/840HE		20	34	1600	4000K	80+		50,000	-	Yes	Damp	Requires T5 HE Ballast
	G5	10	34402	LED10ET5G3/850HE		20	34	1600	5000K	80+		50,000	-	Yes	Damp	Requires T5 HE Ballast
Integrated 2 ft LED Glass T5 HE Tubes (operates on Instant Start or Program Start Ballast)																
	G5	7	34403	LED7ET5/G2/830HE		20	22	1000	3000K	80+		50,000	-	Yes	Damp	Requires T5 HE Ballast
	G5	7	34404	LED7ET5/G2/835HE		20	22	1100	3500K	80+		50,000	-	Yes	Damp	Requires T5 HE Ballast
	G5	7	34411	LED7ET5/G2/840HE		20	22	1150	4000K	80+		50,000	-	Yes	Damp	Requires T5 HE Ballast
	G5	7	34412	LED7ET5/G2/850HE		20	22	1150	5000K	80+		50,000	-	Yes	Damp	Requires T5 HE Ballast

Ballast Bypass Glass Tubes - Type B

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (in)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC*	UL	#Location Rating	Additional Information
Ballast Bypass- 4 ft LED Glass Tubes																
T8	G13	15	34435	LED15BT8/G4/830	120-277	20	48	2000	3000K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
	G13	15	31919	LED15BT8/G4/835	120-277	20	48	2050	3500K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
	G13	15	31933	LED15BT8/G4/840	120-277	20	48	2100	4000K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
	G13	15	31935	LED15BT8/G4/850	120-277	20	48	2100	5000K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
Ballast Bypass- 3 ft LED Glass Tubes																
	G13	13	34472	LED13BT8/G3/830	120-277	20	36	1700	3000K	80+		50,000	-	Yes	Damp	Single-ended, In-line fuse Required
	G13	13	34474	LED13BT8/G3/835	120-277	20	36	1800	3500K	80+		50,000	-	Yes	Damp	Single-ended, In-line fuse Required
	G13	13	34477	LED13BT8/G3/840	120-277	20	36	1850	4000K	80+		50,000	-	Yes	Damp	Single-ended, In-line fuse Required
	G13	13	34478	LED13BT8/G3/850	120-277	20	36	1900	5000K	80+		50,000	-	Yes	Damp	Single-ended, In-line fuse Required
Ballast Bypass- 2 ft LED Glass Tubes																
	G13	8	34468	LED8BT8/G2/830	120-277	20	24	950	3000K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
	G13	8	32125	LED8BT8/G2/835	120-277	20	24	1000	3500K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
	G13	8	32133	LED8BT8/G2/840	120-277	20	24	1000	4000K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
	G13	8	32134	LED8BT8/G2/850	120-277	20	24	1100	5000K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
Ballast Bypass Type B LED U6-Tubes																
	2G13	13	34480	LED13BT8/U6/830	120-277	12	36	1800	3000K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
	2G13	13	34481	LED13BT8/U6/835	120-277	12	36	1850	3500K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
	2G13	13	34482	LED13BT8/U6/840	120-277	12	36	1900	4000K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
	2G13	13	34484	LED13BT8/U6/850	120-277	12	36	1900	5000K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
Ballast Bypass Type B LED U1-5/8-Tubes																
	2G13	13	34487	LED13BT8/U/830	120-277	15	22.5	1750	3000K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
	2G13	13	34489	LED13BT8/U/835	120-277	15	22.5	1800	3500K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required
	2G13	13	34499	LED13BT8/U/840	120-277	15	22.5	1850	4000K	80+		50,000	Yes	Yes	Damp	Single-ended, In-line fuse Required

In-Line Fuse & Socket Kit - Type B

Order Code	Description	Kit Contents
32075	BT8-2L-KIT/NS	1 Fuse (1A), 2 Pre-wired sockets, Prewired quick disconnect.
32083	BT8-3L-KIT/NS	1 Fuse (1A), 3 Pre-wired sockets, Prewired quick disconnect.
32084	BT8-4L-KIT/NS	1 Fuse (1A), 4 Pre-wired sockets, Prewired quick disconnect.

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

*The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a “★” are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in “/TP” indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

<http://products.currentbyge.com>.

LED replacement tubes
Remote Plastic Tubes - Type C

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (in)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC®	UL	#Location Rating	Additional Information
Remote Plastic 4 ft LED Tubes (Operates on Remote Driver)																
T8	G13	18	94381	LED21T8/4/835		10	48	2650	3500K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	18	94382	LED21T8/4/840		10	48	2750	4000K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	18	94383	LED21T8/4/850		10	48	2850	5000K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	18	26059	LED21T8/4/865		10	48	2750	6500K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
	G13	13	38954	LED15T8/4/830		10	48	1950	3000K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	13	38958	LED15T8/4/840		10	48	2050	4000K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	13	38962	LED15T8/4/850		10	48	2100	5000K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	13	38964	LED15T8/4/865		10	48	2050	6500K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
Remote Plastic 3 ft LED Tubes (Operates on Remote Driver)																
	G13	16	82343	LED18T8/3/835		10	36	1800	3500K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
	G13	16	82345	LED18T8/3/840		10	36	1800	4000K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
	G13	16	82346	LED18T8/3/850		10	36	1800	5000K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
	G13	13	99692	LED15T8/3/830		20	36	1850	3000K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
	G13	13	99693	LED15T8/3/835		20	36	1900	3500K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
	G13	13	99694	LED15T8/3/840		20	36	1950	4000K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
	G13	13	99695	LED15T8/3/850		20	36	1950	5000K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
Remote Plastic 2 ft LED Tubes (Operates on Remote Driver)																
	G13	8	65706	LED9T8/2/835		20	24	1100	3500K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	8	65707	LED9T8/2/840		20	24	1150	4000K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	8	65711	LED9T8/2/850		20	24	1150	5000K	80+		70,000	Yes	Yes	Damp	Requires Driver, NSF Rated
	G13	8	92997	LED9T8/2/865		20	24	1000	5000K	80+		70,000	-	Yes	Damp	Requires Driver, NSF Rated
Remote Plastic LED U Tubes (Operates on Remote Driver)																
	G13	12	28084	LED14T8/U/835		15	22.5	1700	3500K	80+		50,000	Yes	Yes	Damp	Requires Driver
	G13	12	28164	LED14T8/U/840		15	22.5	1700	4000K	80+		50,000	Yes	Yes	Damp	Requires Driver

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)
** Minimum order quantity = 6
★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.
UL 1993 Environmental Requirements for LED LAMPS
Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.
Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.
Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.
Notes: 1) Product descriptions ending in "7TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at
http://products.currentbyge.com.

LED replacement lamps

Remote Glass Tubes - Type C

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC®	UL	#Location Rating	Additional Information
Remote 4ft LED Glass Tubes (Operates on Remote Driver)																
T8	G13	18	62428	LED21T8/G/4/835		10	48	2600	3500K	80+		70,000	Yes	Yes	Damp	Requires Driver
	G13	18	62485	LED21T8/G/4/840		10	48	2700	4000K	80+		70,000	Yes	Yes	Damp	Requires Driver
	G13	18	62487	LED21T8/G/4/850		10	48	2800	5000K	80+		70,000	Yes	Yes	Damp	Requires Driver
	G13	18	62406	LED21T8/G/4/835HL		10	48	3100	3500K	80+		70,000	Yes	Yes	Damp	Requires Driver
	G13	18	62407	LED21T8/G/4/840HL		10	48	3200	4000K	80+		70,000	Yes	Yes	Damp	Requires Driver
	G13	18	62408	LED21T8/G/4/850HL		10	48	3200	5000K	80+		70,000	Yes	Yes	Damp	Requires Driver
	G13	18	91475	LED21T8/G/4/830US		20	48	2600	3000K	80+		70,000	Yes	Yes	Damp	Requires Driver - Assembled in USA
	G13	18	91496	LED21T8/G/4/835US		20	48	2600	3500K	80+		70,000	Yes	Yes	Damp	Requires Driver - Assembled in USA
	G13	18	91497	LED21T8/G/4/840US		20	48	2600	4000K	80+		70,000	Yes	Yes	Damp	Requires Driver - Assembled in USA
	G13	18	91498	LED21T8/G/4/850US		20	48	2600	5000K	80+		70,000	Yes	Yes	Damp	Requires Driver - Assembled in USA
	G13	13	99696	LED15T8/G/4/830US		20	48	1950	3000K	80+		70,000	Yes	Yes	Damp	Requires Driver - Assembled in USA
	G13	13	99697	LED15T8/G/4/835US		20	48	2050	3500K	80+		70,000	Yes	Yes	Damp	Requires Driver - Assembled in USA
	G13	13	99698	LED15T8/G/4/840US		20	48	2100	4000K	80+		70,000	Yes	Yes	Damp	Requires Driver - Assembled in USA
	G13	13	99699	LED15T8/G/4/850US		20	48	2100	5000K	80+		70,000	Yes	Yes	Damp	Requires Driver - Assembled in USA
	G13	13	38944	LED15T8/G/4/830		10	48	1850	3000K	80+		70,000	Yes	Yes	Damp	Requires Driver
	G13	13	38945	LED15T8/G/4/835		10	48	1900	3500K	80+		70,000	Yes	Yes	Damp	Requires Driver
	G13	13	38950	LED15T8/G/4/840		10	48	1950	4000K	80+		70,000	Yes	Yes	Damp	Requires Driver
	G13	13	38951	LED15T8/G/4/850		10	48	2050	5000K	80+		70,000	Yes	Yes	Damp	Requires Driver
	G13	13	38952	LED15T8/G/4/865		10	48	1950	6500K	80+		70,000	-	Yes	Damp	Requires Driver
	G13	10	76194	LED12T8/G/4/830		10	48	1550	3000K	80+		70,000	Yes	Yes	Damp	Requires Driver
	G13	10	76264	LED12T8/G/4/835		10	48	1600	3500K	80+		70,000	Yes	Yes	Damp	Requires Driver
	G13	10	76265	LED12T8/G/4/840		10	48	1650	4000K	80+		70,000	Yes	Yes	Damp	Requires Driver
	G13	10	76271	LED12T8/G/4/850		10	48	1650	5000K	80+		70,000	Yes	Yes	Damp	Requires Driver
Remote 3ft LED Glass Tubes (Operates on Remote Driver)																
	G13	13	99687	LED15T8/G/3/830		20	36	1800	3000K	80+		70,000	-	Yes	Damp	Requires Driver
	G13	13	99688	LED15T8/G/3/835		20	36	1850	3500K	80+		70,000	-	Yes	Damp	Requires Driver
	G13	13	99689	LED15T8/G/3/840		20	36	1900	4000K	80+		70,000	-	Yes	Damp	Requires Driver
	G13	13	99691	LED15T8/G/3/850		20	36	1900	5000K	80+		70,000	-	Yes	Damp	Requires Driver
	G13	16	38257	LED18T8/G/3/830		20	36	1800	3000K	80+		70,000	-	Yes	Damp	Requires Driver
	G13	16	38258	LED18T8/G/3/835		20	36	1800	3500K	80+		70,000	-	Yes	Damp	Requires Driver
	G13	16	38260	LED18T8/G/3/840		20	36	1900	4000K	80+		70,000	-	Yes	Damp	Requires Driver
	G13	16	38261	LED18T8/G/3/850		20	36	1900	5000K	80+		70,000	-	Yes	Damp	Requires Driver
Remote 2ft LED Glass Tubes (Operates on Remote Driver)																
	G13	8	38933	LED9T8/G/2/830		20	24	1000	3000K	80+		70,000	Yes	Yes	Damp	Requires Driver
	G13	8	38935	LED9T8/G/2/835		20	24	1000	3500K	80+		70,000	Yes	Yes	Damp	Requires Driver
	G13	8	38936	LED9T8/G/2/840		20	24	1100	4000K	80+		70,000	Yes	Yes	Damp	Requires Driver
	G13	8	38939	LED9T8/G/2/850		20	24	1100	5000K	80+		70,000	Yes	Yes	Damp	Requires Driver
	G13	8	38943	LED9T8/G/2/865		20	24	1000	6500K	80+		70,000	-	Yes	Damp	Requires Driver
Remote 8ft LED Glass Tubes (Operates on Remote Driver)																
	Fa8	30	62326	LED36T8/G/8/830		20	96	4200	3000K	80+		50,000	-	Yes	Damp	Requires Driver - Assembled in USA
	Fa8	30	62327	LED36T8/G/8/835		20	96	4400	3500K	80+		50,000	-	Yes	Damp	Requires Driver - Assembled in USA
	Fa8	30	62329	LED36T8/G/8/840		20	96	4400	4000K	80+		50,000	-	Yes	Damp	Requires Driver - Assembled in USA
	Fa8	30	62349	LED36T8/G/8/850		20	96	4400	5000K	80+		50,000	-	Yes	Damp	Requires Driver - Assembled in USA
Remote Glass U6 Tubes (Operates on Remote Driver)																
	G13	13	43131	LED15T8/G/U6/830		12	22.5	1700	3000K	80+		50,000	Yes	Yes	Damp	Requires Driver
	G13	13	43135	LED15T8/G/U6/835		12	22.5	1800	3500K	80+		50,000	Yes	Yes	Damp	Requires Driver
	G13	13	43143	LED15T8/G/U6/840		12	22.5	1800	4000K	80+		50,000	Yes	Yes	Damp	Requires Driver
	G13	13	43145	LED15T8/G/U6/850		12	22.5	1800	5000K	80+		50,000	Yes	Yes	Damp	Requires Driver

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in “/TP” indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at
<http://products.currentbyge.com>.

LED replacement lamps

Remote Glass Tubes - Type C

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (in)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC®	UL	#Location Rating	Additional Information
Remote 4ft LED Glass T5 HO Tubes (Operates on Remote Driver)																
T5	G5	31	91973	LED36T5/G/4/830	20	46	4300	3000K	80+			50,000	Yes	Yes	Damp	Requires Driver
	G5	31	91976	LED36T5/G/4/835	20	46	4400	3500K	80+			50,000	Yes	Yes	Damp	Requires Driver
	G5	31	91977	LED36T5/G/4/840	20	46	4400	4000K	80+			50,000	Yes	Yes	Damp	Requires Driver
	G5	31	91997	LED36T5/G/4/850	20	46	4700	5000K	80+			50,000	Yes	Yes	Damp	Requires Driver
	G5	31	92006	LED36T5/G/4/865	20	46	4700	6500K	80+			50,000	-	Yes	Damp	Requires Driver
Remote 2ft LED Glass T5 HO Tubes (Operates on Remote Driver)																
	G5	13	76150	LED15T5/G/2/830	20	22	1800	3000K	80+			50,000	-	Yes	Damp	Requires Driver
	G5	13	76164	LED15T5/G/2/835	20	22	1850	3500K	80+			50,000	-	Yes	Damp	Requires Driver
	G5	13	76129	LED15T5/G/2/840	20	22	1900	4000K	80+			50,000	-	Yes	Damp	Requires Driver
	G5	13	76167	LED15T5/G/2/850	20	22	1900	5000K	80+			50,000	-	Yes	Damp	Requires Driver
	G5	13	76192	LED15T5/G/2/865	20	22	1900	6500K	80+			50,000	-	Yes	Damp	Requires Driver
Remote 4ft LED Glass T5 HE Tubes (Operates on Remote Driver)																
	G5	13	34176	LED15T5/G4/830HE	20	46	1900	3000K	80+			50,000	Yes	Yes	Damp	Requires Driver
	G5	13	34182	LED15T5/G4/835HE	20	46	1950	3500K	80+			50,000	Yes	Yes	Damp	Requires Driver
	G5	13	34192	LED15T5/G4/840HE	20	46	2000	4000K	80+			50,000	Yes	Yes	Damp	Requires Driver
	G5	13	34194	LED15T5/G4/850HE	20	46	2000	5000K	80+			50,000	Yes	Yes	Damp	Requires Driver
Remote 2ft LED Glass T5 HE Tubes (Operates on Remote Driver)																
	G5	8	34196	LED9T5/G2/830HE	20	22	1100	3000K	80+			50,000	-	Yes	Damp	Requires Driver
	G5	8	34197	LED9T5/G2/835HE	20	22	1150	3500K	80+			50,000	-	Yes	Damp	Requires Driver
	G5	8	34204	LED9T5/G2/840HE	20	22	1200	4000K	80+			50,000	-	Yes	Damp	Requires Driver
	G5	8	34205	LED9T5/G2/850HE	20	22	1200	5000K	80+			50,000	-	Yes	Damp	Requires Driver

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "7TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at
<http://products.currentbyge.com>.

LED replacement tubes

Regular Remote Drivers

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	Output Current (A)	Frequency	Eff	Output	Output Voltage	Temp (Min)	Temp (Max)	Dimmable	Additional Information
Lightech Drivers - Non-Dimming															
	18	93100	LED9T8/DR/UN/2L	120-277V	10	0.27x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	-	Maximum 2 Tubes (non potted)	
	24	76289	LED12T8/DR/2L	120-277V	10	0.21x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	-	Maximum 2 Tubes	
	30	38970	LED15T8/DR/UN/2L	120-277V	10	0.44x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	-	Maximum 2 Tubes (non potted)	
	36	82347	LED18T8/DR/UN/2L	120-277V	10	0.53x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	-	Maximum 2 Tubes (non potted)	
	21	94384	LED21T8/DR/1L	120-277V	10	0.62	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	-	Maximum 1 Tube	
	42	94385	LED21T8/DR/2L	120-277V	10	0.62x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	-	Maximum 2 Tubes	
Lightech Drivers - Dimming															
	24	76290	LED12T8/DR/D2L	120-277V	10	0.21x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 2 Tubes	
	48	76318	LED12T8/DR/D4L	120-277V	10	0.21x4	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 4 Tubes	
	42	28174	LED14/DR/D3L	120-277V	10	0.43x3	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 3 Tubes	
	30	38974	LED15T8/DR/D2L	120-277V	10	0.44x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 2 Tubes	
	60	38975	LED15T8/DR/D4L	120-277V	10	0.44x4	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 4 Tubes	
	36	88141	LED18T8/DR/D2L	120-277V	10	0.53x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 2 Tubes	
	72	88139	LED18T8/DR/D4L	120-277V	10	0.53x4	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 4 Tubes	
	42	60041	LED21T8/DR/D2L	120-277V	10	0.62x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 2 Tubes	
	84	62030	LED21T8/DR/D4L	120-277V	10	0.62x4	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 4 Tubes	
	72	63126	LED36T8/DR/D2L	120-277V	10	1.06x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 2 Tubes	
	144	92013	LED36T/DR/D4L	120-277V	10	1.06x4	50/60 Hz	>.9	DC	26-34V	-4 F	113F	Yes	Maximum 4 Tube	

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "7TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at
<http://products.currentbyge.com>.

GE LumenChoice™ Type C LED Tube and Driver System



Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED tubes are ideal for those seeking high energy savings with minimal installation time.

GE's LumenChoice™ Type C system utilizes one LED tube to create multiple lumen options via the wattage of the selected GE LED driver. See reverse for LED tubes and driver product details.

GE offers two driver platforms:

- 1) **Regular Drivers**-choose the desired fixed-wattage option based on the desired lumen output, i.e. 12W, 15W, 21W .
- 2) **LumenChoice™ Drivers**-adjust the wattage/lumen level on the driver, in the field i.e. toggle from 9W, 12W, 16W. This option simplifies bill of materials and inventory even further, and allows for making on-the-fly wattage/lumen adjustments at the point of installation.

FEATURES

- 2', 3' & 4' tubes
- Available in Plastic & Glass
- Assembled in USA options
- 1050 – 2,850 lumens
- >120 total system lumens per watt (LPW)
- 3000K, 3500K, 4000K, 5000K and 6500K color temperatures
- 70,000 hour rated life
- UL and cUL
- Open or Enclosed Fixtures
- Damp rating
- Dimmable (with dimming driver)
- 7 year warranty

PERFORMANCE BENEFITS

- Fast and Easy LED upgrade
- Low energy LFL replacement
- 2.3X Longer Life vs LFL (70,000 vs. 30,000 hours)
- Better quality of light –instant on
- Plastic-NSF rated, shatter resistant, prevents breakage and downtime
- Glass-270° light distribution
- Easy disposal, non-hazardous waste

General Lamp Product Information and Performance Data

General information						
Lamp Type	Base Type	CRI	Case Pack	Rated life (L70)	UL	Location Rating
T8	G13	80+	20	70,000	Yes	Damp

Performance Data

The tables below show the LumenChoice LED tubes in combination with regular fixed wattage driver options and LumenChoice™ driver options that will result in different lumen levels.

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

<http://products.currentbyge.com>.

GE LumenChoice™ Type C LED Tube and Driver System

Lamp Performance-Regular Drivers

2'-4' Glass and Regular Driver									
Lamp Product Code	4ft Glass	CCT	DLC [®]	Driver Wattage	LED12T8/DR/XX	LED15T8/DR/XX	LED18T8/DR/XX	LED21T8/DR/XX	Notes
	Lamp Description				12W	15W	18W	21W	
34211	LEDT8/LC/G/4/830	3000K	-	Initial Lumens	1550	1900	2250	2650	
34227	LEDT8/LC/G/4/835	3500K	-		1600	1950	2300	2700	
34235	LEDT8/LC/G/4/840	4000K	-		1600	1950	2300	2700	
34239	LEDT8/LC/G/4/850	5000K	-		1600	1950	2300	2700	
Lamp Product Code	4ft US Glass	CCT	DLC [®]	Driver Wattage	LED12T8/DR/XX	LED15T8/DR/XX	LED18T8/DR/XX	LED21T8/DR/XX	Notes
	Lamp Description				12W	15W	18W	21W	
36385	LEDT8LC/G4/830US	3000K	-	Initial Lumens	1550	1900	2250	2650	
36386	LEDT8LC/G4/835US	3500K	-		1600	1950	2300	2700	
36389	LEDT8LC/G4/840US	4000K	-		1600	1950	2300	2700	
36390	LEDT8LC/G4/850US	5000K	-		1600	1950	2300	2700	
Lamp Product Code	3ft Glass	CCT	DLC [®]	Driver Wattage	LED12T8/DR/XX	LED15T8/DR/XX	LED18T8/DR/XX	Notes	Notes
	Lamp Description				12W	15W	18W		
36394	LEDT8/LC/G/3/830	3000K	-	Initial Lumens	1550	1900	2250		
36395	LEDT8/LC/G/3/835	3500K	-		1600	1950	2300		
36398	LEDT8/LC/G/3/840	4000K	-		1600	1950	2300		
36401	LEDT8/LC/G/3/850	5000K	-		1600	1950	2300		
Lamp Product Code	2ft Glass	CCT	DLC [®]	Driver Wattage	LED9T8/DR/XX	LED12T8/DR/XX			
	Lamp Description				9W	12W			
36406	LEDT8/LC/G/2/830	3000K	-	Initial Lumens	1100	1450			
36408	LEDT8/LC/G/2/835	3500K	-		1200	1550			
36409	LEDT8/LC/G/2/840	4000K	-		1200	1550			
36413	LEDT8/LC/G/2/850	5000K	-		1200	1550			

2'-4' Plastic and Regular Driver									
Lamp Product Code	4ft Plastic	CCT	DLC [®]	Driver Wattage	LED12T8/DR/XX	LED15T8/DR/XX	LED18T8/DR/XX	LED21T8/DR/XX	Notes
	Lamp Description				12W	15W	18W	21W	
34248	LEDT8/LC/4/830	3000K	-	Initial Lumens	1550	1850	2200	2600	
34249	LEDT8/LC/4/835	3500K	-		1550	1900	2250	2650	
34250	LEDT8/LC/4/840	4000K	-		1550	1900	2250	2650	
34253	LEDT8/LC/4/850	5000K	-		1550	1900	2250	2650	
34262	LEDT8/LC/4/865	6500K	-		1500	1800	2100	2500	
Lamp Product Code	3ft Plastic	CCT	DLC [®]	Driver Wattage	LED12T8/DR/XX	LED15T8/DR/XX	LED18T8/DR/XX	Notes	Notes
	Lamp Description				12W	15W	18W		
36416	LEDT8/LC/3/830	3000K	-	Initial Lumens	1500	1850	2200		
36419	LEDT8/LC/3/835	3500K	-		1550	1900	2250		
36420	LEDT8/LC/3/840	4000K	-		1550	1900	2250		
36435	LEDT8/LC/3/850	5000K	-		1550	1900	2250		
36436	LEDT8/LC/3/865	6500K	-		1500	1800	2150		
Lamp Product Code	2ft Plastic	CCT	DLC [®]	Driver Wattage	LED9T8/DR/XX	LED12T8/DR/XX			
	Lamp Description				9W	12W			
36437	LEDT8/LC/2/830	3000K	-	Initial Lumens	1150	1500			
36439	LEDT8/LC/2/835	3500K	-		1250	1600			
36440	LEDT8/LC/2/840	4000K	-		1250	1600			
36453	LEDT8/LC/2/850	5000K	-		1250	1600			
36459	LEDT8/LC/2/865	6500K	-		1250	1600			

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

<http://products.currentbyge.com>

GE LumenChoice™ Type C LED Tube and Driver System

Lamp Performance-LumenChoice™ Drivers

2'-4' Glass and LumenChoice Driver										
4ft Glass				Driver	Low Watt LumenChoice Driver			21378 - LED/DR/D2L/LW 21379 - LED/DR/D4L/LW		
Lamp Product Code	Lamp Description	CCT	DLC*	Wattage	8W	9W	12W	15W	16.5W	Notes
34211	LEDT8/LC/G/4/830	3000K	-	Initial Lumens	1050	1150	1550	1900	2000	Available in Q1
34227	LEDT8/LC/G/4/835	3500K	-		1050	1200	1600	1950	2050	Available in Q1
34235	LEDT8/LC/G/4/840	4000K	-		1050	1200	1600	1950	2050	Available in Q1
34239	LEDT8/LC/G/4/850	5000K	-		1050	1200	1600	1950	2050	Available in Q1
4ft Glass				Driver	High Watt LumenChoice Driver			21383 - LED/DR/D2L/HW 21392 - LED/DR/D4L/HW		
Lamp Product Code	Lamp Description	CCT	DLC*	Wattage	18W	19.5W	21W	23W	25W	Notes
34211	LEDT8/LC/G/4/830	3000K	-	Initial Lumens	2250	2500	2650	2850	2950	Available in Q1
34227	LEDT8/LC/G/4/835	3500K	-		2300	2550	2700	2900	3000	Available in Q1
34235	LEDT8/LC/G/4/840	4000K	-		2300	2550	2700	2900	3000	Available in Q1
34239	LEDT8/LC/G/4/850	5000K	-		2300	2550	2700	2900	3000	Available in Q1
4ft US Glass				Driver	Low Watt LumenChoice Driver			21378 - LED/DR/D2L/LW 21379 - LED/DR/D4L/LW		
Lamp Product Code	Lamp Description	CCT		Wattage	8W	9W	12W	15W	16.5W	
36385	LEDT8LC/G/4/830US	3000K	-	Initial Lumens	1050	1150	1550	1900	2000	Available in Q1
36386	LEDT8LC/G/4/835US	3500K	-		1050	1200	1600	1950	2050	Available in Q1
36389	LEDT8LC/G/4/840US	4000K	-		1050	1200	1600	1950	2050	Available in Q1
36390	LEDT8LC/G/4/850US	5000K	-		1050	1200	1600	1950	2050	Available in Q1
4ft US Glass				Driver	High Watt LumenChoice Driver			21383 - LED/DR/D2L/HW 21392 - LED/DR/D4L/HW		
Lamp Product Code	Lamp Description	CCT		Wattage	18W	19.5W	21W	23W	25W	
36385	LEDT8LC/G/4/830US	3000K	-	Initial Lumens	2250	2500	2650	2850	2950	Available in Q1
36386	LEDT8LC/G/4/835US	3500K	-		2300	2550	2700	2900	3000	Available in Q1
36389	LEDT8LC/G/4/840US	4000K	-		2300	2550	2700	2900	3000	Available in Q1
36390	LEDT8LC/G/4/850US	5000K	-		2300	2550	2700	2900	3000	Available in Q1
3ft Glass				Driver	Low Watt LumenChoice Driver			21378 - LED/DR/D2L/LW 21379 - LED/DR/D4L/LW		
Lamp Product Code	Lamp Description	CCT		Wattage	8W	9W	12W	15W	16.5W	
34211	LEDT8/LC/G/4/830	3000K	-	Initial Lumens	1050	1150	1550	1900	2050	Available in Q1
34227	LEDT8/LC/G/4/835	3500K	-		1050	1200	1600	1950	2100	Available in Q1
34235	LEDT8/LC/G/4/840	4000K	-		1050	1200	1600	1950	2100	Available in Q1
34239	LEDT8/LC/G/4/850	5000K	-		1050	1200	1600	1950	2100	Available in Q1
2ft Glass				Driver	Low Watt LumenChoice Driver			21378 - LED/DR/D2L/LW 21379 - LED/DR/D4L/LW		
Lamp Product Code	Lamp Description	CCT		Wattage	8W	9W	12W			
36406	LEDT8/LC/G/2/830	3000K	-	Initial Lumens	1000	1100	1450			Available in Q1
36408	LEDT8/LC/G/2/835	3500K	-		1050	1200	1550			Available in Q1
36409	LEDT8/LC/G/2/840	4000K	-		1050	1200	1550			Available in Q1
36413	LEDT8/LC/G/2/850	5000K	-		1050	1200	1550			Available in Q1

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "7/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

<http://products.currentbyge.com>.

GE LumenChoice™ Type C LED Tube and Driver System

Lamp Performance-LumenChoice™ Drivers

2'-4' Plastic and LumenChoice Driver										
4ft Plastic				Driver	Low Watt LumenChoice Driver			21378 - LED/DR/D2L/LW 21379 - LED/DR/D4L/LW		
Lamp Product Code	Lamp Description	CCT	DLC*	Wattage	8W	9W	12W	15W	16.5W	Notes
34248	LEDT8/LC/4/830	3000K	-	Initial Lumens	1000	1100	1500	1850	1950	Available in Q1
34249	LEDT8/LC/4/835	3500K	-		1000	1150	1550	1900	2000	Available in Q1
34250	LEDT8/LC/4/840	4000K	-		1000	1150	1550	1900	2000	Available in Q1
34253	LEDT8/LC/4/850	5000K	-		1000	1150	1550	1900	2000	Available in Q1
34262	LEDT8/LC/4/865	6500K	-		950	1100	1500	1800	1900	Available in Q1
4ft Plastic				Driver	High Watt LumenChoice Driver			21383 - LED/DR/D2L/HW 21392 - LED/DR/D4L/HW		
Lamp Product Code	Lamp Description	CCT	DLC*	Wattage	18W	19.5W	21W	23W	25W	Notes
34248	LEDT8/LC/4/830	3000K	-	Initial Lumens	2200	2450	2600	2800	2950	Available in Q1
34249	LEDT8/LC/4/835	3500K	-		2250	2500	2650	2850	3000	Available in Q1
34250	LEDT8/LC/4/840	4000K	-		2250	2500	2650	2850	3000	Available in Q1
34253	LEDT8/LC/4/850	5000K	-		2250	2500	2650	2850	3000	Available in Q1
34262	LEDT8/LC/4/865	6500K	-		2100	2350	2500	2700	2850	Available in Q1
3ft Plastic				Driver	Low Watt LumenChoice Driver			21378 - LED/DR/D2L/LW 21379 - LED/DR/D4L/LW		
Lamp Product Code	Lamp Description	CCT	DLC*	Wattage	8W	9W	12W	15W	16.5W	Notes
36416	LEDT8/LC/3/830	3000K	-	Initial Lumens	1000	1100	1500	1850	2000	Available in Q1
36419	LEDT8/LC/3/835	3500K	-		1000	1150	1550	1900	2050	Available in Q1
36420	LEDT8/LC/3/840	4000K	-		1000	1150	1550	1900	2050	Available in Q1
36435	LEDT8/LC/3/850	5000K	-		1000	1150	1550	1900	2050	Available in Q1
36436	LEDT8/LC/3/865	6500K	-		950	1100	1500	1800	1950	Available in Q1
2ft Plastic				Driver	Low Watt LumenChoice Driver			21378 - LED/DR/D2L/LW 21379 - LED/DR/D4L/LW		
Lamp Product Code	Lamp Description	CCT	DLC*	Wattage	8W	9W	12W			
36437	LEDT8/LC/2/830	3000K	-	Initial Lumens	1050	1150	1500			
36439	LEDT8/LC/2/835	3500K	-		1100	1250	1600			
36440	LEDT8/LC/2/840	4000K	-		1100	1250	1600			
36453	LEDT8/LC/2/850	5000K	-		1100	1250	1600			
36459	LEDT8/LC/2/865	6500K	-		1100	1250	1600			

GE LumenChoice™ Type C LED Tube and Driver System with reveal® TriGain™ Technology

Lamp Performance-Regular Drivers

2'-4' Glass and Regular Driver									
4ft Glass				Driver		LED12T8/DR/XX	LED15T8/DR/XX	LED18T8/DR/XX	
Lamp Product Code	Lamp Description	CCT	DLC®	Wattage		12W	15W	18W	Notes
34271	LEDT8/LC/G/4/935	3500K	-	Initial Lumens		1650	1950	2350	Available in July MTO, 12 Weeks
34273	LEDT8/LC/G/4/940	4000K	-			1700	2000	2400	Available in July MTO, 12 Weeks
34276	LEDT8/LC/G/4/950	5000K	-			1700	2050	2450	Available in July MTO, 12 Weeks
3ft Glass				Driver		LED12T8/DR/XX	LED15T8/DR/XX		
Lamp Product Code	Lamp Description	CCT		Wattage		12W	15W		
36338	LEDT8/LC/G/3/935	3500K	-	Initial Lumens		1600	1850		Available in July MTO, 12 Weeks
36355	LEDT8/LC/G/3/940	4000K	-			1650	1900		Available in July MTO, 12 Weeks
36362	LEDT8/LC/G/3/950	5000K	-			1700	1900		Available in July MTO, 12 Weeks
2ft Glass				Driver		LED9T8/DR/XX			
Lamp Product Code	Lamp Description	CCT		Wattage	9W				
36371	LEDT8/LC/G/2/935	3500K	-	Initial Lumens	1000				Available in July MTO, 12 Weeks
36378	LEDT8/LC/G/2/940	4000K	-		1100				Available in July MTO, 12 Weeks
36383	LEDT8/LC/G/2/950	5000K	-		1100				Available in July MTO, 12 Weeks

Lamp Performance-LumenChoice™ Drivers

2'-4' Glass and LumenChoice Driver										
4ft Glass				Driver	Low Watt LumenChoice Driver			21378 - LED/DR/D2L/LW 21379 - LED/DR/D4L/LW		
Lamp Product Code	Lamp Description	CCT	DLC*	Wattage	8W	9W	12W	15W	16.5W	Notes
34271	LEDT8/LC/G/4/935	3500K	-	Initial Lumens	1050	1200	1650	1950	2100	Available in Q1
34273	LEDT8/LC/G/4/940	4000K	-		1100	1250	1700	2000	2150	Available in Q1
34276	LEDT8/LC/G/4/950	5000K	-		1100	1250	1700	2050	2250	Available in Q1

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

<http://products.currentbyge.com>.

LED replacement Drivers

Regular Remote Drivers

Type	Watts	Order Code	Description	Volts	Case Qty**	Output Current (A)	Frequency	Eff	Output	Output Voltage	Temp (Min)	Temp (Max)	Dimmable	Additional Information
Lightech Drivers - Non-Dimming														
	18	93100	LED9T8/DR/UN/2L	120-277V	10	0.27x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	-	Maximum 2 Tubes (non potted)
	24	76289	LED12T8/DR/2L	120-277V	10	0.21x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	-	Maximum 2 Tubes
	30	38970	LED15T8/DR/UN/2L	120-277V	10	0.44x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	-	Maximum 2 Tubes (non potted)
	36	82347	LED18T8/DR/UN/2L	120-277V	10	0.53x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	-	Maximum 2 Tubes (non potted)
	21	94384	LED21T8/DR/1L	120-277V	10	0.62	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	-	Maximum 1 Tube
	42	94385	LED21T8/DR/2L	120-277V	10	0.62x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	-	Maximum 2 Tubes
Lightech Drivers - Dimming														
	24	76290	LED12T8/DR/D2L	120-277V	10	0.21x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 2 Tubes
	48	76318	LED12T8/DR/D4L	120-277V	10	0.21x4	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 4 Tubes
	42	28174	LED14/DR/D3L	120-277V	10	0.43x3	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 3 Tubes
	30	38974	LED15T8/DR/D2L	120-277V	10	0.44x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 2 Tubes
	60	38975	LED15T8/DR/D4L	120-277V	10	0.44x4	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 4 Tubes
	36	88141	LED18T8/DR/D2L	120-277V	10	0.53x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 2 Tubes
	72	88139	LED18T8/DR/D4L	120-277V	10	0.53x4	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 4 Tubes
	42	60041	LED21T8/DR/D2L	120-277V	10	0.62x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 2 Tubes
	84	62030	LED21T8/DR/D4L	120-277V	10	0.62x4	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 4 Tubes
	72	63126	LED36T8/DR/D2L	120-277V	10	1.06x2	50/60 Hz	>.9	DC	26-34V	-4 F	113 F	Yes	Maximum 2 Tubes
	144	92013	LED36T8/DR/D4L	120-277V	10	1.06x4	50/60 Hz	>.9	DC	26-34V	-4 F	113F	Yes	Maximum 4 Tube

LumenChoice™ Drivers

Type	Watts	Order Code	Description	Volts	Case Qty**	Output Current (A)	Frequency	Eff	Output	Output Voltage	Temp (Min)	Temp (Max)	Dimmable	Additional Information
Lumen Choice™ Drivers - Dimming														
	33	21378	LED/DR/D2L/LW	120-277V	10	0.48x2	50/60 Hz	>.9	DC	26-34V	-4 F	104 F	Yes	Maximum 2 Tubes, Available in Q1
	66	21379	LED/DR/D4L/LW	120-277V	10	0.48x4	50/60 Hz	>.9	DC	26-34V	-4 F	104 F	Yes	Maximum 4 Tubes, Available in Q1
	50	21383	LED/DR/D2L/HW	120-277V	10	0.72x2	50/60 Hz	>.9	DC	26-34V	-4 F	104 F	Yes	Maximum 2 Tubes, Available in Q1
	100	21392	LED/DR/D4L/HW	120-277V	10	0.72x4	50/60 Hz	>.9	DC	26-34V	-4 F	104 F	Yes	Maximum 4 Tubes, Available in Q1

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Get more information at

<http://products.currentbyge.com>.

Awaken like never before the moment you turn on GE's LED replacement lamp.

Light influences people's emotions, how they view their space and their world, and how they start and end their day. GE understands this and wants to help transform your stores, buildings or facilities, while ensuring your upfront investment is paid back as quickly as possible.

If you're inspired to enhance your space — with substantial savings — call your GE Lighting representative.

To experience what we've done for our existing customers, see case studies, videos and image galleries at <http://products.currentbyge.com>.



Product is compliant with material restriction requirements of RoHS

ENERGY STAR® is a registered U.S. mark

current
powered by GE

<http://products.currentbyge.com>.

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2018 GE.

78945 (Rev 09/19/2018)

