

34484 - Ballast Bypass U6 LED Glass Tubes

LED13BT8/U6/850

- Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED tubes are ideal for those seeking high energy savings with minimal installation time. The existing fixture is wired to bypass the ballast which further reduces energy use and eliminates the need to check ballast compatibility. Additional maintenance savings are realized by removing costs associated with replacing ballasts.
- Each LED tube is outfitted with a Single-ended In-line fuse
- 66% longer life than LFL (50 000 vs. 30 000 hours)
- Easy disposal non-hazardous waste
- UL Listed
- Check ballast compatibility at www.gelighting.com/LEDTUBESballast-compatibility
- For In-Line Fuse & Socket Kits please check our Awaken brochure.

PRODUCT PHOTO



GENERAL CHARACTERISTICS

Base Description	LED_Bs_G13
Base Type	G13
Dimmable	No
Product Technology	LED
Rated Life (Hours)	50000 h
Dimmable / Non-Dimmable	No
Lamp Count	1
Life in Years	45.7 yr
Requested Structure	Carton
Estimated Energy Cost per Year	1.57
Bulb Shape	T8

PHOTOMETRIC CHARACTERISTICS

Nominal Initial Lumen per Watt	146
Initial Lumens-nominal	1900 lm
Color Rendering Index-CRI	80
Color Temperature	5000 K

PRODUCT INFORMATION

Product Code	34484

Description LED13BT8/U6/850

Alternative Unit Of Measure CASE

Standard Package Quantity 12

Ean UPC 043168344845 Standard Package GTIN 10043168344842

No Of Items Per Sales Unit

No Of Items Per Standard Package 12 Sales Unit Case

UCC

Alternative Unit Of Measure EACH Standard Package Quantity 1

Ean UPC 043168344845 Standard Package GTIN 00043168344845

No Of Items Per Sales Unit

No Of Items Per Standard Package 1
Sales Unit Each

UCC

DIMENSIONS

Bulb Max Overall Length-MOL 36.0 in

ELECTRICAL CHARACTERISTICS

Voltage <Nom> 120 V Rated power (Watts) 12 W