



GE
Lighting

75950 - GEC225MVPS-A

GE CFL UltraStart™ High Lumen Biax™ Electronic MultiVolt Programmed Start Ballast

- Multi-Voltage Technology handles voltage from 120 to 277V
- A new generation of ultra-efficient Programmed Start ballasts (> 90% efficiency).
- Parallel Lamp Operation keeps lights on when one lamp fails
- Anti-Striation Control for better light quality, with no striations.
- Lamp End-of-Life Safety Shutdown Circuit with Re-Lamping Auto-reset
- Starting time visually the same as instant start



NOTES

- For 1 lamp application, cap unused blue lead, insulate for 600 Vrms

GENERAL CHARACTERISTICS

Lamp Type	Fluorescent -
Bulb	Electronic
Ballast Type	MultiVolt Programmed Start
Starting Method	Programmed start
Line Voltage Regulation (+/-)	10.0 %
Case Temperature (MAX)	70.0 °C
Ballast Factor	Normal
Power Factor Correction	Active
Sound Rating	A (20-24 decibels)
Enclosure Type	Metal
Additional Info	Auto-restart/Inherent thermal protection/Lamp End-of-Life Safety Shutdown Circuit/Anti-striation control

DIMENSIONS

Weight	1.4 lb
Exit Type	
Remote Mounting Distance	10.0 ft
Remote Mounting Wire	18.0 AWG
Gauge	

PRODUCT INFORMATION

Product Code	75950
Description	GEC225MVPS-A
Standard Package	Case
Standard Package GTIN	10043168759509
Standard Package Quantity	10
Sales Unit	Standard Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168759502