



Metal Halide & High Pressure Sodium 65W LED Replacement Lamp

**ETL Certified for Compliance
to UL1598C and UL1993**

- High Power Factor • Self Ballasted •
- Suitable for Open & Enclosed Fixtures •
- Bright • High CRI • High Lumen Output •
- Built-in Surge Suppressors & Protection •
- 5-Years / 50,000 Hours Warranty (*) •



US Patent D762,884 S

Available in:

CCT 5,500K $\pm 10\%$ (CW) for MH Replacement

CCT 3,000K $\pm 10\%$ (WW) for HPS Replacement






- Simple Installation • High Lumen per Watt • Rugged Design •

Model	Product	Size	Power	Flux	Equivalent
CL-65W8-55K-E39	LED Lamp 65W 360° 55K MH Replacement	$\varnothing 3\frac{1}{2} \times 8\frac{3}{4}$ "	73W Max.	9,300 Lumen	250W MH
CL-65W8-30K-E39	LED Lamp 65W 360° 30K HPS Replacement	$\varnothing 3\frac{1}{2} \times 8\frac{3}{4}$ "	73W Max.	8,600 Lumen	250W HPS

- 120-277Vac ~50/60Hz • PF > 0.9 • Med. (E26) or Mogul (E39) Lamp Base • ~100 lm/W • CRI > 75 •
- (*) Rated Life 50,000 Hrs. ($L_{70} B_{50}$) at $T_{[A]}$ 25°C Max. • CCT 5500K (55K) or 3000K (30K) $\pm 10\%$ •



65W Cluster LED Lamp



Model	Product	Power	Equivalent
CL-65W8-xxK-E39	Cluster LED Bulb	65W	250W MH/HPS
Input Voltage	Power/Power Factor	Efficacy	Flux
120-277Vac ~50/60Hz	73W Max. P.F. ≈ 0.97	~125 lm/W	9,300 Lumen (CW) 8,600 Lumen (WW)
Color Rendering	Color Temperature	Beam Angle	Life
CRI ÷ 75~80	30K ÷ CCT 3,000K ±10% 55K ÷ CCT 5,500K ±10%	360°	5-Years / 50,000 Hours (L ₇₀ B ₅₀) T _A 25°C Max.