## PL H 5.5W BYP E26 TITANIUM LED SERIES











- Built-in universal voltage driver Bypass installation
- Compatible with E26 bases
- Exceptional efficacy 102 LPW
- Lasts 4 times longer than CFL
- Ompact form factor fits most fixtures
- Available in 3000K, 3500K & 4000K
















#### PL PRODUCT FEATURES

#### **BYPass Installation**

This PL H lamp requires bypassing the ballast during installation and runs directly off line voltage to eliminate compatibility problems, incidental power loss, lifetime issues, and maintenance costs associated with ballasts.




#### Adjustable Base





This PL H lamp features a base that can be rotated 310° to fit any socket configuration. After installation simply rotate the lamp to achieve maximum light output.

# PL H 5.5W BYP E26 TITANIUM LED SERIES









1.34"(34mm)

5.66°(144mm)

Base: E26

**Voltage:** 120-277V

Dimmable: No PF: 0.9

Lifetime: 50,000 hrs
Weight: 0.15lb / 68g

### **SPECIFICATIONS**

Model	Product	Power (W)	сст	CRI (typ.)	Lumens	LPW	Beam Angle
5.5PLH/830/BYP/E26	98393	5.5	Warm White 3000K	82	550	100	110°
5.5PLH/835/BYP/E26	98394	5.5	Neutral White 3500K	82	550	100	110°
5.5PLH/840/BYP/E26	98395	5.5	Cool White 4000K	82	560	102	110°

<sup>\*</sup> Suitable for damp locations. Not for use where directly exposed to weather or water

<sup>\*\*</sup> Not intended for use in enclosed fixtures

<sup>\*\*\*</sup> Full installation guide and more details available on website