

7" ROUND DOWNLIGHT 15W TITANIUM LED SERIES



15W REPLACES



**75W
Inc.**

80% Energy Savings

CRI^{SP}



\$197 Savings
per lamp*

- ⌚ Innovative **CLICK** design
- ⌚ **SootheOptic** low glare technology
- ⌚ Fits most 4" J-boxes and 4" & 6" recessed housings
- ⌚ Installs in just minutes - no rewiring
- ⌚ **Wet location rated**
- ⌚ Exceptional color rendering **CRI 90, R9 60 & R13 94**



LM 79

LM 80

TM 21



50,000 H



DIMMABLE



LOW GLARE



WARRANTY



CRI (Ra)




WET LOCATION

DOWNLIGHT PRODUCT FEATURES

Edge Lighting Technology

The **CLICK DESIGN** SURFACE MOUNT SQUARE & ROUND DOWNLIGHTS use the latest in edge lighting technology to produce a smooth uniform lighting effect. These naturally low glare downlights integrate seamlessly into all ceiling applications.




- BACK PLATE
- WATERPROOF FOAM
- EDGE LIGHTING REFLECTOR
- LIGHT GUIDE PLATE
- TRIM**

SootheOptic Low Glare Technology

These downlights all feature **SootheOptic** technology that reduces high-angle light and minimizes visual glare. The smooth low glare diffuser gives each luminaire a soft cutoff without visible color separation.

Glare Control Diffuser



2.4mm Hex Pattern

Viewing Angle



0°

45°

>65°


7" ROUND DOWNLIGHT 15W TITANIUM LED SERIES



DUAL INSTALLATION

4" J-BOX FLUSHMOUNT

For all models



ACCESSORIES INCLUDED:

- Attach mounting bracket to J-box
- Click downlight into mounting bracket



Mounting Bracket



J-Box Screws




Wire Nuts



LED Adapter

4" & 6" CAN RECESSED

4" CAN - 5.5" & 7" models
6" CAN - 7" model only



ACCESSORIES SOLD SEPARATELY:

- Connect E26 adapter to the LED adapter
- Insert mounting clips and push downlight up until flush with ceiling



E26 Adapter



Mounting Clips



Ground Screw



LED Adapter

SPECIFICATIONS

Product Model	97978 15SMPR7DIM/927/R	97979 15SMPR7DIM/930/R	97980 15SMPR7DIM/940/R
Type	7" SMPR	7" SMPR	7" SMPR
Base	LED Adapter (E26 & GU24 optional)	LED Adapter (E26 & GU24 optional)	LED Adapter (E26 & GU24 optional)
Power (W)	15	15	15
Voltage - Frequency	120V 60Hz	120V 60Hz	120V 60Hz
Color Temp. (ANSI)	Soft White 2700K	Warm White 3000K	Cool White 4000K
CRI (Ra)	90	90	90
R9 / R13 (typ.)	60 / 94	60 / 94	60 / 94
Typical lumens (lm)	850	850	870
Efficacy (LPW)	57	57	58
Beam Angle	100°	100°	100°
Dimmable	Yes**	Yes**	Yes**
Housing Compatibility	4" J-box / Most 4" & 6" housing	4" J-box / Most 4" & 6" housing	4" J-box / Most 4" & 6" housing
Power Factor	0.9	0.9	0.9
Rated Lifetime - L70 (hrs.)	50,000	50,000	50,000
Dia. x MOL	7.17"x1.65" (182x42mm)	7.17"x1.65" (182x42mm)	7.17"x1.65" (182x42mm)
Weight (lb. / g)	0.88lb. / 399g	0.88lb. / 399g	0.88lb. / 399g

ACCESSORY ORDERING INFORMATION

Model	Product	Description
SMP/ACC	58033	4" or 6" Recessed Can Accessories for 5.5" & 7" Round & Square (5.5" for Use in 4" Can Only, 7" for Use in 4" or 6" Can)

* Savings per lamp based on \$0.11 / kw energy cost, 12 hrs / day lamp usage, \$4 incandescent with 1000-hr lifetime, \$35 LED with 50,000-hr lifetime

** List of tested dimmer switches available on website