

Exit & Emergency

Evade Emergency Wallpack

- LED Life-Cycle exceeding 10 years
- Architectural Low Profile Design
- 120-277 VAC Input
- Photocell with Enable/Disable Function
- Self Testing

Specifications

Description

The Evade Series Emergency Wallpack offers a quality emergency lighting solution in a low profile architectural design. This wallpack is ideal for egress and safety lighting on building exteriors and over doorways. .

Electrical

- 120-277 VAC Input
- Self Testing/Diagnostics
- Long-Life Maintenance Free NiCad Battery
- 24 Hour Recharge Time
- Photocell Enable/Disable

Certifications

- UL924
- NFPA 101 and NFPA 70
- CEC T20 Compliant
- Wet Location Listed



Construction & Mounting

- Diecast Aluminum Housing with Corrosion Resistant Powder Coat Finish
- Polycarbonate Lens
- Universal J-Box Mounting Pattern on Back Plate
- Low Profile Design
- 1/2" Threaded Conduit Entry at Top of Fixture

Exit & Emergency

Evade Emergency Wallpack

Ordering Information

Product SKU	Product Code	Product Description
95014	EV-WPK-EM	Evade Emergency Wallpack

Specifications Table

	EV-WPK-EM
Input Current	.125A(120VAC) - .54A(277VAC)
Input Wattage	15W
Battery	Ni-cad 4.8V 1.8Ah
Lumen Output	1200 LM
CCT	5000K
Recharge Time	24 Hours
Voltage	120-277 VAC
Frequency	60Hz
Housing	Die-Cast Aluminum Housing
Testing Function	Self Test/Diagnostics
Operating Temperature	0°C to 50°C
Listings & Compliance	UL 924, CEC Title 20, NFPA 70 & NFPA 101
Environment	Damp Location Listed
Warranty	2 Year Battery

Dimensions

