

LED Luminaires

Mini Bullet Flood Series

- Toolless adjustable head for precise illumination
- Reliable high lumen output and efficient COB LED
- Adjustable visor
- Multiple color temperatures
- Quick and easy installation
- Multiple finishes



Specifications

Description

The Mini Bullet Flood provides premium performance for increased safety and security. Featuring an efficient 10W LED floodlight supplying full light protection. With a sleek modern design and robust weather proof construction, the Mini Bullet is ideal for outdoor applications.

Performance

- Color temperatures: 3000K, 5000K
- Lifetime: more than 30,000 hrs
- >1050 Lumens
- >105 lm/W
- >80 CRI
- 120-277V
- Operating temperature: -40°C to 60°C

Construction

- Die-cast aluminum housing for superior thermal performance
- Internally sealed design to shield water and dust from entry
- Transparent PC optics
- Black and bronze finish

Certifications

- ETL
- Wet location

LED Luminaires

Mini Bullet Flood Series

Ordering Logic

Series	Wattage	CCT	Voltage	Finish
MBUL = Mini Bullet	10 = 10W	30 = 3000K 50 = 5000K	U = 120-277VAC	BL = Black BZ = Bronze

Ordering Information

Product SKU	Product Code	Product Description
24950	MBUL-10-30-U-BZ	Mini Bullet Flood, 10 Watt, 3000K, Universal 120-277 VAC, Bronze Finish
24951	MBUL-10-30-U-BL	Mini Bullet Flood, 10 Watt, 3000K, Universal 120-277 VAC, Black Finish
24952	MBUL-10-50-U-BZ	Mini Bullet Flood, 10 Watt, 5000K, Universal 120-277 VAC, Bronze Finish
24953	MBUL-10-50-U-BL	Mini Bullet Flood, 10 Watt, 5000K, Universal 120-277 VAC, Black Finish
Accessories		
998100	GS08	8" GROUND STAKE PVC 1629

Performance Table

Model Number	Nominal Wattage	3000K		5000K	
		Lumens	Efficacy (LPW)	Lumens	Efficacy (LPW)
MBUL-10-XX-X-XX	10W	1239	129	1284	136

Mini Bullet Flood Series

Specifications Table

	MBUL-10-30-U-XX
Nominal Wattage	10W
Lumens	1239-1284
CCT	3000K, 5000K
Efficacy	128 - 136 LPW
Amperage	120VAC(0.083A) 277VAC(.036A)
Beam Angle	100°
CRI	80 CRI
L70 Lifetime (Hrs)	30,000
Voltage	120-277V
Power Factor	>0.9
Housing	Die-Cast Aluminum Housing
Lens	PC Optics
Operating Temperature	-40°C to 60°C
Listings	ETL
Environment	Wet Location
Weight	0.55 lbs
Warranty	5 Years Standard

Dimensions

