

LNC3

LITEPAK

Midsized LED Wallpack – Zero Uplight

LED WALLPACKS



The midsized LED LNC3 is designed for perimeter illumination for safety, security and identity. No uplight and lower glare lenses offer neighbor friendly lighting at typical mounting heights of 10-20'. Units have protective polyester finish for long lasting appearance. Ideal for schools, factories, hospitals, warehouses and retail applications. Energy efficient LEDs provide up to 70% energy savings with little to no maintenance when compared to traditional light sources.

Die-cast aluminum housing protects components and provides an architectural appearance. Casting thermally conducts LED heat to optimize performance and long life. Powder paint finish provides durability in outdoor environments.

Quick-mount adapter with gasket seal provides easy installation to wall or to recessed junction

box (4" square junction box). Fixture attaches by two Allen-head hidden fasteners for tamper resistance. Designed for direct j-box mount or conduit feed on all four sides in single SKU.

- 120-277, 347 and 480 voltage, 50/60Hz,
- 0-10V dimming drivers standard
- IP-65 rated assembly
- Surge protection – 10kA
- 2 and 24 LED configurations available, see specification sheet for electrical and photometric data
- Zero uplight distributions using chip on board LEDs or individual acrylic LED optics
- 7-pin photo-receptacle available for twist lock photocell and controls by others
- Frosted acrylic diffuser available for reduced glare or inverted/up mounting (factory install only)



*3000K and warmer CCTs only

COB luminaire



STOCK

ORDERING INFORMATION

CATALOG NUMBER	DESCRIPTION	DISTRIBUTION	WATTAGE	LUMENS	LPW	VOLTAGE	# OF DRIVERS @ DRIVE CURRENT	WEIGHTS LBS. (KBS)
LNC3-2L4K-075	2 LED - 60W Configuration, 4000K, Dark Bronze	Type IV	62.0	5,857	94.8	120-277	1 @ 750mA	15.0 (6.8)
LNC3-2L4K-105	2 LED - 90W Configuration, 4000K, Dark Bronze		87.4	7,721	86.1		1 @ 1050mA	
LNC3-2L5K-105	2 LED - 90W Configuration, 5000K, Dark Bronze		87.4	7,288	82.0		1 @ 1050mA	
LNC3-2L4K-105-7PR	2 LED - 90W Configuration, 4000K, Dark Bronze, 7-Pin		87.4	7,721	86.1		1 @ 1050mA	
LNC3-2L4K-105-SCP	2 LED - 90W Configuration, 4000K, Dark Bronze, SCP		87.4	7,721	86.1		1 @ 1050mA	

MADE-TO-ORDER

ORDERING INFORMATION - CONFIGURABLE (SEE SPEC SHEET FOR PERFORMANCE INFORMATION AND DETAILS)

LNC3	-		-		-		-		-	
SERIES		CCT	IES DISTRIBUTION	VOLTAGE ⁷	FINISH	CONTROL OPTIONS	OPTIONS			
LNC3 Medium Litepak Wallpack		3K 3000K 4K 4000K 5K 5000K	2 Type II 3 Type III 4 Type IV	U 120v-277v 1 120v ¹ 2 208v ¹ 3 240v ¹ 4 277v ¹ 5 480v F 347v	DB Bronze BL Black WH White GR Gray PS Platinum CC Custom Color	PCU Universal button PC 7PR ⁶ 7-pin receptacle SCP ^{3,4} Programmable occupancy sensor SWP ^{1,7} SiteSync wireless pre-commissioned SWPM ^{1,4,7,8} SiteSync wireless pre-commissioned w/ occupancy sensor	F ¹ Fusing (must specify voltage per footnote) CS Comfort shield CSU ² Comfort shield up position E ^{1,5} Battery backup 0°C EH ^{1,5} Battery backup with heater rated for -30° C			
NUMBER OF LEDS		DRIVE CURRENT								
24L 24LEDs		050 500mA (41w) 075 750mA (60w) 105 500mA (83w)								

¹ Specify voltage for voltage specific option (battery backup 120 or 277V only, SiteSync 120, 277 or 347V only)

² Factory install only. Not available with SCP or SWPM sensor/control options

³ Must order minimum of one remote control to program dimming settings, 0-10V fully adjustable dimming with automatic daylight calibration and different time delay settings, 120-277V only.

⁴ PCU option not applicable, included in sensor

⁵ 500mA and 750mA version only. Not available with SWP or SWPM control options.

⁶ Accepts standard 3, 5, and 7-Pin ANSI controls (by others). Not available with PCU, SWP or SWPM control options

⁷ Must specify group and zone information at time or order. See www.hubbellighting.com/products/sitesync for further details.

⁸ Specify time delay; dimming level and mounting height

CATALOG NUMBER	DESCRIPTION
LNC3-CS	Frosted acrylic diffuser (comfort shield), improves uniformity with only 20% lumen reduction
SCP-REMOTE2*	Remote control for SCP option. Order at least one per project to program and control
SWUSB**	SiteSync loaded on USB flash drive (Windows based only)
SWTAB**	SiteSync Windows Tablet
SWBRG*	SiteSync Wireless Bridge Node

* Must order minimum of one remote control to program dimming settings, 0-10V fully adjustable dimming with automatic daylight calibration and different time delay settings, 120V or 277V only

** When ordering with SiteSync, one of the following interface options must be chosen and ordered separately. Each option contains the SiteSync License, GUI and Bridge Node.

+ If needed, an additional Bridge Node can be ordered.

LNC3





WITHOUT DIFFUSER
(Comfort Shield)



WITH DIFFUSER
(Comfort Shield)

DIMENSIONS

A	B	C	D	E	Weight	Weight w/BBU
12.9"	10.1"	9.6"	5.8"	7.3"	15 lbs.	16 lbs.
327 mm	257 mm	243 mm	146 mm	185 mm	6.8 kg	7.3 kg



HUBBELL
Outdoor Lighting