



LED WALL PACK FIXTURE



PRODUCT FEATURES

- Philips Lumileds 3030 LED Chips
- High Quality Tempered Glass Optics
- Heavy Duty Die-Cast Aluminum Housing with Quick Mount Back Plate for Easy Installation
- Integral Secondary Heat Sink to Optimize Thermal Transfer and Maximize Performance and Life of LED
- Polyester Powder Coated Finish - Rust & Corrosion Proof
- Drive is Mounted in Direct Contact with the Casting for Low Operating Temperature and Long Life
- IP65 Rating - Suitable for Wet Locations
- Operating Temperature: -40°F to 104°F (-40°C to 40°C)
- 120-277 Voltage Rating
- 50,000 Hour Lifetime Rating
- DLC Premium Listed
- ETL Listed
- 5-Year Limited Warranty

PRODUCT SPECIFICATIONS

MODEL	POWER (W)	LUMENS (LM)	CCT (K)	DIMENSIONS (IN)	EFFICIENCY (lm/W)	DIMMABLE
CLW99-604DWMBR-HLV	60	8580	4000	14.3 x 9.2 x 7.52	143	YES
CLW99-605DWMBR-HLV	60	8700	5000	14.3 x 9.2 x 7.52	145	YES
CLW99-804DWMBR-HLV	80	11,440	4000	14.3 x 9.2 x 7.52	143	YES
CLW99-805DWMBR-HLV	80	11,600	5000	14.3 x 9.2 x 7.52	145	YES
CLW99-1004DWMBR-HLV	100	14,300	4000	14.3 x 9.2 x 7.52	143	YES
CLW99-1005DWMBR-HLV	100	14,500	5000	14.3 x 9.2 x 7.52	145	YES
CLW99-1205DWMBR-HLV	120	17,400	5000	14.3 x 9.2 x 7.52	145	YES

