



LED FLOOD LAMP



15W, 30W & 50W
Knuckle Mount



30W & 50W
Yoke Mount



100W & 150W
Mount Sold Separately

PRODUCT FEATURES

- ADC12 Aluminum Heat Sink Housing
- Outdoor Powder Coating
- Bronze Finish
- IP65 Rating - Suitable for Wet Locations
- 100-277 Voltage Rating
- 50,000 Hour Lifetime Rating
- UL / DLC 4.4 Certified
- 5-Year Limited Warranty
- High Light Transmittance PC, Anti-UV and Fire Resistance Lens
- Highly Conductive, Waterproof, Aging Resistance, Salt Mist Resistance Aluminum LED Board
- Mounts sold separately for 100W & 150W Flood Lamps
 - Slip-Fitter - CLF4-SLIP-100/150 (9.35 x 2.36 x 2.95)
 - Straight Arm - CLF4-STRAIGHT-100/150 (7.14 x 6.73 x 3.54)
 - Trunnion - CLF4-TRUN-100/150 (5.71 x 6.57 x 1.97)

PRODUCT SPECIFICATIONS

MODEL	POWER (W)	LUMENS (LM)	CCT (K)	DIMENSIONS (IN)	EFFICIENCY (lm/W)	BEAM ANGLE / OPTIC TYPE	MOUNT
CLF4-155KNBR	15	1725	5000	4.72 x 3.27 x 2.60	115	90° x 120°	KNUCKLE
CLF4-305KNBR	30	3450	5000	6.89 x 4.76 x 3.07	115	90° x 120°	KNUCKLE
CLF4-305YKBR	30	3450	5000	6.89 x 4.76 x 3.07	115	90° x 120°	YOKE
CLF4-505KNBR	50	6000	5000	8.62 x 5.94 x 3.54	120	90° x 120°	KNUCKLE
CLF4-505YKBR	50	6000	5000	8.62 x 5.94 x 3.54	120	90° x 120°	YOKE
CLF4-100P5YYBR *	100	13,500	5000	11.00 x 12.58 x 3.38	135	TYPE III	-
CLF4-150P5YYBR *	150	20,250	5000	11.00 x 12.58 x 3.38	135	TYPE III	-

* DLC 4.4 PREMIUM

