

KT-BPLEDXXPS-XXC-8CSA-VDIM-EM8

BACKLIT LED PANEL LIGHT WITH INTEGRATED EMERGENCY PACK

DESCRIPTION

LED Panel | 120-277V input | 0-10V dimming



**5 YEAR
WARRANTY**

PRODUCT FEATURES

- Features Keystone Color Select technology. Adjust CCT between 3500/4000/5000K
- Features Keystone Power Select technology. (see Performance Specifications for details)
- Extruded aluminum frame with precision laser welded corners and satin white powder coating
- Suitable for recessed or surface mount (with optional accessories)
- Construction features precise optical lenses over each individual LED, offering optimal light diffusion and consistent surface illumination, with no risk of yellowing over product lifetime
- UL Certified for Dry/Damp locations
- Powered by Keystone 0-10V dimmable LED driver with built-in junction box
- LED chip lifetime: L70 >100,000 hours @ 25°C/77°F ambient fixture temperature
- Over 50% energy savings compared to traditional fluorescent troffers
- Operating temp range -20°C/-4°F to 40°C/104°F
- IC Rated
- Complete, pre-wired emergency panel solution—including test button
- Built-in 8W LED Keystone SmartSafe Emergency Driver compliant with CEC T20
- Included expanded J-box for easy wiring

PERFORMANCE SPECIFICATIONS

Catalog Number	Nominal Size	Selectable Wattage	Selectable CCT	Lumens	Efficacy	Input Voltage	Dimmable	CRI
KT-BPLED35PS-22C-8CSA-VDIM-EM8	2' x 2'	35W	3500K	3950	113 lm/W	120-277V	0-10V	>80
			4000K	4200	120 lm/W			
			5000K	4000	114 lm/W			
		30W	3500K	3450	115 lm/W			
			4000K	3700	123 lm/W			
			5000K	3500	117 lm/W			
		20W	3500K	2400	120 lm/W			
			4000K	2600	130 lm/W			
			5000K	2450	123 lm/W			
KT-BPLED45PS-24C-8CSA-VDIM-EM8	2' x 4'	45W	3500K	5300	118 lm/W	120-277V	0-10V	>80
			4000K	5650	125 lm/W			
			5000K	5350	118 lm/W			
		35W	3500K	4200	120 lm/W			
			4000K	4550	130 lm/W			
			5000K	4235	121 lm/W			
		30W	3500K	3850	128 lm/W			
			4000K	4200	140 lm/W			
			5000K	3900	130 lm/W			

* Preset to (5000K)

* Color Uniformity: CCT (Correlated Color Temperature) range as per guidelines outlined in ANSI C78.377-2017.

INTEGRATED EMERGENCY TEST SWITCH

POWER BUTTON



LED INDICATOR


KT-BPLEDXXPS-XXC-8CSA-VDIM-EM8

BACKLIT LED PANEL LIGHT WITH INTEGRATED EMERGENCY PACK

KT-BPLED35PS-22C-8CSA-VDIM-EM8


PHOTOMETRIC SPECIFICATIONS

POLAR CANDELA DISTRIBUTION




Average beam angle (50%): **117.8°** 1 Violet C0/180, 121.4
Unit: cd 2 Green C90/270, 114.2

FLUX CHART



ISOCANDELA PLOT




KT-BPLEDXXPS-XXC-8CSA-VDIM-EM8

BACKLIT LED PANEL LIGHT WITH INTEGRATED EMERGENCY PACK

KT-BPLED45PS-24C-8CSA-VDIM-EM8


PHOTOMETRIC SPECIFICATIONS

POLAR CANDELA DISTRIBUTION




Average beam angle (50%): **116.5°** **1 Violet** C0/180, 119.4
Unit: **cd** **2 Green** C90/270, 113.6

FLUX CHART



ISOCANDELA PLOT




KT-BPLEDXXPS-XXC-8CSA-VDIM-EM8


BACKLIT LED PANEL LIGHT WITH INTEGRATED EMERGENCY PACK

PHYSICAL SPECIFICATIONS


KT-BPLED35PS-22C-8CSA-VDIM-EM8



KT-BPLED45PS-24C-8CSA-VDIM-EM8



POWER SELECT AND COLOR TEMPERATURE SELECT CAPABILITY



KEYSTONE POWER SELECT TECHNOLOGY
Adjust power between 35W, 30W, or 20W

KEYSTONE COLOR SELECT TECHNOLOGY
Adjust CCT between 3000K, 4000K, or 5000K

KT-BPLEDXXPS-XXC-8CSA-VDIM-EM8

BACKLIT LED PANEL LIGHT WITH INTEGRATED EMERGENCY PACK

ACCESSORIES

SENSORS

Factory-Installable OR Field-Installable (field-installable purchased separately)

✓	SUFFIX*	CATALOG NUMBER	DESCRIPTION	UPC	EASY CODE
	/FC1	KTSL-FC1-UV-KO-PIR	Bluetooth Mesh Wireless Fixture Controller for SmartLoop System with remote mountable daylight and PIR motion sensor. 120-277V. 3A Max Load with 0-10V Dimming	843654129259	MGZ-59



Note: Keystone SmartLoop is a DLC Qualified Network Lighting Control solution, offering advanced functions such as complete wireless control, zoning, high-end trim, occupancy/vacancy sensing, scene setting, and scheduling. To learn more about SmartLoop, please visit <http://www.keystonetech.com/smartloop>.

CORD SETS

Factory-Installable OR Field-Installable (field-installable purchased separately)

✓	SUFFIX*	CATALOG NUMBER	DESCRIPTION	UPC	EASY CODE
	/515P6	KT-CS-515P-6-18/3	Cord set for high bay; 125V NEMA 5-15P; straight blade plug; 6' SJTOW cable; 18/3 wire	843654140124	UKH-26
	/MC13	KT-MC-NP-1-18/3	Metal clad cable for fixtures, No Plug, 1ft long, 18/3 wire (L,N,G)	843654139777	AYT-71
	/MC63	KT-MC-NP-6-18/3	Metal clad cable for fixtures. No Plug. 6ft long. 18/3 wire (L,N,G)	843654134505	EYP-82
	/MC65	KT-MC-NP-6-18/5	Metal clad cable for fixtures. No Plug. 6ft long. 18/5 wire (L,N,G, LV)	843654134512	CBU-56
	/MC66	KT-MC-NP-6-18/6	Metal clad cable for fixtures. No Plug. 6ft long. 18/6 wire (L,S,N,G, LV)	843654164229	KFF-99


* For factory installation of accessory, add suffix to fixture part number (see ordering examples and instructions on last page of spec sheet).

Note: For cord sets not listed here, please contact your Keystone sales rep.

MOUNTS AND BRACKETS

Field-Installable / Field-Use ONLY (purchased separately)

CATALOG NUMBER	DESCRIPTION	UPC	EASY CODE
KT-BPLED-SM-22-KIT /G2	Surface Mount Kit 2x4 Backlit panels	843654134536	MUZ-60
KT-BPLED-SM-24-KIT /G2	Surface Mount Kit 2x4 Backlit panels	843654134543	CGY-52
KT-BPLED-CABLE-KIT	Aircraft cable hanging kit for LED high bay fixtures	843654133423	JLB-77
KT-BPLED-JBOX-3	Larger Junction Box add-on for C style LED backlit panels	843654166940	KSS-95



(Accessories continued on next page)

