

KT-FLED25PS-C1E-UNV-8CSB-VDIM-W

BULLET FLOOD LIGHT

DESCRIPTION

LED Bullet Flood Light with Photocell | Power Select 25/20/15W | Color Select 3000/4000/5000K | 120-277V Input | White Housing

APPLICATION

Perfect in both residential and commercial applications, such as landscape, facade, accent, and flagpole lighting



PRODUCT FEATURES


- Sturdy die cast aluminum housing in a sleek, modern design
- IP65 design includes twist on/off glass lens cap for easy field changeable optics
- Keystone Power Select technology (25/20/15W)
- Keystone Color Select technology (3000/4000/5000K)
- Built-in dusk-to-dawn photocell with on/off switch
- Standard NEMA 4H x 4V optics installed, with optional NEMA 3H x 3V optics included in box
- Available in bronze and white finishes
- Ambient operating temperature: -40°C/-40°F to 45°C/113°F
- L70 > 50,000 hours @ 45°C/113°F
- UL and DLC 5.1 listed

PRODUCT SPECIFICATIONS

Catalog Number	Selectable Wattage	Selectable CCT	Lumens	Efficacy	Input Voltage	CRI	Housing Color	Rated Life
KT-FLED25PS-C1E-UNV-8CSB-VDIM-W	25W	3000K	2971	119 lm/W	120-277V	80	White	50,000 hrs
		4000K	3292	132 lm/W				
		5000K	3273	131 lm/W				
	20W	3000K	2398	120 lm/W				
		4000K	2609	130 lm/W				
		5000K	2580	129 lm/W				
	15W	3000K	1862	124 lm/W				
		4000K	1998	133 lm/W				
		5000K	1986	132 lm/W				

IMAGES







KT-FLED25PS-C1E-UNV-8CSB-VDIM-W

BULLET FLOOD LIGHT

PHYSICAL SPECIFICATIONS



PHOTOMETRICS FOR 4H X 4V LENS




FLUX DISTRIBUTION

Zone	Lumens	% Luminaire
Forward Light	1,638 lm	50.0%
0°–30°	1,241 lm	37.9%
30°–60°	331.76 lm	10.1%
60°–80°	39.975 lm	1.2%
80°–90°	2.9898 lm	0.1%
Back Light	1,635.1 lm	50.0%
0°–30°	1,234 lm	37.7%
30°–60°	323.16 lm	9.9%
60°–80°	50.183 lm	1.5%
80°–90°	4.3756 lm	0.1%
Up Light	45.556 lm	1.4%
90°–100°	1.1682 lm	0.0%
100°–180°	44.388 lm	1.4%

BUG* Rating

Asymmetrical Luminaire Types	
Type I, II, III, IV	B2 U0 G2
Quadrilateral Symmetrical Luminaire Types	
Type V, Area Light	B2 U0 G2

* BACKLIGHT, UPLIGHT, GLARE




KT-FLED25PS-C1E-UNV-8CSB-VDIM-W

BULLET FLOOD LIGHT

POWER SELECT (WATTAGE) AND COLOR SELECT (CCT) ADJUSTMENT

This fixture is equipped with field-adjustable Keystone Power Select and Color Select technology.

1. Ensure power is off to the fixture.
2. Remove knockouts.
3. Adjust dip switches to desired settings.
4. Replace knockouts.
5. Restore power to fixture.




KT-FLED25PS-C1E-UNV-8CSB-VDIM-W


BULLET FLOOD LIGHT

LENS REPLACEMENT INSTRUCTIONS


1. Open the cap with a lens wrench tool (provided).




2. Remove the cap and reflector and unscrew the 4 lens screws, then use a screwdriver to take off the original lens through the grooves.




3. Install the NEMA 3H × 3V replacement lens (provided) on the fixture, aligning arrow on lens with arrow on LED board and groove on housing.




4. Tighten the 4 lens screws, put back the reflector, and twist on the cap,



5. Lock the cap in place with a lens wrench tool (provided).





KT-FLED25PS-C1E-UNV-8CSB-VDIM-W

BULLET FLOOD LIGHT

ORDERING INFORMATION

ORDER CODE	UPC	EASY CODE
KT-FLED25PS-C1E-UNV-8CSB-VDIM-W	843654141893	NCD-13

CATALOG NUMBER BREAKDOWN

KT-FLED25PS-C1E-UNV-8CSB-VDIM-W

1 2 3 4 5 6 7 8 9 10 11 12 13

- 1 Keystone Technologies
- 2 Floodlight LED
- 3 Max Wattage
- 4 Power Select
- 5 Circular
- 6 Series 1
- 7 4H x 4V Distribution
- 8 Universal Voltage
- 9 80 CRI
- 10 Color Select
- 11 Color Select Designation
- 12 0-10V Dimming
- 13 White

11 Color Select Designation

B	3000/4000/5000K
---	-----------------