

LED GARAGE LIGHT



The LED Garage Light offers an affordable option for facility managers to upgrade parking garage lighting to LED, creating better visibility and making it an overall safer environment for visitors, while significantly reducing operating and maintenance costs.

Certified as a DLC Premium product, this luminaire goes above and beyond the minimum rating, delivering up to 133 LMW from both the 39W and 59W models. It's high efficiency combined with polycarbonate Fresnel lens and 160° beam angle ensure wide-spreading, uniform light, potentially decreasing the number of fixtures needed in a space. The optional microwave motion sensor takes savings a step further, enabling occupancy sensing and daylight harvesting, each fully programmable on unit or remotely via a remote control accessory.

This unit is designed for easy installation, with surface or pendant mounting capabilities. The easy-mount connecting plate enables hands-free wiring for surface mounting, saving effort, time and cost on the installation process.

KEY FEATURES

- DLC Premium (133 LPW)
- Programmable sensor with occupancy and daylight sensing (Optional)
- Sensor remote control
- IP54 rated
- 0-10V Dimming (dims to 6%)
- Polycarbonate Fresnel lens
- 5 year warranty
- 50,000 hour rated life
- Easy installation for surface or pendant mounting

MARKETS

- Parking Garages
- Covered walkways
- Entranceways
- Canopies
- Soffits

APPLICATIONS

- Commercial
- Industrial
- Residential



LED ROUND HIGH BAY PL

SPECIFICATIONS

Average Rated Life: 50,000H

CRI: 83

Power Factor: ≥0.95



Mounting: Surface or pendant

Beam Angle: 160°

Operating Temperature: -4°F to 113°F

Volts: 120-277

Dimming: 0-10V



ORDERING INFORMATION

STANDARD MODEL WITHOUT SENSOR

WATTS	ORDERING CODE	DESCRIPTION	CCT (K)	LUMINAIRE LUMENS
39	GL39UR40DLP	39W LED Garage Light Round 120-277V 4000K 0-10V DIM PREM	4000	5200
	GL39UR50DLP	39W LED Garage Light Round 120-277V 5000K 0-10V DIM PREM	5000	
59	GL59UR40DLP	59W LED Garage Light Round 120-277V 4000K 0-10V DIM PREM	4000	7800
	GL59UR50DLP	59W LED Garage Light Round 120-277V 5000K 0-10V DIM PREM	5000	

MODEL WITH SENSOR

WATTS	ORDERING CODE	DESCRIPTION	CCT (K)	LUMINAIRE LUMENS
59	GL59UR40DLPS	59W LED Garage Light Round 120-277V 4000K 0-10V DIM PREM W/ SENSOR	4000	7800
	GL59UR50DLPS	59W LED Garage Light Round 120-277V 5000K 0-10V DIM PREM W/ SENSOR	5000	

ACCESSORIES

SENSOR REMOTE CONTROL

ORDERING CODE	DESCRIPTION	USAGE
SCR051	Microwave Motion Sensor remote	Remotely adjust sensor settings



WHAT COMES IN THE BOX

- LED Garage Light
 - (4) Screws
 - (4) Anchors
- (1) 3/4" Plug
 - (1) 6" Long Wire (Attached)
 - Installation Instructions