



Energy Efficient Lighting Products

Model No.	SKEU962/SC
Ballast Type	Electronic
Lamp Operation	Parallel / Instant start
Input Voltage	120/277
Frequency	50/60hz

SPECIFICATION

Lamp Type	No. of Lamps	Input Voltage (V)	Input Current (A)	Input Power (W)	Power Factor	MAX THD (%)	Ballast Factor	Min. Starting Temperature (°F)	Lamp Current Crest Factor	B.E.F.
F96T8 59W	2	120/277	0.92/0.40	108/106	0.99	10%	0.88	32	1.7	0.8
F96T8 59W	1	120/277	0.57/0.25	68/67	0.99	10%	1.09	32	1.7	1.60/1.62
F96T8HO 86W	1	120/277	0.77/0.33	92/91	0.99	10%	1.05	32	1.7	1.14/1.15

Performance:

- Meets ANSI Standard C82.11
- Meets ANSI Standard C62.41
- Meets FCC Part 18 Class A (Consumer Limits)

Safety:

- No PCBs
- UL/CUL Listed
- Class P, Type 1 Outdoor
- OCV 750v

Application:

- Remote Mounting: 18 ft. Max. overall lead length, 18AWG
- Maximum Case Temperature 75°C / 167° F
- Sound Rated - "A"
- Maximum Ambient Temperature 40°C / 105° F

Case	Inches
Length (L)	9.5
Width (W)	1.3
Height (H)	1
Mounting (M)	8.91
Weight (lbs.)	1.2

Lead Length	Inches (+/-1)
Black	25
White	25
Red	79
Blue	46
Yellow	N/A

