

## AREA LIGHT

A stunning blend of performance, value and aesthetics, the **MPulse Area Light** is available in a wide range of lumen packages to address a variety of outdoor lighting needs. The Area Light can be combined with a full, architectural-grade LED family to create a total site solution for commercial, municipal, retail, education, and hospitality applications. Optional visual comfort optics distribute light through a non-pixelated light source that creates uniform, eye-pleasing illumination with minimal glare. The high-performance, IP66-rated luminaire delivers a minimum of 120 lumens per watt, providing significant energy savings while remaining durable in the field.



**100W**



**150W & 200W**



**250W & 300W**

**DIMENSIONS:** Please see page 4 for dimensional drawings.

### PERFORMANCE:

- Available in lumen packages ranging from 12,400lm to 38,400lm
- Calculated lumen maintenance value of > 90% (L90) at 100,000 hours calculated at 25°C
- 120-277V dimming standard. 347-480V options available
- 10KV surge suppression standard

### OPTICS:

- Available in Type II, Type III, Type IV, and Type V optics

### OPTIONS:

- NEMA 3-pin and 7-pin photocontrol receptacle
- High/Low/Off PIR fixture-integrated photo/motion sensor compatible with FSIR-100 remote control

### FINISHES:

- Satin bronze and silver finish standard

### CONTROLS:

**Photo/Motion Sensor:** The Wattstopper FSP-211 uses passive infrared (PIR) sensing technology to react to changes in infrared energy (i.e. moving body heat) within the coverage area. This slim, low-profile sensor is designed for installation inside the bottom of a light fixture body and is ideal for outdoor environments. The sensor operates at 120V/230V-240V and single phase 277V. The motion sensor is fully adjustable with dimmed light level options as well as on/off dusk to dawn control. Sensor can be combined with various lenses to operate at mounting heights from 8' to 40'. Factory settings can be adjusted via the FSIR-100, a wireless configuration tool. **Note that the sensor comes with photocell setting disabled and the FSIR-100 must be purchased if photocell functionality is desired.**

**RPC, PR7 Options:** Allow the use of 3rd party distributed intelligence controllers designed to connect to the fixture via our NEMA standard C136.41 3-, and 7-pin twist lock receptacle to provide dimming and On/Off control. Separate Photocontrol options are available, see page 2.

### SENSOR DEFAULT SETTINGS:

FACTORY DEFAULTS	
High Mode	10V
Low Mode	1V
Time Delay	5 Min
Cut Off	1 Hr
Sensitivity	Max

# AREA LIGHT

## SPECIFICATIONS:

ITEM	SPECIFICATION	100 WATTS - DETAILS	150 WATTS - DETAILS	200 WATTS - DETAILS	250 WATTS - DETAILS	300 WATTS - DETAILS
GENERAL PERFORMANCE	Input Power (W)	100W	150W	200W	250W	300W
	Lumens Delivered @ 4000K (lm)	12,460	20,245	25,630	33,120	38,155
	Lumens Delivered @ 5000K (lm)	12,550	20,380	25,810	33,355	38,425
	Efficacy (lm/W)	>120				
	CRI	>70				
	Calculated Lumen Maintenance (L93, TM-21 @ 25°C)	>100,000 hours				
	Color Temperature	Available in 3000K, 4000K & 5000K				
ELECTRICAL	Input Voltage	120-277V dimming standard; 347-480V options available				
	Max THD %	10%				
	Power Factor	>90%				
PHYSICAL	Housing	Die-cast aluminum				
	Weight	16.5lb	24.2lb	24.2lb	33.0lb	33.0lb
	EPA(sq. ft) 0°/ 90°	0.45/2.25	0.57/3.18	0.57/3.18	0.69/4.13	0.69/4.13
CERTIFICATION	Certification	DLC 4.2 Premium, cULus listed				
	Environment	Wet location listed, IP66				
	Warranty	10 years				
	Operating Temperature	-40°F - 122°F (-40°C - 50°C)				
	Humidity	10% - 90% RH, non condensing				

MODEL SELECTION Typical order example: MP-AR100UT5-50B									
MP		AR							
FAMILY	SUB-FAMILY	WATTAGE		VOLTAGE	DISTRIBUTION	CCT	FINISH	OPTIONS	
MP= MPulse	AR= Area Light	100=	100W, 250W MH equiv.	U= 120-277V H= 347-480V	T2=	30=	B=	(BLANK)=	None
		150=	150W, 320W PSMH equiv.		T3=	40=	S=	MS=	Photo/Motion Sensor
		200=	200W, 400W MH equiv.		T4=	50=	Contact Maxlite for additional finishes	RPC=	NEMA 3-Pin Photocell Receptacle
		250=	250W, 400W PSMH equiv.		T5=			PR7=	NEMA 7-Pin Photocell Receptacle
		300=	300W, 750W PSMH equiv.						

## MOUNTING:

MODEL SELECTION Typical order example: QMP-PM-B			
FAMILY		MOUNTING	FINISH
QMP		PM= Pole Mount	B= Bronze S= Silver
		SK= Slipfitter Knuckle	
		TS= Trunnion Swivel	

## ACCESSORIES:

ITEM ACCESSORY	ITEM NAME	ITEM DESCRIPTION
Photocontrols	6390LBK	Twist-Lock Electronic Photocontrol 120/208/240/277V
	6394LL	Twist-Lock Electronic Photocontrol 432-528VAC
Remote Control	FSIR-100	Remote Handheld Configuration Tool
Round Pole Adapter	QMP-3RPA-B	3" ROUND POLE ADAPTER FOR QMP-PM SERIES, TO BE USED WITH POLE MOUNT, BRONZE
	QMP-4RPA-B	4" ROUND POLE ADAPTER FOR QMP-PM SERIES, TO BE USED WITH POLE MOUNT, BRONZE
	QMP-5RPA-B	5" ROUND POLE ADAPTER FOR QMP-PM SERIES, TO BE USED WITH POLE MOUNT, BRONZE



## AREA LIGHT

### PHOTOMETRIC PERFORMANCE (4000K):

WATTAGE	T2	T3	T4	T5
	LUMENS			
100W	11,975	11,890	11,520	12,460
150W	19,450	19,315	18,715	20,245
200W	24,400	24,165	23,505	25,630
250W	31,675	31,305	30,570	33,120
300W	36,445	36,185	35,195	38,155

### PHOTOMETRIC PERFORMANCE (5000K):



WATTAGE	T2	T3	T4	T5
	LUMENS			
100W	12,055	11,975	11,600	12,550
150W	19,585	19,450	18,850	20,385
200W	24,570	24,335	23,675	25,810
250W	31,895	31,525	30,785	33,355
300W	36,700	36,440	35,285	38,425

### BACKLIGHT, UPLIGHT, AND GLARE RATINGS:


WATTAGE	T2			T3			T4			T5		
	B	U	G	B	U	G	B	U	G	B	U	G
100W	2	0	2	2	0	2	2	0	2	3	0	0
150W	2	0	2	3	0	2	3	0	2	4	0	1
200W	3	0	3	3	0	3	3	0	2	5	0	1
250W	3	0	3	3	0	3	3	0	3	5	0	1
300W	3	0	3	3	0	3	3	0	3	5	0	1

## AREA LIGHT


### DIMENSIONS:



**100W**




**150W & 200W**




**250W & 300W**


### MOUNTING DIMENSIONS:




**POLE MOUNT**  
QMP-PM



**SLIPFITTER MOUNT**  
QMP-SK



**TRUNNION SWIVEL MOUNT**  
QMP-TS



**ROUND POLE ADAPTER**  
QMP-4RPA

## AREA LIGHT

### ISOFOOTCANDLE:

Each gridline represents one mounting height.

For mounting heights other than noted multiply FC by the below factor.

$$\text{Factor} = \frac{(\text{Chart's Mtg Height})^2}{(\text{Actual Mtg Height})^2}$$

### LEGEND



Layouts based on 4000K or 5000K. Results are 3-5% less for 3000K. Consult IES file for more precise calculations.

#### TYPE II





#### TYPE III

#### TYPE IV

#### TYPE V





#### 100 WATT

20 ft mounting height







#### 150 WATT

20 ft mounting height







#### 200 WATT

25 ft mounting height







#### 250 WATT

30 ft mounting height



#### 300 WATT

30 ft mounting height



\*Lighting layouts and spacing criteria available upon request.