

LED VAPORPROOF JELLY JAR

JJ SERIES (WITH LAMP)



Ceiling Mount



Wall Mount



Pendant Mount

PRODUCT DESCRIPTION:

The MaxLite sealed Jelly Jar series offers a great value with its market leading enclosed rated LED lamps. These fixtures have multiple uses in cooler walk-in applications, high traffic areas susceptible to impact damages, or public spaces where lamp protection is important. Featuring aluminum die-cast bodies and guards, with a polycarbonate clear lens. These fixtures use EPDM gasketing, and brass assembly screws for the highest durability and long life

FEATURES:

- Die Cast body and cages
- Polycarbonate enclosures
- Multiple side and rear knock-outs
- Locking Allen screws to secure cages in place.
- Optional pendant mount also available
- See page 2 for operating temperature ranges – lamp dependent

CONSTRUCTION:

- UL Listed for self ballasted LED Lamps
- Wet Rated
- Three wire grounding included
- Ceramic high temp sockets used.
- Die Cast using ADC12 aluminum material
- Silver Powder Coat finish

CONTROL:

- Circuit controlled dimming is supported based on lamps used
- KO's are ½" Trade size and support external photo-control device installation

MODEL SELECTION (Full list of order codes on pg. 2)

Typical order example: JJP12001

JJ		12	001
FAMILY	APPLICATION	OPERATING VOLTAGE	LAMPING
JJ= Jelly Jar	W= Wall Mounted P= Pendant Mounted C= Ceiling Mounted	12= 120V	001= 9W A19 E26 Base 3000K CCT Included

ACCESSORIES:

ORDER CODE	MODEL	ENERGY STAR	WATTS	EQUIVALENCY	DELIVER LUMENS	EFFICACY (lm/W)	CRI	CCT	DIMENSIONS (W" x MOL")
E26 Base									
14099394	E9A19DLED27/G6	★	9	60W Inc.	800	88	80	2700K	2.36" x 4.25"
14099397	E9A19DLED30/G6	★	9	60W Inc.	800	88	80	3000K	
14099398	E9A19DLED40/G6	★	9	60W Inc.	800	88	80	4000K	
76907	10CPUALED927	★	10	60W Inc.	900	90	80	2700K	2.97" x 2.47"
76908	10CPUALED930	★	10	60W Inc.	1000	100	80	3000K	



SPECIFICATIONS:

ITEM	SPECIFICATION	JJW1200X	JJP1200X	JJC1200X
PHYSICAL	Dimensions (W x H x Projection)	4.13" D.(5.38" across tabs) x 9.67" H x 7.37" projection	4.13" W (5.38" across tabs) x 9.89" H	4.25" W (5.38" across tabs) x 9.17" H
	Weight	3.1 lbs.	2.1 lbs.	2.6 lbs.
	Housing	Aluminum Die Cast ADC12, EPDM Gasketing		
	Lens	Polycarbonate, clear		
	Mounting	Fits std. wall and ceiling j-boxes		
	Operating Temperature*	-4F-104F (Contact MaxLite for use beyond ratings)		
GENERAL PERFORMANCE	Lamp Type	A-19 Lamp		
	Spacing Criteria	Contact Maxlite for layout assistance		
	Color Temperature (CCT)	Bulb dependent		
	Source Lumens	E9A19DLED30 = 800 lm		
	Efficacy	9w ; 89 lm/w		
	Equivalency	60w Incan.		
	Dimming	Lamp and control dependent		
	Lumen Maintenance (L70)	25,000 hr		
ELECTRICAL	Input Voltage	120VAC		
	Power Consumption	Max 100W input		
APPLICATION	Certification	cULus 8750, listed for use with enclosed rated SBLED		
	Environment	Wet		
	LED Class	LM-80, UL listed		
	Warranty	5yr when operated within listed temperature ranges		

*When operating above 90°F for extended periods of time, lifespan of bulb may be shorter than stated L70 time. Please contact your MaxLite representative for more information.