

LED 4" RESIDENTIAL RETROFIT RR4-L9 SERIES



PRODUCT DESCRIPTION:

Constructed with a high-efficacy LED array and dimmable driver, the 4-inch Downlight Retrofit features an optical diffuser that produces high lumen transmission and even illumination. The fixtures are suitable for wet locations. These four-inch downlight retrofit are the economical solution for consumers looking to reduce energy costs. These retrofits are offered in a variety of CRI options and lumen packages appropriate for residential applications.

FEATURES:

- High lumen transmission and diffusing for even illumination
- Supplied with E26 base adapter
- Suitable for wet locations
- High CRI models support compliance of CEC T20 2016

CONSTRUCTION:

- Module construction includes LED, lens, and white trim
- Impact-resistant plastic lens
- Fits recessed cans with tension springs

ELECTRICAL:

- 120V, 60Hz
- Dimmable down to 10%
- L70 of 36,000 hours
- Power factor: ≥ 0.9

WARRANTY:

5-year standard warranty* (further details available at www.maxlite.com/warranties)

*Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

MODEL SELECTION (Full Order List On Page 2)

Typical order example: RR41027W-L9

RR	4			W		
FAMILY	SIZE	WATTAGE (NOMINAL)	CCT	TRIM	CRI	VERSION
RR= Residential Retrofit	4= 4"	10= 10W 13= 13W	27= 2700K 30= 3000K	W= White	(OMIT) = 80 CRI	-L9= Version 9
RR= Residential Retrofit	4= 4"	10= 10W	27= 2700K 30= 3000K	W= White	C= 90 CRI	-L7= Version 7

NOTES:

1. Additional CCTs are available, contact MaxLite for more information

ACCESSORY		
ORDER CODE	MODEL NUMBER	DESCRIPTION
74216	MLRR-E26ADAPT	E26 socket adapter (Included)
73552	MLRR-GUADAPT	GU24 socket adapter

SPECIFICATIONS:

		RR41027W-L9	RR41327W-L9	RR41027WC-L7
ITEM	SPECIFICATION	DETAILS		
GENERAL PERFORMANCE	Wattage	9.6	12.7	9.9
	Lumens Delivered (lm)	718	879	680
	Efficacy (lm/W)	75	70	69
	CRI	≥80		≥90
	Color Temperature (CCT)	2700K, 3000K (Additional CCT available, contact MaxLite for info.)		
	L70 Lifetime (hours)	36,000		
	Color Consistency	Proprietary binning for uniform color		
ELECTRICAL	Power Factor	0.9		
	Input Voltage	120V		
	Compatible Dimmers	Triac Dimmable		
PHYSICAL	Weight	2 lbs		
	Mounting	Mounts into existing recessed frame		
	Operating Temperature	-4°F to 104°F		
	Humidity	20-85% RH, non-condensing		
CERTIFICATION	Certification	Energy Star, cULus, FCC		
	Material Usage	RoHS compliant; no mercury		
	Environment	Wet Location		
	Warranty	5-year standard warranty*		

ORDERING:

ORDER CODE	MODEL NUMBER	WATTAGE	CCT	CRI
14099591	RR41027W-L9	10	2700K	80
14099592	RR41030W-L9		3000K	
107305	RR41027WC-L7	10	2700K	90
107306	RR41030WC-L7		3000K	

* PLEASE CONTACT MAXLITE FOR ORDER CODES THAT ARE NOT LISTED HERE.

DIMMERS:

COMPATIBLE DIMMERS
Lutron DVCL-153PL
Leviton IPL106
Lutron CTELV-303P
Lutron DVELV-300P
Lutron MACL-153M
Lutron SELV-300P-WH