

PROJECT NAME: _____

CAT. #: _____

NOTES: _____

FIXTURE SCHEDULE: _____

Commercial Downlight

 UNIVERSAL RCF SERIES
 WATTAGE AND COLOR SELECTABLE


4"




6"



8"



9.5"


CCT & WATTAGE SELECTABLE

Description:

The Universal Commercial Downlight is an economical, all-in-one solution for adding recessed downlighting to hospitality, retail, office and other commercial lighting applications. It is both wattage and CCT selectable, allowing for easy, on-the-job customization. The downlight is designed with an integral whip which connects directly to a junction box (existing or independently mounted) and an integral driver that eliminates the need for a traditional recessed housing, saving installers time and money. Easy to install in new construction, remodel and retrofit projects, the downlight has a slim body that fits into shallow ceilings. Its white baffle trim blends seamlessly into interiors and reduces glare for soft, eye-pleasing illumination.

Features:

- ETL listed as a fixture and a retrofit
- Field installable Emergency Battery back up kit available (includes a test switch and the charge indicator kit, no cover)
- Mounts directly into ceiling, no housing required
- Comes standard with 24" power whip
- IC Rated (4", 6", 8")

Dimming:

- 120-347V option available with 0-10V dimming (10%)

Construction:

- Die Cast Aluminum housing
- Plastic lens

Listings:

- cETLus for damp locations, Indoor
- ENERGY STAR certified

Controls Ready:

Luminaire Level Lighting Control (LLLC), individual addressability and/or grouping, ability to create scenes and high-Trim/ tuning sets (minimum dimming level is 15%) is available and enabled on the product family with wireless Bluetooth technology via the field installable c-Max Network power pack and the optional occupancy PIR sensor.

Ordering Information

FAMILY	SIZE	WATTAGE	CCT	VOLTAGE	TRIM
RCF= Recessed Commercial Fixture	4= 4"	12= 12W	CS= Color Selectable (3000K/3500K/4000K)	D= 120-347V, 0-10V dimming	W= White
	6= 6"	10W= 10/12/17W			
	8= 8"	14W= 14/17/20W			
	10= 9.5"	30W= 30/35/40W			

Order Code

ORDER CODE	MODEL NUMBER	ENERGY STAR ID #
104776	RCF412CSDW	2367879
104777	RCF610WCSDW	2367890
104778	RCF814WCSDW	2367892
104779	RCF1030WCSDW	2367893

Dimming Compatibility

DIMMER MODELS	
Leviton	IP710
Lutron	DIVA DVTV, NOVA NTSTV-DV, DIVA DVSCV



5-year standard warranty (further details available at www.maxlite.com/warranties) Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

Commercial Downlight

UNIVERSAL RCF SERIES
WATTAGE AND COLOR SELECTABLE

Accessories (SOLD SEPARATELY)

ORDER CODE	MODEL NUMBER	DESCRIPTION	IMAGE
14098874	RCF-4	4" Commercial Recessed Frame, New Construction	
14098875	RCF-6	6" Commercial Recessed Frame, New Construction	
14098876	RCF-8	8" Commercial Recessed Frame, New Construction	
100298	EBUUP15007N0100	Emergency Battery Back up, 07W, 100-347V, Field installable	
105172	RCF-XTRIM10	Goof ring for RCF10 models, 9.5" to 12" coverage	
106318	NPP-300W	120-277V Network Power Pack 300W Max	
107788	NPPSL-PSW	Network Power Pack PIR Sensor, 12V, White	

Specifications

	RCF412CSDW	RCF610WCSDW	RCF814WCSDW	RCF1030WCSDW
Nominal Wattage (W)	12W	10/12/17W, 10W Default	14/17/20W, 14W Default	30/35/40W, 30W Default
Lumens Delivered (lm)	900	1000/1200/1700	1400/1700/2000	2550/2975/3400
Lumens Battery Mode (lm)	700	700	700	700
Equivalency	12W CFL	12W /18W/ 20W CFL	18W /20W/ 22W CFL	2x32W / 2x42W /3x32W CFL
Efficacy (lm/W)	75	100	100	85
Beam Angle	97	104	106	114
CRI	≥80			
Color Temperature (K)	3000K/3500K/4000K (4000K Default setting)			
L70 Lifetime (Hrs)	≥50,000 Hrs			
Voltage	120V-347V, 0-10V, 10%			
Power Factor	≥0.90			
Housing	Die Cast Aluminum			
Lens	Plastic			
Operating Temperature	-4°F to 104°F			
Listings	ENERGY STAR, cULus, IC Rated, FCC			ENERGY STAR, cETLus, FCC
Environment	Damp locations, Indoor			
Warranty	5 years			

Dimensions:

NOMINAL SIZE	HEIGHT	INNER DIAMETER	OUTER DIAMETER
4"	3.61"	3.61"	5.91"
6"	3.98"	5.77"	8.29"
8"	4.29"	7.31"	10.26"
9.5"	4.74"	8.3"	11.28"

