



Catalog Number	39069
UPC Number	60198639069
Description	Mini Photocontrol Flush Mount 120 Volt

Features

- Weatherproof Polycarbonate Housing & Lens
- SPST - Normally Open
- 1/2" CDS Photocell
- 30-60 Second Time Delay
- Light Levels: ON: .9 to 1.9 FC OFF: 2.8 to 5.6 FC
- Thermal Switch
- Temperature Range: -40°F to 158°F
- Power Consumption Below 1.5 Watts Average
- Relative Humidity: 96%
- Contact Position at Night is Normally Closed
- Life Cycle: 6500 cycles
- 3/8"-18 Thread Nipple with Rubber Gasket and Plastic Lockout
- 6" Wire Leads
- UL Listed

General

Material:	Weatherproof Polycarbonate Housing
Switching:	Single Pole, Single Throw
Load Rating:	150W 100VA
Sensor Type:	1/2" CDS

Dimension Information

Lead:	18AWG, LENGTH 6"
-------	------------------

Specifications

Temperature Rating:	-40°F to 158°F
Voltage Rating:	120 V
Durability under load (cycles):	>6500
Turn-On Light Level:	10~20 Lux
Turn-Off Light Level:	30~60 Lux
Turn-On Time Delay:	30 sec
Turn-Off Time Delay:	30 sec

Packaging

Bag Qty	1
Master Bag Qty	1

Certifications

UL	UL 773 Standard
cUL	
RoHS	

www.morrisproducts.com

Morris Products 53 Carey Road, Queensbury, NY 12804

