



71419
LED Classic Mini Wall-Pack



Model :		71419
OVERALL LAMP PARAMETERS	Input Voltage	120 VAC (With Pre-Installed Photocell) 50/60HZ
	Input Current	0.5A Max @120V
	Input Power	30W
	Power Factor	PF≥0.95
	Luminance	2000 LM
	Luminous Efficiency	65 LM/W
	CRI	>70
	Beam Angle	180°
	Main Structure	Aluminium + Polycarbonate
LED DRIVER	Output Voltage	18.2-36 VDC
	Output Current	0.9A
	Driver Efficiency	88%
LED	LED Manufacturer	PHILLIPS
	LED Type	LUMILED LUXEON 3030
	LED Quantity	18 PCS
	LED Efficacy	110 LM/W
	Color Temperature	5000K
Photocell	-	Yes dusk-to-dawn UL listed
LIFESPAN & ENVIRONMENT	Lifespan	50000 Hrs.
	Warranty	5 Years
	IP Rating	IP65(NEMA 4X) Dust & Water Tight
	Operating Temperature	-40°F—+131°F
	Storage Temperature.Humidity	-40°F—+176°F , 10—90% RH
SAFETY&EMC	Safety Norms	UL1598,UL8750, EN60598, EN61347-2-13, EN62031, EN62471
	Withstand Voltage	I/P-FG: 2121VDC
	Grounding Resistance	25A 100mΩ
	Electromagnetic Compatibility	EN55015, EN61000-2-3, EN61000-3-3, EN61547
OTHERS	Dimension	Pls refer to attached dimension drawing
	Net Weight	0.6KG
	Gross Weight	0.8KG
	Q'ty / Carton	6PCS
	Volume	0.52Cbm/carton
	Housing Color	White

Dimension :

71419

