


MORRIS CAT#: 71636C LED Small Classic WallPack 120W, 120-277V, 4000K Bronze











Features:

 Use in general lighting applications: Parking Lots & Building Security

Die cast Aluminum Housing, polyester powder coating

 Aluminum Heat Sink, customized fin design for optimal heat dissipation

Heat Resistant Directed Optics

• Polycarbonate Lens

4KV surge protector inside of power supply

5 Year Limited Warranty


IP65 rated

Certification: ETL/cETL, DLC

Environment: Suitable for Wet Locations

Part#	Input/ Wattage	Volts	Lumens	ССТ	CRI	Dimming	Light Pattern	Lumens/ Watt	DLC PRODUCT ID#:
71636C	120W	120-277V	15,400	4000K	72	0-10V	Garage	134	PLJNGAAPU83M

PHOTOMETRY



www.morrisproducts.com



MORRIS CAT#: 71636C LED Small Classic WallPack 120W, 120-277V, 4000K Bronze

Technical Specifications:

Electrical:

Input Voltage: 120V-277V Current: 1.1A@120V Frequency: 50/60Hz Power Factor: ≥.9

THD: 7%

Product Parameters:

Input Watts: 120W

Lumens: 15,400

Efficacy: 134 lumens per watt 50,000+ Hour L70 Life Span CCT: 4000K (Cool White)

Chromacity Measurements:

Beam Angle: 365° H X 256° V

CRI: 72 R9: -25

BUG Rating: B2-U5-G5

Component Specifications:

LED: Lumileds 3030 120-277V, 50-60Hz

Driver Output Volts: 90-120V Driver Output Amps: 1800mA

6KV Surge Protection

Dimming: 0-10V

Operating Temperature:

Minimum Starting: -40°F to 131°F

Construction:

Housing: Aluminum Alloy

Powder Coated

IP Rating: IP65 suitable for wet locations

Lens Material: Heat Resistant Polycarbonate

Lens UV Resistant, Fire Resistant

Mounting: Hinged Spider Plate

Listings: ETL, DLC

Accessories:

Emergency Backup - CAT#: 71471B

LED Button Style Photocell - CAT#: 39100 LED Shutter Style Photocell - CAT#: 39102 LED Pencil Style Photocell - CAT#: 39104 Semi-Cutoff Visor - White - CAT#: 71463B

Wire Guard - CAT#: 71460B

Warranty:

Morris Products carries a 5 year warranty from date of purchase against defects in materials and workmanship (assuming normal and proper usage).