




Morris Products Inc.

## Silver Bay Ceiling Light

|                       |                                                   |                                                                                                            |
|-----------------------|---------------------------------------------------|------------------------------------------------------------------------------------------------------------|
| Model#:               | 72202                                             |  <p>external view</p>   |
| Product series:       | Silver Bay Ceiling Series                         |                                                                                                            |
| Product description:  | LED 13" Decorative Ceiling Fixture, 120V dimmable |                                                                                                            |
| Size:                 | 13"D x 4-1/4"H                                    |                                                                                                            |
| LED chip:             | 5730LED, 0.5W*28pcs                               |                                                                                                            |
| Input Voltage:        | 120V,60Hz                                         |                                                                                                            |
| Rated power input:    | 17W                                               |                                                                                                            |
| Output:               | N/A, Driver On Board(DOB)                         |                                                                                                            |
| Rated Power factor:   | >0.9                                              |  <p>dimension view</p> |
| THD:                  | <15%                                              |                                                                                                            |
| Ra:                   | Ra ≥ 80                                           |                                                                                                            |
| CCT:                  | 3000K                                             |                                                                                                            |
| Delivered lumen:      | 1000LM                                            |                                                                                                            |
| Luminaire efficacy:   | 60LM/W                                            |                                                                                                            |
| life hour:            | 35000h                                            |                                                                                                            |
| Dimmable:             | YES                                               |                                                                                                            |
| Certificate:          | ETL                                               |                                                                                                            |
| IP Rated:             | IP23                                              |                                                                                                            |
| Warranty              | 5 Year                                            |                                                                                                            |
| Beam Angle            | 170° (10%) 120° (50%)                             |                                                                                                            |
| THD:                  | <20%                                              |                                                                                                            |
| SCDM                  | <6                                                |                                                                                                            |
| Operating temperature | -10~45℃                                           |                                                                                                            |
| Housing IP rating     | Damp                                              |                                                                                                            |
| Range of application: | Indoor                                            |                                                                                                            |
| Body color:           | satin nickel                                      |                                                                                                            |
| Body material:        | metal                                             |                                                                                                            |
| Lens color:           | alabaster                                         |                                                                                                            |
| Lens material:        | glass                                             |                                                                                                            |