



72503
LED Entryway Light



RoHS



Model:		72503
OVERALL LAMP PARAMETERS	Input Voltage	120-277 VAC 60HZ
	Input Current	0.5A Max @120V
	Input Power	22W
	Power Factor	PF≥0.95
	Luminance	2,497 LM
	Luminous Efficiency	114 LM/W
	CRI	>83
	Beam Angle	106°
	Main Structure	Aluminium + Polycarbonate Lens
LED DRIVER	Output Voltage	12-24 VDC
	Output Current	0.9A
	Driver Efficiency	88%
LED	LED Manufacturer	Citizen
	LED Type	COB
	LED Quantity	1 PCS
	LED Efficacy	120 LM/W
	Color Temperature	WW/NW/CW (5000K)
Photocell	-	Not Included
LIFESPAN & ENVIRONMENT	Lifespan	50,000+ Hrs.
	Warranty	5 Years
	IP Rating	IP54 Wet Locations
	Operating Temperature	-20℃---40℃
	Storage Temperature, Humidity	-40℃---80℃ , 10--90% RH
SAFETY&EMC	Safety Norms	UL1598, UL8750, EN60598, EN61347-2-13, EN62031, EN62471
	Withstand Voltage	I/P-FG: 2121VDC
	Grounding Resistance	25A 100mΩ
	Electromagnetic Compatibility	EN55015, EN61000-2-3, EN61000-3-3, EN61547
OTHERS	Dimension	Pls refer to attached dimension drawing
	Net Weight	0.6KG
	Gross Weight	0.8KG
	Q'ty / Carton纸箱	4 PCS
	Volume	0.52Cbm/carton
	Housing Color	White

Dimension:

72503

