


# MORRIS CAT#: 72584A LED Round 2-Head Security Light 120-277V, 25W, 5000K










#### Features:


- Replaces old HID, mercury vapor, high pressure sodium
  & metal halide fixtures.
- Dual Head Configuration
- Turns Lights on Automatically When Motion is Detected
- Ideal for Walkways, Entrances, Backyards and Patios
- Provides Years of Trouble Free Service
- 270° Detection Angle out to 60Ft
- Adjustable Motion & Light Sensitivity & Time Delay

- Adjustable Motion & Light Sensitivity & Time Delay
- Durable Die Cast Aluminum IP65 Weather Resistant Housing
- High Temperature Silicone Gasketing
- Fluted Prismatic Reflector
- Operating Temperature: -4°F to 122°F
- Listings: cETLus
- 5 Year Warranty

Part#	Input/ Wattage	Volts	Lumens	ССТ	CRI	Dimming	Light Pattern	Lumens/ Watt	
72584A	25W	120-277	2,619	5000K	>80	N/A	Outdoor	105lm/w	

#### **PHOTOMETRY**







# MORRIS CAT#: 72584A LED Round 2-Head Security Light 120-277V, 25W, 5000K

## **Technical Specifications:**

**Electrical:** 

Input Voltage: 120V-277V Current: .22A@120V Frequency: 50/60Hz Power Factor: ≥.98

THD: >20%

#### **Product Parameters:**

Input Watts: 25W Lumens: 2,619

Efficacy: 105 lumens per watt 30,000+ Hour L70 Life Span CCT: 5000K (Cool White)

# **Chromacity Measurements:**

Beam Angle: 49° per head

CRI: 80 R9: 7

## **Component Specifications:**

LED: Lumileds 3030 120-277V, 50-60Hz

Dimming: N/A

## **Operating Temperature:**

Minimum Starting: -4°F to 122°F

#### **Construction:**

Housing: Aluminum Alloy

Powder Coated

IP Rating: IP65 suitable for wet locations

Lens Material: Polycarbonate

Mounting: Wall or Eve Mounted to

Standard Junction Box

Listings: cETLus

### Warranty:

Morris Products carries a 5 year warranty from date of purchase against defects in materials and workmanship (assuming normal and proper usage).