





2x4

LED Color and Wattage Tunable Panel Lights MORRIS# 71165



Features:

Replacement for office, hallway, conference room

Color Tunable: 5000K, 4000K & 3000K

Wattage Tunable: 20W, 25W, 30W, 35W& 40W

Flicker Free Driver

Dimmable

SMD 2835 LEDs

Operating Temperature: 14°F - 104°F




PMMA Light Guide Panel

IP20 Dry Location Rated

5 Year Warranty

Part#	CCT	Lumens	Voltage	Light Pattern	Dimming	Lumens/Watt	DLC #
71165	5000	5,465	120-277	110°	0-10/PWM	109	POFWWHG5
	4000	5,204				105	
	3500	5,148				102	

PHOTOMETRY



Max , Ave Beam angle of C157.5plane113.72



2x4

LED Color and Wattage Tunable Panel Lights

MORRIS# 71165

Technical Specifications:

Electrical:

Input Voltage: 120 thru 277

Current: .420A @ 120V/40W/5K

.412A @ 120V/40W/4K

.421A @ 120V/40W/3K

Frequency: 60Hz

Power Factor: ≥ 0.9

THD: $< 20\%$

Product Parameters:

Wattage: 30W, 35W, 40W, 45W, 50W

Efficacy: 102 Lumens Per Watt

50,000+ LED Life Span

CCT Adjustable: 5000K (Cool White)

4000K (Neutral White)

3000K (Warm White)

Chromaticity Measurements:

Beam Angle: 110°

CRI: > 80

R9: 2 @ 5000K

8 @ 4000K

3 @ 3000K

Component Specifications:

LED: SMD3030

Driver: 100-277V 50-60HZ

Driver Output Volts: 24-42VDC

Driver Output Amps: 1100mA

1KV Surge Protection

Dimming:

0-10V/PWM

Operating Temperature:

Minimum Starting 14°F - 104°F

Construction:

Housing: Aluminum

Powder Coated

IP Rating: IP20 Dry Location Rated

Lens Material: PMMA

Mounting:

Listings: ETL Listed

DLC: P0FWWHG5

Carton Qty: 1

Weight: 1.87 lb

Warranty:

Morris Products carries a 5 year warranty from date of purchase against defects in materials and workmanship (assuming normal and proper usage).