





MORRIS #: 71166

LED BACKLIT PANEL LIGHT 40W

120-277V 5000K






Features:

- Can be installed in offices, hotels, shopping malls, office buildings, hospitals etc
- Aluminum Alloy + Iron Housing
- High-Power 2835 LEDs
- High Transmittance Lens
- Operating Temperature: 14°F-104°F
- 1KV surge protector inside of power supply
- 5 Year Limited Warranty
- IP40 rated
- Certification: cETLus, DLC
- Environment: Suitable for Damp Locations

| Part# | Input/Wattage | Volts | Lumens | CCT | CRI | Dimming | Light Pattern | Lumens/Watt | DLC # |
|-------|---------------|---------|--------|-------|-----|---------|---------------|-------------|----------|
| 71166 | 40 | 120-277 | 4380 | 5000K | 80 | 0-10V | 110° | 110 | P38IRC15 |

PHOTOMETRY





MORRIS #: 71166

LED CCT TUNABLE PANEL LIGHT

40W 120-277V 5000K

Technical Specifications:

Electrical:

Input Voltage: 120-277V

Current: 335A @ 120V

Frequency: 50/60Hz

Power Factor: $\geq .9$

THD: $<20\%$

Operating Temperature:

Minimum Starting 14°F-104°F

Construction:

Powder Coated

IP40 Rated

Lens Material: PC

Product Parameters:

Input Watts: 40

Lumens: 4380

Efficacy: 100 lumens per watt

50,000+ Hour L70 Life Span

CCT: 5000K (Cool White)

Mounting: Recessed

Listings: cETLus Listed

DLC #: P38IRC15

Mounting Accessories:

Chromaticity Measurements:

Beam Angle: 110°

BUG Rating: B3-U3-G2

UGR Rating: ≤ 22

CRI: >80

R9: 5

Component Specifications:

LED: Seoul 2835

120V 50-60HZ

Driver Output Volts: 55V / DC

Driver Output Amps: 1100Ma

1KV Surge Protection

Dimming: 0-10V / PWM

Warranty:

Morris Products carries a 5 year warranty from date of purchase against defects in materials and workmanship (assuming normal and proper usage).

www.morrisproducts.com