

Project

Schedule

Date

Notes

DESCRIPTION

naturaLED® security lighting provides cast aluminum back plate, our security lights are suitable for wet locations with the IP ratings of 65. Easy installation, gasketing between back plate and front prevents entry of water. Polyester powder-coated finish, rust and corrosion proof, maintenance free throughout the years of usage.



► FX-SECW13/20



► SECWRT



► SECW20



FEATURES

- Energy Star Certified
- ETL Certified
- IP65 Rating
- Excellent thermal design
- Uniform and consistent color
- CRI 80
- Input line Voltage: 120V / 120-277V
- Voltage Frequency: 50/60
- Input Current: 0.2A
- Power Factor: >0.99
- Surge Protection Level: 1KV
- Operating Temperature: -22°F~131°F
- 15-30 foot height performance
- Material: Die-Cast Aluminum / Plastic Housing

APPLICATIONS

- Security Lighting
- Pathway Lighting
- Perimeter Lighting
- Area Lighting
- Wall Lighting

WARRANTY

- 5 Year Warranty

COLOR

- Black

Ordering Information

EXAMPLE: LED-FXSECW20/40K/MV

LED	FX	SECW	20	40K	MV
LED	Category	Series	Wattage	CCT	Voltage
	FX Fixture	SECW Security Wall Lights	20 20W	40K 4000K	MV Multiple Voltage

ORDERING


💧 = For Wet Location

Watts (W)	Ordering Code	Description	Color Temp (K)	Lumens (lm)	Equiv. Wattage (W)	Voltage	Rated Hrs	IP 65	Energy Star
13	7414	LED-FXSECW13/40K (120V)	4000K	1,040	75	120V	50,000	•	•
13	7415	LED-FXSECW13/50K (120V)	5000K	1,040	75	120V	50,000	•	•
20	7773	LED-FXSECW20/40K/MV	4000K	1,622	100	120-277V	50,000	•	•
20	7774	LED-FXSECW20/50K/MV	5000K	1,769	100	120-277V	50,000	•	•
13	7556	LED-FXSECWRT13/40K/MV	4000K	1,026	75	120-277V	50,000	•	•
13	7557	LED-FXSECWRT13/50K/MV	5000K	1,040	75	120-277V	50,000	•	•
20	7137	* LED-FXSECW20/50K	5000K	1,446	100	120-277V	50,000	💧	•


* Limited Availability

SPECIFICATIONS


SECW 13/20



SECWRT




SECW 20




Model	Length (L)	Width (W)	Depth (D)	Weight (lbs)
SECW 13/20	8.5" (214mm)	5.5" (230mm)	3.15" (185mm)	1.15
SECWRT	8.5" (214mm)	5.5" (188mm)	3.15" (230mm)	1.30
SECW 20	11" (280mm)	6.7" (188mm)	5.5" (230mm)	3.10

PHOTOMETRICS CHART


SECW 13/20
Energy Star



SECWRT
Energy Star



SECW 20
Energy Star



PACKAGE

Master Pack: 10

