

# HMI 18000W/SE GX51

54324



#### **Product features**

- High intensity light providing true color performance with a CRI>90
- Longer life with heat dissipating round moly-foil design on lamps  $\geq 6000W$
- Mechanically robust with eXtreme Seal (XS) technology, up to 450°C at the pinch seal
- Capable of hot restrike ignition
- High color stability with average changes in color temperature during lamp life only 1°K/hr
- Dimmable down to 40% with stable color using many electronic ballasts
- High energy efficiency providing up to 100 LPW

### **Product benefits**

- Enhanced safety with UV-Stop (UVS) feature on select HMI single-end lamps
- Enhanced HMI technologies offered including the new HMI DIGITAL and HMI STUDIO

### Areas of application

- Studio, Film & TV
- Professional Photography
- Solar Simulation

# Product datasheet

### Technical data

# General product information

Product Number	54324			
Product Name	HMI18000WSEGX51 1/CS 1/SKU			
Ordering Abbreviation	HMI 18000W/SE GX51			
Brand Name	OSRAM			
General Description	18000 watt, metal halide, single-ended, GX51 base, 90 CRI, 6000K			
Application	Film, TV, Studio, Solar Simulation			
Product Remark	s (Operating Position) = Vertical, base downType of current: sine-wave (sinusoidal) AC.Optimized lamp eXtreme Seal (XS) technology to withstand interior base temperatures of up to 450 degrees celsius.			

## **Electrical data**

Nominal Wattage	18000 W
Nominal Voltage	225 V
Current (A)	88 A
Type of Current	AC

# Light technical data

Luminous Flux	1600000
Rated Lumens	1600000
Luminous Efficacy (lm/W)	100 lm/W
Light Center Length - LCL (mm)	260 mm
Color Temperature	6000 K
Color Rendering Index	90
Average Rated Life	350 h

# **Physical attributes**

Base	GX51 Mogul Bipost	
Bulb Shape	T31	
Maximum Overall Length (mm)	495	
Length I max. (mm)	495 mm	
Diameter d (in)	3.937 in	
Diameter d (mm)	100.00 mm	
Distance a (mm)	260 mm	
Electrode Gap - cold (mm)	44 mm	
Reflector Coating	100.00	

## Product datasheet

## Additional product data

Operating Position	s135	
Maximum Base Temperature( °C)	450 C	
Cooling	Convection	
Hot Restart	Yes	
Method of Operation	SINGLE END	

#### **Download Data**

File



**Product Datasheet** 

317289\_TECHNICAL DATA SHEET HMI 18000 WSE GX51 (GB)

### **Packaging Information**

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54324	4008321098955	Shipping box (Case)	1	28.1 in x 9.4 in x 9.4 in	7.2 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.