

# **HALOLINE ECO 120 W 230 V R7S**

# HALOLINE ECO | Double ended halogen lamps with tube base



- General illumination
- Entrance lighting
- Pathway lighting
- · Garden lighting
- Traffic areas
- Shops
- · Restaurants, hotels and similar prestigious applications
- · Offices, public buildings

### **Product benefits**

- · Brilliant ECO accent lighting
- Direct replacement for standard tubular halogen lamps
- Significantly lower CO<sub>2</sub> emissions
- Lower thermal output (compared with the standard reference product)
- · No transformer required
- · Contains no mercury, can be thrown away with normal household waste

### **Product features**

• Average life: 2,000 h

Dimmable

• Color rendering index R<sub>a</sub>: 100

• Base: R7s



# **Technical data**

### **Electrical data**

Rated wattage	120 W
Nominal wattage	120 W
Nominal voltage	230 V
Power factor λ	1.00

# Light technical data

Light color as per EN 12464-1	Warm White
Nominal luminous flux	2250 lm
Rated luminous flux	2250 lm
Color temperature	2950 K
Color rendering index Ra	100
Starting time	0.0 s
Warm-up time (60 %)	0 s
Lumen main.fact.at end of nom.life time	0.85

# Dimensions & weight

Length	114.2 mm
Overall length	114.2 mm
Diameter	12.0 mm
Outer bulb	T12





Product line drawing with letters

### Colors & materials

Lamp mercury content	0.0 mg
Mercury-free	Yes

### Lifespan

Nominal lamp life time	2000 h
Rated lamp life time	2000 h
Number of switching cycles	1000000 1)

 $<sup>^{1)}</sup>$  At 1 min on / 3 min off

# Additional product data

Base (standard designation)	R7s
Footnote used only for product	Fuse protection with indicated values recommended acc. to IEC60357, EN60357/For outdoor applications and operation in damp locations special approved fixtures are required/Technical and light values are subject to be changed

# Product datasheet



# Capabilities

Dimmable	Yes
Burning position	Any
Fuse, quick-acting	2.0 A

### Certificates & standards

EEI – Energy Label	С
--------------------	---

# **Country specific categorizations**

ILCOS	HDG-120-230-R7s-114,2
Order reference	64696 ECO

# Product datasheet



# Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.