



TrueForce High Lumen PAR

25.5PAR30L/PER/830/S15/ND/120-277V 6/1FB

Philips LED TrueForce PAR high lumen lamps are the perfect transition from CDM lamps to LED.

Product data


General Information		Wattage Equivalent	
Base	E26 [Single Contact Medium Screw]	75 W	
EU RoHS compliant	Yes	Starting Time (Nom)	
Nominal Lifetime (Nom)	25000 h	0.5 s	
Switching Cycle	50000X	Warm Up Time to 60% Light (Nom)	
Technical Type	25.5-75W	0.5 s	
Light Technical		Power Factor (Nom)	
Color Code	830 [CCT of 3000K]	0.8	
Beam Angle (Nom)	15 °	Voltage (Nom)	
Initial lumen (Nom)	2500 lm	120-277 V	
Luminous Intensity (Nom)	16000 cd	Temperature	
Color Designation	White (WH)	T-Case Maximum (Nom)	
Correlated Color Temperature (Nom)	3000 K	95 °C	
Luminous Efficacy (rated) (Nom)	98.00 lm/W	Controls and Dimming	
Color Consistency	<4	Dimmable	
Color Rendering Index (Nom)	80	No	
LLMF At End Of Nominal Lifetime (Nom)	70 %	Approval and Application	
Operating and Electrical		Energy Efficiency Label (EEL)	
Input Frequency	50 to 60 Hz	Not applicable	
Power (Rated) (Nom)	25.5 W	Suitable For Accent Lighting	
		Yes	
		Energy Consumption kWh/1000 h	
		- kWh	
		Product Data	
		Order product name	
		25.5PAR30L/PER/830/S15/ND/120-277V	
		6/1FB	
		EAN/UPC - Product	
		046677534646	
		Order code	
		534644	

TrueForce High Lumen PAR

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929001917004

Net Weight (Piece)	0.290 kg
--------------------	----------



Dimensional drawing



PAR30L 27.5-W 2300lm 15D 3000K E26 ND


Product	25.5PAR30L/PER/830/S15/ND/120-277V 6/1FB
---------	--

Photometric data



LEDspot PAR30 1FB


LEDspot 25,5 PAR30L 830 S15




LEDspot 25,5 PAR30L 830 S15

TrueForce High Lumen PAR

Lifetime



LEDspot PAR30 1FB



LEDspot PAR30 1FB

