



LED B11

5B11/PER/UD/CL/G/E26/WGD 6/3PF T20

Philips LED B11 candles offer energy saving ambiance with the elegant effect of incandescent candles. These designs provides light in an omnidirectional manner, giving lighting designers a long life alternative to standard incandescent sources.

Product data


General information	
Cap-Base	E26 [Single Contact Medium Screw]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	15000 h
Switching Cycle	20000
Light technical	
Color Code	922-927 [CCT of 2200K-2700K]
Beam Angle (Nom)	300 °
Luminous Flux (Nom)	500 lm
Color Designation	Warm Glow(WG)
Correlated Color Temperature (Nom)	2200 2700 K
Luminous Efficacy (rated) (Nom)	100 lm/W
Color Consistency	<4
Color Rendering Index (Nom)	95
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and electrical	
Input Frequency	60 Hz
Power (Nom)	5 W
Lamp Current (Nom)	55 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.4 s

Power Factor (Nom)	0.7
Voltage (Nom)	120 V
Temperature	
T-Ambient (Max)	40 °C
T-Ambient (Min)	-20 °C
Controls and dimming	
Dimmable	Only with specific dimmers
Mechanical and housing	
Bulb Finish	Clear
Bulb Material	Glass
Bulb Shape	B11
Approval and application	
Energy Certifications	Energy Star
Product data	
Order product name	5B11/PER/UD/CL/G/E26/WGD 6/3PF T20
EAN/UPC - Product	50046677573374
Order code	929003085503
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6

LED B11

Material Nr. (12NC)	929003085503
Net Weight (Piece)	0.020 kg


Dimensional drawing




5B11/PER/UD/CL/G/E26/WGD 6/3PF T20

Product	D	C
5B11/PER/UD/CL/G/E26/WGD 6/3PF T20	35 mm	90 mm


Photometric data



Light Distribution Diagram




General uniform lighting




Spectral Power Distribution Colour

LED B11

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram

