

T8

14.5T8/COR/48-5CCT/MF18/G/DIM 25/1

Our TLEDs are available in InstantFit (Type A / Type C) or MainsFit (Ballast bypass / Type B) versions. The InstantFit lamps work on a broad variety of ballasts and LED drivers. Only InstantFit has over 15,000 lamp & ballast combinations delivering even light output, energy savings and a long lifetime. Our MainsFit products feature a double-ended design, simplifying installation while a proprietary safety circuit minimizes a shock risk. Lamp sizes range from 2-foot to 8-foot and U-bend with a variety of lumen outputs.

Product data

General information		Power (Rated) (Nom)	14.5 W
Base	G13 [Medium Bi-Pin Fluorescent]	Lamp Current (Max)	125 mA
EU RoHS compliant	Yes	Lamp Current (Min)	58 mA
Nominal Lifetime (Nom)	50000 h	Starting Time (Nom)	0.5 s
Switching Cycle	50000X	Warm Up Time to 60% Light (Nom)	0.5 s
Tier	CorePro	UL Type	TLED_Type B; UL classified double end
Light technical		Power Factor (Nom)	0.9
Color Code	3000K/3500K/4000K/5000K/6500K	Voltage (Nom)	120-277 V
Beam Angle (Nom)	240 °	Temperature	
Initial lumen (Nom)	1800 lm	T-Ambient (Max)	113 °F
Color Designation	3000K/3500K/4000K/5000K/6500K	T-Ambient (Min)	-4 °F
Correlated Color Temperature (Nom)	3000 3500 4000 5000 6500 K	T-Storage (Range)	-40 °C to 65 °C
Luminous Efficacy (rated) (Nom)	124.00 lm/W	T-Storage (Max)	149 °F
Color Consistency	6SCDM	T-Storage (Min)	-40 °F
Color Rendering Index (Nom)	80	T-Case Maximum (Nom)	158 °F
LLMF At End Of Nominal Lifetime (Nom)	70 %	Controls and dimming	
Operating and electrical		Dimmable	Only with specific dimmers
Input Frequency	50 to 60 Hz		


Mechanical and housing	
Bulb Finish	Frosted
Bulb Material	Glass
Product Length	47-1/4 in
Bulb Shape	Tube, double-ended

Approval and application	
Energy Saving Product	Yes
Approbation Marks	RoHS compliance UL certificate DLC compliance

Application conditions	
Ambient temperature range	-20 °C to 45 °C

Product data	
Order product name	14.5T8/COR/48-5CCT/MF18/G/DIM 25/1
EAN/UPC - Product	046677579678
Order code	579672
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	929003540104
Net Weight (Piece)	0.441 lb


Dimensional drawing




14.5T8/COR/48-5CCT/MF18/G/DIM 25/1

Product	D1	D2	A1	A2	A3
14.5T8/COR/48-5CCT/ MF18/G/DIM 25/1	1-1/16 in	1-1/8 in	47-3/16 in	47-1/2 in	47-3/4 in

Photometric data




Spectral Power Distribution Colour




General uniform lighting

Photometric data




Light Distribution Diagram


Lifetime




LumenVsTc



Life Expectancy Diagram




FailureRate



Lumen Maintenance Diagram

Lifetime



LifetimeVsTc

