



LED PAR30 S/L

10PAR30L/EXPERTCOLOR/F40/927/P/D/T/JA8

Philips LED spots with a single optic beam, provide a clean beam that's free from shadows with beam angles from 15 and 40 degrees to suit every general lighting application.

Product data

| General Information | |
|---------------------------------------|--------------------|
| Cap-Base | E26 |
| Nominal lifetime | 40,000 hour(s) |
| Switching Cycle | 50,000 |
| Lighting Technology | LED |
| Light Technical | |
| Color Code | 927 [CCT of 2700K] |
| Beam Angle (Nom) | 40 degree(s) |
| Luminous Flux | 950 lm |
| Luminous Intensity (Nom) | 2,000 cd |
| Color Designation | Warm White (WW) |
| Correlated Color Temperature (Nom) | 2700 K |
| Luminous Efficacy (rated) (Nom) | 95 lm/W |
| Color Consistency | <4 |
| Color rendering index (CRI) | 95 |
| LLMF At End Of Nominal Lifetime (Nom) | 70 % |
| Operating and Electrical | |
| Input Frequency | 60 Hz |
| Power Consumption | 10 W |
| Lamp Current (Nom) | 90 mA |
| Wattage Equivalent | 75 W |
| Starting Time (Nom) | 0.5 s |


| Warm-up time to 60% light | 0.5 s |
|------------------------------|----------------------------|
| Power Factor (Fraction) | 0.9 |
| Voltage (Nom) | 120 V |
| Temperature | |
| T-Case Maximum (Nom) | 163 °F |
| Controls and Dimming | |
| Dimmable | Only with specific dimmers |
| Mechanical and Housing | |
| Bulb Finish | Clear |
| Bulb Material | Plastic |
| Bulb Shape | PAR30L |
| UL Wet/ damp/ dry location | Damp location |
| Net Weight (Piece) | 0.507 lb |
| Approval and Application | |
| Suitable For Accent Lighting | Yes |
| EU RoHS compliant | Yes |
| T20 compliant | Yes |
| Ambient temperature range | -4 to +113 °F |

LED PAR30 S/L

| | |
|-------------------------------------|--|
| Application Conditions | |
| can it be used in closed luminaires | Yes |
| Product Data | |
| Order product name | 10PAR30L/EXPERTCOLOR/ F40/927/P/D/T/JA8 |
| Full product name | 10PAR30L/EXPERTCOLOR/ F40/927/P/D/T/JA8 |



| | |
|---------------------------------|----------------|
| Order code | 587626 |
| Material Nr. (12NC) | 929003755604 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 046677587628 |
| Numerator - Packs per outer box | 6 |
| EAN/UPC - Case | 50046677587623 |

Dimensional drawing



| Product | D | C |
|--|------------|------------|
| 10PAR30L/EXPERTCOLOR/F40/927/P/D/T/JA8 | 3-3/4 inch | 4-1/2 inch |

Photometric data




Accent Lighting Spots - 10PAR30L/EXPERTCOLOR/F40/927/P/D/T/JA8

Spectral Power Distribution Colour - 10PAR30L/EXPERTCOLOR/
F40/927/P/D/T/JA8


LED PAR30 S/L

Photometric data




Light Distribution Diagram - 10PAR30L/EXPERTCOLOR/
F40/927/P/D/T/JA8

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - 10PAR30L/EXPERTCOLOR/
F40/927/P/D/T/JA8

