



# Actinic BL PL-S/PL-L

# PL-L 36W/10/4P 1CT/25

With an optimized spectrum matching the eye sensitivity of the housefly, Actinic BL TL(-K)/TL-D(-K)/TL-E/PL-S and PL-L lamps are perfect for attracting insects. They have virtually no UV-B output, and so are perfectly safe. What's more, with the lowest mercury content in the industry and being 100% lead-free, these lamps represent a very good environmental choice. Furthermore, the availability of a wide range of form factors (straight (T5, T8, T12), circular (TL-E) and compact (PL-S/PL-L)) and wattages enables you to make all kinds of designs for your electronic fly killers.

#### **Product data**

General Information			
Cap-Base	2G11 [ 2G11] 2xT16 Insect traps 2000 h		
Bulb Shape			
Main Application			
Life To 50% Failures (Nom)			
Useful Life (Nom)	2000 h		
Light Technical			
Color Code	210 [ leadfree 360 glass (10)]		
Chromaticity Coordinate X (Nom)	220		
Chromaticity Coordinate Y (Nom)	215		
LLMF 2000 h Rated	20 %		
Operating and Electrical			
Power (Rated) (Nom)	36 W		
amp Current (Nom)	0.435 A		
/oltage (Nom)	106 V		


Mechanical and Housing				
Cap-Base Information	4 Pins			
Approval and Application				
Mercury (Hg) Content (Max)	2.1 mg			
Mercury (Hg) Content (Nom)	2.0 mg			
UV				
UV-A Radiation 100Hr (IEC)	8.5 W			
Product Data				
Full product code	871150026481740			
Order product name	PL-L 36W/10/4P 1CT/25			
EAN/UPC - Product	8711500264817			
Order code	927903421007			
Numerator - Quantity Per Pack	1			
Numerator - Packs per outer box	25			
Material Nr. (12NC)	927903421007			
Net Weight (Piece)	104.000 g			

Datasheet, 2017, February 1 data subject to change

## Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### **Dimensional drawing**



Product	D1	D	Α	В	С	
PL-L 36W/10/4P 1CT/25	18 mm	39 mm	384.2 mm	410 mm	416.6 mm	

#### Photometric data

