



# Optanium T8 Programmed Start

### OPTANIUM IOP3PSP32SC35I

Philips Advance Optanium high-efficiency electronic ballasts are engineered to optimize lighting performance and maximize energy savings. These ballasts provide an unparalleled package of features and benefits to support the wide variety of T8 fluorescent lamps.

#### **Product data**

General Information	
Lamp Type	F32T8
Number of Lamps	2/3 piece/unit
Ballast Type	Electronic Fluorescent
Base Model	IOP3PSP32SC
Suitable For Outdoor Use	Yes
Automatic Restart	Yes
Operating and Electrical	
Input Voltage	120 to 277 V
Input Frequency	50 to 60 Hz
Total Harmonic Distortion USA	10 %
Ignition Method	Programmed Start
Crestfactor (Nom)	1.6
Ignition Time (Nom)	1.5 s
Ballast Factor (Nom)	0.88
Power Factor (Nom)	0.98
Input Current (Max)	0.71 A
Input Current (Min)	0.31 A
Input Power (Nom)	85-84 W

Rated Lamp Power	32 W
Wiring	
Color Input Terminals	No terminals
Color Output Terminals	No terminals
Wire Striplength	0.50/0.375 mm
Lamp Connection	Parallel
Wire Length by Color	See data sheet
Wire Gauge (Nom)	18AWG mm
Wire Type	Solid
Remote Wiring Configuration Allowed	Yes
Tandem Wiring Configuration Allowed	Yes
Through Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote Wiring	20'
Max Ballast-Lamp Distance Tandem Wiring	Any = 20'
Max Ballast-Lamp Distance Through Wiring	Any = 20'
Connector Type	No connector
Temperature	
T-Case Maximum (Nom)	70 °C


Datasheet, 2015, November 29 data subject to change

# **Optanium T8 Programmed Start**

Mechanical and Housing       Housing Material     Metal       Housing     SC       Housing Dimensions     9.5" x 1.7" x 1.18"       Approval and Application     EMC Immunity Standard       EMC Immunity Standard     FCC Non-Consumer       Approval Marks     CSA certificate UL certificate CEC Listing CEE Rated NEMA Premium RoHS Compliant       Hum And Noise Level     A       UL Recognized     No		
Housing SC Housing Dimensions 9.5" x 1.7" x 1.18"  Approval and Application  EMC Immunity Standard FCC Non-Consumer  Approval Marks CSA certificate UL certificate CEC Listing CEE Rated NEMA Premium RoHS Compliant  Hum And Noise Level A	Mechanical and Housing	
Housing Dimensions  9.5" x 1.7" x 1.18"  Approval and Application  EMC Immunity Standard  FCC Non-Consumer  Approval Marks  CSA certificate UL certificate CEC Listing CEE Rated NEMA Premium RoHS Compliant  Hum And Noise Level  A	Housing Material	Metal
Approval and Application  EMC Immunity Standard FCC Non-Consumer  Approval Marks CSA certificate UL certificate CEC Listing CEE Rated NEMA Premium RoHS Compliant  Hum And Noise Level A	Housing	SC
EMC Immunity Standard FCC Non-Consumer  Approval Marks CSA certificate UL certificate CEC Listing CEE Rated NEMA Premium RoHS Compliant  Hum And Noise Level A	Housing Dimensions	9.5" x 1.7" x 1.18"
EMC Immunity Standard FCC Non-Consumer  Approval Marks CSA certificate UL certificate CEC Listing CEE Rated NEMA Premium RoHS Compliant  Hum And Noise Level A		
Approval Marks  CSA certificate UL certificate CEC Listing CEE Rated NEMA Premium RoHS Compliant  Hum And Noise Level  A	Approval and Application	
Rated NEMA Premium RoHS Compliant  Hum And Noise Level A	EMC Immunity Standard	FCC Non-Consumer
Hum And Noise Level A	Approval Marks	CSA certificate UL certificate CEC Listing CEE
		Rated NEMA Premium RoHS Compliant
UL Recognized No	Hum And Noise Level	Α
	UL Recognized	No

Product Data	
Order product name	OPTANIUM IOP3PSP32SC35I
EAN/UPC - Product	781087081631
Order code	913710894401
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	913710894401
Net Weight (Piece)	0.441 kg

## Dimensional drawing



FIFE	RALLA	ST (3)	F32T8	120-277V

Product	A1	A2	B1	C1
OPTANIUM IOP3PSP32SC35I	9.5 in	8.90 in	1.7 in	1.18 in

