



MSR Gold™ MiniFastFit (Touring/Stage)

MSR Gold™ 700 MiniFastFit 1CT/16

Thanks to the specially designed lamp base, the MSR Gold™ MiniFastFit takes just seconds to replace, to help ensure non-stop clubbing entertainment. In addition, the innovative gold plated pins ensure excellent current transfer to prolong lamp and lamp holder lifetimes and thereby reduce lamp replacement costs. Easy handling and small compact fixture designs are allowed by the lamps compact size, while the very short arc provides a high perceived brightness and high beam intensity.

Product data

General Information		Operating and Electrical	
Cap-Base	PGJX28 [PGJX28]	Power (Rated) (Nom)	700 W
Operating Position	UNIVERSAL [Any or Universal (U)]	Lamp Current (Nom)	10.8 A
Main Application	Entertainment	Ignition Supply Voltage (Min)	220 V
Life To 50% Failures (Nom)	750 h		
System Description	MiniFastFit		
Light Technical		Controls and Dimming	
Color Code	- [Not Specified]	Dimmable	Yes
Luminous Flux (Min)	44500 lm		
Luminous Flux (Nom)	49000 lm		
Chromaticity Coordinate X (Nom)	289		
Chromaticity Coordinate Y (Nom)	308		
Correlated Color Temperature (Nom)	6000 K		
Luminous Efficacy (rated) (Nom)	70 lm/W		
Color Rendering Index (Nom)	65		
		Mechanical and Housing	
		Cap-Base Information	PGJX28
		Luminaire Design Requirements	
		Bulb Temperature (Max)	950 °C
		Pinch Temperature (Max)	450 °C
		Product Data	
		Full product code	871829114103700

MSR Gold™ MiniFastFit (Touring/Stage)


Order product name	MSR Gold™ 700 MiniFastFit 1CT/16
EAN/UPC - Product	8718291141037
Order code	928194105114
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	16

Material Nr. (12NC)	928194105114
Net Weight (Piece)	0.053 kg

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSR Gold™	23 mm	3.5	55 mm	57 mm	56	116 mm	36.5	36	35.3
700 MiniFastFit		mm			mm		mm	mm	mm
1CT/16									

MSR GOLD 700 MiniFastFit

