

Description:

Apogee Collection 15" LED Flush Mount

Specifications:

- Etched Glass Shade
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 14.875 in W., 0.875 in ht., 14.875 in depth
- Mounting strap for outlet box included
- 6 in of wire supplied

Performance:

Number of Modules	1
Input Power	28.3 W
Input Voltage	120-277 VAC
Input Frequency	60 Hz
Lumens/LPW (Delivered)	1,660/59.5 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	58000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class A
Max. Operating Temp	30°C
Warranty	5-year Limited Warranty
Labels	cETLus Damp Location Listed
	Meets California Title 24 JA8-2016

P350070-009-30



Dimensions:

Diameter: 15 in
 Height: 3-11/16 in

Etched Glass Shade
 Width: 12-3/4 in
 Height: 2-1/8 in



P350070-009-30

Dimming Notes:

P350070-009-30 is designed to be compatible with many 0-10V controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron_NFTV

Lutron_NTFTV

Lutron_DVTV

Leviton_AWSMT-7DW

Leviton_IP710

Lithonia_ISD BC

Pass & Seymour_CD4FB

Wattstopper_ADF-120277

Hunt Dimming_PS-010-120V

Hunt Dimming_PS010 277V

Lightolier Controls_MP1500FAM120

Lightolier Controls_ZP600FAM120

Synergy Lighting Controls_V2000FAMU

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.