

## Elevate

Flush-Mount Mounted • Damp Location Listed **PROGRESS LED**

### Description:

Elevate Collection 13" LED Flush Mount

### Specifications:

- White Glass Bowl
- Dimmable to 10% brightness (See Dimming Notes)
- Fixture covers a standard 4" recessed outlet box: 13 in W., 1.625 in ht., 13 in depth
- Mounting strap for outlet box included
- 6 in of wire supplied

### Performance:

Number of Modules	1
Input Power	17 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	1,452/83 (LM-82)
Lumens/LPW (Delivered)	670/38.3 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60000 (L70/TM-21)
EMI/RFI	Meets FCC Title 47, Part 15 Class B
Max. Operating Temp	30°C
Warranty	5-year Limited Warranty
Labels	cCSAus Damp Location Listed
	Meets California Title 24 JA8-2016

# P350105-109-30



### Dimensions:

Diameter: 13 in  
Height: 5-1/4 in

White Glass Bowl  
Width: 12-1/4 in  
Height: 4-3/8 in



# P350105-109-30

## Dimming Notes:

P350105-109-30 is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

## Dimming Controls:

Lutron_Diva DVELV-300P
Lutron_Nova T NTELV-300
Lutron_Caseta
Lutron_Ariadni AY-600P
Leviton_Illumatech IPI06-1LZ
Lutron_Lumea LG-603PG
Leviton_SureSlide 6672
Leviton_SureSlide 6674
Lutron_Skylark Contour CTCL-153P
Lutron_Diva DVCL-153P
Pass & Seymour_Harmony DCL453PTCCCV6
Lutron_Toggler TGCL-153P
Lutron_Maestro MACL-153M
Lutron_Ariadni AYLV-600P
Lutron_Maestro MA-600
Lutron_Nova T NTLV-600
Lutron_Maestro MAELV-600
Lutron_spacer/system SPSELV-600
Leviton_Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.